



Home: PCB Receptacles >

Part Number: 22-16-1073

2.50mm Pitch KK® PC Board Connector, Right Angle, 0.50µm Gold (Au), 7 Circuits



Series image - Reference only

Status:	OBsolete
Replacement:	Contact Molex
Series:	7534
Category:	PCB Receptacles
Overview:	KK® Interconnect System - Molex
Engineering/Old PN:	753407AG

[CHECK DISTRIBUTOR INVENTORY](#)[Add to My Parts](#)[Email this page](#)Go to [Part Detail](#) ▾**Mates With Part(s):**[6494](#), [3094](#), [3202](#), [3022](#)**Product Environmental Compliance**[EU ELV](#):Product not active[EU RoHS](#):Product not active[EU RoHS Phthalates](#):Product not active[China RoHS](#):[REACH SVHC](#):Product not active[Low-Halogen Status](#):Product not active[EU RoHS Certificate of Compliance \(PDF\)](#)[Multiple Part Product Compliance Statements](#)

EU RoHS, REACH SVHC, & Low-Halogen

[Multiple Part Industry Compliance Documents](#)

*IPC 1752A Class C

*IPC 1752A Class D

*Molex Product Compliance Declaration

Application Tooling**FAQ**

Tooling specifications and manuals are found by selecting the products below.

Crimp Height Specifications are then contained in the Application Tooling Specification document.

Previously Available Application Tooling[Check our list of old tooling that used to be available for this part](#)Questions on Product Environmental Compliance? Email ProductCompliance@molex.comRequest Molex's CMRT from conflictminerals@molex.com**Part Detail**[COLLAPSE ALL](#)**General**

Status	Obsolete
Category	PCB Receptacles
Series	7534
Application	Board-to-Board, Signal
Overview	KK® Interconnect System - Molex
Product Name	KK®
UPC	800753738317

Physical

Circuits (Loaded)	7
Circuits (maximum)	7
Color - Resin	Natural (White)
Durability (mating cycles max)	50
Flammability	94V-0
Glow-Wire Compliant	No
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Gold
Material - Resin	Nylon
Number of Rows	1
Orientation	Right Angle
PC Tail Length	3.60mm
PCB Locator	No
PCB Retention	Yes
PCB Thickness - Recommended	1.60mm
Packaging Type	Tray
Pitch - Mating Interface	2.50mm
Plating min - Mating	0.508µm
Plating min - Termination	0.051µm
Polarized to PCB	Yes
Temperature Range - Operating	0°C to +75°C
Termination Interface: Style	Through Hole

Electrical

(Please review the Product Specification for specific details.)

Current - Maximum per Contact	2.5A
Voltage - Maximum	250V

Agency CertificationPlease find UL Certificates by searching the UL Database using the Molex Series Number. [Click here to visit the UL Database](#)

CSA	LR19980
UL	E29179

Material Info

Engineering Number	753407AG
--------------------	----------