

TOSHIBA BIPOLAR DIGITAL INTEGRATED CIRCUIT SILICON MONOLITHIC

TD62384APG, TD62384AFG TD62385APG, TD62385AFG

8CH LOW INPUT ACTIVE DARLINGTON SINK DRIVER



The TD62384APG / AFG and TD62385APG / AFG are non-inverting transistor arrays, which are comprised of eight NPN darlington output stages and PNP input stages. These devices can be operated by source input voltage and are suitable for operations with a 5-V general purposed logic IC such as 5-V TTL, 5-V CMOS and 5-V Microprocessor which have sink current output drivers. Please observe the thermal condition for using. This devices are a product for the Pb free(Sn-Ag).

FEATURES

- Output current (single output) 500 mA (Max)
- High sustaining voltage 50 V (Min)
- Low level active input
- Inputs compatible with 5-V TTL and 5-V CMOS
- Package type-APG : DIP-18 pin
- Package type-AFG : SOP-18 pin



TYPE	$V_{IN(ON)}$
TD62384APG / AFG	$-20\text{ V} \sim V_{CC} - 2.8\text{ V}$
TD62385APG / AFG	$0\text{ V} \sim V_{CC} - 3.7\text{ V}$

PIN CONNECTION (TOP VIEW)



Weight
DIP18-P-300-2.54D : 1.47 g (Typ.)
SOP18-P-375-1.27 : 0.41 g (Typ.)

SCHEMATICS (EACH DRIVER)



Note : The input and output parasitic diodes cannot be used as clamp diodes.

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Supply Voltage	V_{CC}	-0.5~7.0	V
Output Sustaining Voltage	$V_{CE(SUS)}$	-0.5~50	V
Output Current	I_{OUT}	500	mA / ch
Input Voltage	V_{IN} (Note 1)	-22~ $V_{CC} + 0.5$	V
	V_{IN} (Note 2)	-0.5~7	
Input Current	I_{IN}	-10	mA
Power Dissipation	APG	P_D (Note 3)	W
	AFG		
Operating Temperature	T_{opr}	-40~85	°C
Storage Temperature	T_{stg}	-55~150	°C

Note 1: TD62384APG / AFG

Note 2: TD62385APG/ AFG

Note 3: Delated above 25°C in the proportion of 11.7 mW / °C (APG-Type), 7.7 mW / °C (AFG-Type).

RECOMMENDED OPERATING CONDITIONS (Ta = -40~85°C)


CHARACTERISTIC	SYMBOL	CONDITION	MIN	TYP.	MAX	UNIT
Supply Voltage	V_{CC}	—	4.5	5.0	5.5	V
Output Sustaining Voltage	$V_{CE(SUS)}$	—	0	—	50	V
Output Current	APG	$T_{pw} = 25 \text{ ms}$, Duty = 50% 8 Circuits, Ta = 85°C, Tj = 120°C	0	—	115	mA / ch
	AFG		0	—	78	
		$T_{pw} = 25 \text{ ms}$, Duty = 10% 1 Circuit	0	—	400	
Input Voltage	TD62384	V_{IN}	-20	—	V_{CC}	V
	TD62385		0	—	5.5	
Power Dissipation	APG	P_D	—	—	0.52	W
	AFG		—	—	0.35	

ELECTRICAL CHARACTERISTIC (Ta = 25°C)


CHARACTERISTIC			SYMBOL	TEST CIR- CUIT	TEST CONDITION	MIN	TYP.	MAX	UNIT	
Output Leakage Current			I _{CEX}	1	V _{CC} = 5.5 V, I _{IN} = 0 Ta = 85°C	V _{OUT} = 50 V	—	—	100	μA
Output Saturation Voltage			V _{CE (sat)}	2	V _{CC} = 4.5 V, I _{OUT} = 350 mA V _{IN} = V _{IN (ON)} MAX.		—	1.4	2.0	V
Input Current		(Output On)	I _{IN (ON)}	3	V _{CC} = 5.5 V, V _{IN} = 0.4 V		—	-0.32	-0.45	mA
		V _{CC} = 5.5 V, V _{IN} = -20 V			—	—	-2.6			
		(Output Off)	I _{IN (OFF)}	4	—		—	—	-4.0	μA
Input Voltage	(Output on)	TD62384	V _{IN (ON)}	5	—		—	—	V _{CC} - 2.8	V
		TD62385			—		—	—	V _{CC} - 3.7	
Supply Current			I _{CC (ON)}	6	V _{CC} = 5.5 V, V _{IN} = 0		—	17	22	mA
			I _{CC (OFF)}		V _{CC} = 5.5 V, V _{IN} = V _{CC}		—	—	100	μA
Turn-On Delay			t _{ON}	7	V _{CC} = 5 V, V _{OUT} = 50 V R _L = 163 Ω, C _L = 15 pF		—	0.1	—	μs
Turn-Off Delay			t _{OFF}				—	3	—	

TEST CIRCUIT


1. I_{CEX}




2. $V_{CE(sat)}$




3. $I_{IN(ON)}$




4. $I_{IN(OFF)}$





5. $V_{IN(ON)}$



6. I_{CC}



7. t_{ON}, t_{OFF}



Note 1: Pulse Width 50 μ s, Duty Cycle 10%
Output Impedance 50 Ω , $t_r \leq 5$ ns, $t_f \leq 10$ ns







Note 2: C_L includes probe and jig capacitance.

PRECAUTIONS for USING

This IC does not integrate protection circuits such as overcurrent and overvoltage protectors.

Thus, if excess current or voltage is applied to the IC, the IC may be damaged. Please design the IC so that excess current or voltage will not be applied to the IC.


Utmost care is necessary in the design of the output line, V_{CC} and GND line since IC may be destroyed due to short-circuit between outputs, air contamination fault, or fault by improper grounding.



PACKAGE DIMENSIONS

DIP18-P-300-2.54D

Unit: mm







Weight: 1.47 g (Typ.)

PACKAGE DIMENSIONS

SOP18-P-375-1.27

Unit: mm



Weight: 0.41 g (Typ.)

About solderability, following conditions were confirmed

- Solderability

- (1) Use of Sn-63Pb solder Bath

- solder bath temperature = 230°C
 - dipping time = 5 seconds
 - the number of times = once
 - use of R-type flux

- (2) Use of Sn-3.0Ag-0.5Cu solder Bath

- solder bath temperature = 245°C
 - dipping time = 5 seconds
 - the number of times = once
 - use of R-type flux

RESTRICTIONS ON PRODUCT USE

030619EBA

- The information contained herein is subject to change without notice.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- TOSHIBA products should not be embedded to the downstream products which are prohibited to be produced and sold, under any law and regulations.