

To all our customers

Regarding the change of names mentioned in the document, such as Hitachi Electric and Hitachi XX, to Renesas Technology Corp.

The semiconductor operations of Mitsubishi Electric and Hitachi were transferred to Renesas Technology Corporation on April 1st 2003. These operations include microcomputer, logic, analog and discrete devices, and memory chips other than DRAMs (flash memory, SRAMs etc.) Accordingly, although Hitachi, Hitachi, Ltd., Hitachi Semiconductors, and other Hitachi brand names are mentioned in the document, these names have in fact all been changed to Renesas Technology Corp. Thank you for your understanding. Except for our corporate trademark, logo and corporate statement, no changes whatsoever have been made to the contents of the document, and these changes do not constitute any alteration to the contents of the document itself.

Renesas Technology Home Page: <http://www.renesas.com>

Renesas Technology Corp.
Customer Support Dept.
April 1, 2003

Cautions

Keep safety first in your circuit designs!

1. Renesas Technology Corporation puts the maximum effort into making semiconductor products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with semiconductors may lead to personal injury, fire or property damage.

Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (i) placement of substitutive, auxiliary circuits, (ii) use of nonflammable material or (iii) prevention against any malfunction or mishap.

Notes regarding these materials

1. These materials are intended as a reference to assist our customers in the selection of the Renesas Technology Corporation product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Renesas Technology Corporation or a third party.
2. Renesas Technology Corporation assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

3. All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Renesas Technology Corporation without notice due to product improvements or other reasons. It is therefore recommended that customers contact Renesas Technology Corporation or an authorized Renesas Technology Corporation product distributor for the latest product information before purchasing a product listed herein.

The information described here may contain technical inaccuracies or typographical errors.

Renesas Technology Corporation assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.

Please also pay attention to information published by Renesas Technology Corporation by various means, including the Renesas Technology Corporation Semiconductor home page (<http://www.renesas.com>).

4. When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Renesas Technology Corporation assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.
5. Renesas Technology Corporation semiconductors are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake. Please contact Renesas Technology Corporation or an authorized Renesas Technology Corporation product distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or systems for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
6. The prior written approval of Renesas Technology Corporation is necessary to reprint or reproduce in whole or in part these materials.
7. If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination.
Any diversion or reexport contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.
8. Please contact Renesas Technology Corporation for further details on these materials or the products contained therein.

HA12228F/HA12229F

Audio Signal Processor for Car Deck
(Decode only Dolby B-type NR* with PB Amp.)



ADE-207-325A

2nd Edition
Dec. 2000

Description

HA12228F/HA12229F are silicon monolithic bipolar IC providing Dolby noise reduction system*, music sensor, PB equalizer system in one chip.

Notes: 1. Dolby is a trademark of Dolby Laboratories Licensing Corporation.

A license from Dolby Laboratories Licensing Corporation is required for the use of this IC.

2. HA12229F is not built-in Dolby B-NR.

Functions

- PB equalizer $\times 2$ channel
- Music sensor $\times 1$ channel
- Dolby B-NR (Only HA12228F) $\times 2$ channel
- Line mute SW $\times 2$ channel

Features

- Different type of PB equalizer characteristics selection (120 μ s/70 μ s) is available with fully electronic control switching built-in.
- Easy interface with the PB head. (The PB-EQ resistance self-containing)
- Changeable to Forward, Reverse-mode for PB head with fully electronic control switching built-in.
- Available to change music sensing level by external resistor.
- Available to change response of music sensor by external capacitor.
- Music sensing level, built-in switch to change a band (MSG_v).
- NR ON/OFF fully electronic control switching built-in. (Only HA12228F)
- Line mute control switching built-in.
- Available to connect direct with MPU.
- These ICs are strong for a cellular phone noise.

HA12228F/HA12229F

Ordering Information

Operating Voltage

Product	Min	Max	Unit
HA12228F	6.5	12	V
HA12229F			

Note: 1. These ICs are designed to operate on single supply.





Standard Level

Product	Package	PB-OUT Level
HA12228F	FP-40B	300 mVrms
HA12229F		

Function

Product	PB-EQ	Music Sensor	Mute	Dolby B-NR
HA12228F	○	○	○	○
HA12229F	○	○	○	×





Pin Description, Equivalent Circuit ($V_{CC} = 9\text{ V}$ single supply, $T_a = 25^\circ\text{C}$, No Signal, The value in the table shows typical value.)

Pin No.	Terminal Name	Note	Equivalent Circuit	Description
13	MSI	$V = V_{CC}/2$		MS input ^{*1}
4	TAI(L)			Tape input
27	TAI(R)			
23 ^{*2}	DET(R)	$V = 2.5\text{ V}$		Time constant pin for NR rectifier
8 ^{*2}	DET(L)			
26	RIP	$V = V_{CC}/2$		Ripple filter
5 ^{*3}	Bias	$V = 0.28\text{ V}$		Dolby bias current input
14	MSDET	—		Time constant pin for MS rectifier ^{*1}

- Notes: 1. MS: Music Sensor
 2. Non connection regarding HA12229F.
 3. Test pin regarding HA12229F. Usually open or pull down to GND with 18 kΩ.





HA12228F/HA12229F

Pin Description, Equivalent Circuit ($V_{cc} = 9\text{ V}$ single supply, $T_a = 25^\circ\text{C}$, No Signal, The value in the table shows typical value.) (cont.)

Pin No.	Terminal Name	Note	Equivalent Circuit	Description
25	PBOUT(R)	$V = V_{cc}/2$		PB output
6	PBOUT(L)			
12	MAOUT			MS amp. output *1
29	EQOUT(R)	$V = V_{cc}/2$		Equalizer output
2	EQOUT(L)			
30	M-OUT(R)	$V = V_{cc}/2$		Equalizer output for time constant
1	M-OUT(L)			
37	FIN(R)	—		Equalizer input (FORWARD)
39	FIN(L)			
35	RIN(R)	—		Equalizer input (REVERSE)
33	RIN(L)			

Note: 1. MS: Music Sensor


Pin Description, Equivalent Circuit ($V_{CC} = 9\text{ V}$ single supply, $T_a = 25^\circ\text{C}$, No Signal, The value in the table shows typical value.) (cont.)


Pin No.	Terminal Name	Note	Equivalent Circuit	Description
20	MUTE ON/OFF	—		Mode control input
21 ^{*1}	NR ON/OFF			
19	120/70			
17	F/R			
18	S/R(MS G_v)			
16	MSOUT	—		MS output (to MPU) ^{*2}
10	MS G_v (S)	$V = V_{CC}/2$		MS gain terminal ^{*2}
11	MS G_v (R)			
31	NFI(R)	$V = V_{CC}/2$		Equalizer output for time constant
40	NFI(L)			

Notes: 1. Non connection regarding HA12229F.
2. MS: Music Sensor

HA12228F/HA12229F

Pin Description, Equivalent Circuit ($V_{cc} = 9\text{ V}$ single supply, $T_a = 25^\circ\text{C}$, No Signal, The value in the table shows typical value.) (cont.)

Pin No.	Terminal Name	Note	Equivalent Circuit	Description
32	VREF1	$V = V_{cc}/2$	HA12228F 	Reference output
38	VREF2			
28	VREF3			
3	VREF4			




15	V_{cc}	—	V_{cc} pin
36	GND	—	GND pin
7	NC	—	
9			
22			
24			
34			


Note: 1. R_{AL} : Parasitic metal resistance

Block Diagram

HA12228F



HA12229F



Functional Description

Power Supply Range

HA12228F/HA12229F are provided with three line output level, which will permit on optimum overload margin for power supply conditions. And these are designed to operate on single supply only.

Table 1 Supply Voltage Range

Product	Single Supply
HA12228F	6.5 V to 12.0 V
HA12229F	

Note: The lower limit of supply voltage depends on the line output reference level.
 The minimum value of the overload margin is specified as 12 dB by Dolby Laboratories.

Reference Voltage

These devices provide the reference voltage of half the supply voltage that is the signal grounds. As the peculiarity of these devices, the capacitor for the ripple filter is very small about 1/100 compared with their usual value. The block diagram is shown as figure 1.




Figure 1a The HA12228F Block Diagram of Reference Supply Voltage




Figure 1b The HA12229F Block Diagram of Reference Supply Voltage

Operating Mode Control

HA12228F/HA12229F provides fully electronic switching circuits. And each operating mode control are controlled by parallel data (DC voltage).

When a power supply of this IC is cut off, for a voltage, in addition to a mode control terminal even though as do not destruct it, in series for resistance.

Table 2 Threshold Voltage (V_{TH})

Pin No.	Lo	Hi	Unit	Test Condition
17, 18, 19, 20, 21*	-0.2 to 1.0	3.5 to V_{CC}	V	Input Pin Measure


Note: * Non connection regarding HA12229F.

Table 3 Switching Truth Table

Pin No.	Pin Name	Lo	Hi
17	Forward/Reverse	Forward	Reverse
18	Search/Repeat	Search (FF or REV)	Repeat (Normal speed)
19	120 μ /70 μ	70 μ (Metal or Chrome)	120 μ (Normal)
20	MUTE ON/OFF	MUTE-OFF	MUTE-ON
21*	NR ON/OFF	NR-OFF	NR-ON

Notes: * Non connection regarding HA12229F.

- Each pins are on pulled down with 100 k Ω internal resistor.
Therefore, it will be low-level when each pins are open.
- Over shoot level and under shoot level of input signal must be the standardized.
(High: V_{CC} , Low: -0.2 V)
- Reducing pop noise is so much better for 10 k Ω to 22 k Ω resisitor and 1 μ F to 22 μ F capacitor shown figure 2.

**Figure 2 Interface for Reduction of Pop Noise**

Input Block Diagram and Level Diagram




Figure 3 Input Block Diagram

Adjustment of Playback Dolby Level

After replace R5 and R6 with a half-fix volume of 10 kΩ, adjust playback Dolby level.

The Sensitivity Adjustment of Music Sensor

Adjusting MS Amp. gain by external resistor, the sensitivity of music sensor can set up. The music sensor block diagram is shown in figure 4, and frequency response is shown in figure 5.




Figure 4 Music Sensor Block Diagram




Figure 5 Frequency Response

1. Search mode

$$G_{V1} = 20\text{dB} + 20 \log \left(1 + \frac{90\text{k}}{\text{REX2}} \right) \text{ [dB]}$$
$$f_1 = \frac{1}{2\pi \cdot \text{CEX2} \cdot \text{REX2}} \text{ [Hz]}, \quad f_2 = 25\text{k} \text{ [Hz]}$$

2. Repeat mode

$$G_{V2} = 20\text{dB} + 20 \log \left(1 + \frac{90\text{k}}{\text{REX1}} \right) \text{ [dB]}$$
$$f_3 = \frac{1}{2\pi \cdot \text{CEX1} \cdot \text{REX1}} \text{ [Hz]}, \quad f_4 = 25\text{k} \text{ [Hz]}$$

G_VIA: L-R signal addition circuit gain.

The sensitivity of music sensor (S) is computed by the formula mentioned below.

$$S = - \left(G_V^{*1} - 20 \log \frac{130^{*3}}{30^{*2}} \right) = 12.7 - G_V \text{ [dB]}$$

- Note: 1. Search mode: G_{V1}, Repeat mode: G_{V2}
2. Standard level of TAI pin (Dolby level correspondence) = 30 mVrms
3. Standard sensing level of music sensor = 130 mVrms

Item	REX1, 2	CEX1, 2	G _{V1, 2}	f _{1, 3}	f _{2, 4}	S (one side channel)	S (both channel)
Search mode	24 kΩ	0.01 μF	33.5 dB	663 Hz	25 kHz	−14.8 dB	−20.8 dB
Repeat mode	2.4 kΩ	1 μF	51.7 dB	66.3 Hz	25 kHz	−33.0 dB	−39.0 dB

Note: S is 6 dB down in case of one-side channel. And this MS presented hysteresis lest MSOUT terminal should turn over again High level or Low level, in case of thresh S level constantly.

Music Sensor Time Constant

1. Sensing no signal to signal (Attack) is determined by C6, 0.01 μF to 1 μF capacitor C6 can be applicable.
2. Sensing signal to no signal (Recovery) is determined by C6 and R11, however preceding (1), 100 kΩ to 1 MΩ can be applicable.

Music Sensor Output (MSOUT)

As for the internal circuit of music sensor block, music sensor output pin is connected to the collector of NPN type directly, therefore, output level will be “high” when sensing no signal. And output level will be “low” when sensing signal.

$$I_L = \frac{DV_{CC} - \text{MSOUT}_{LO}^{*}}{R_L}$$

* MSOUT_{LO} : Sensing signal (about 1V)

Note: 1. Supply voltage of MSOUT pin must be less than V_{cc} voltage.

The Tolerances of External Components for Dolby NR (Only HA12228F)

For adequate Dolby NR tracking response, take external components shown below.
Also, leak is small capacity, and please employ a good quality object.




Figure 6 Tolerance of External Components

Countermeasure of a Cellular Phone Noise

This IC have reinforced a cellular phone noise countermeasure, to show it hereinafter.

However, it is presumed that this effect change it greatly, by a mount set.

Please sufficiently examine an arrangement of positions, shield method, wiring pattern, in order to obtain a maximum effect.

A high terminal of a noise sensitivity of this IC is FIN, RIN, NFI and RIP.




Figure 7 Test Circuit




Figure 8 EQOUT Noise Output vs. Transmission Frequency Characteristic




Figure 9 EQOUT Noise Output vs. Transmission Signal Input Level Characteristic

Absolute Maximum Ratings ($T_a = 25^{\circ}\text{C}$)

Item	Symbol	Rating	Unit	Note
Maximum supply voltage	V_{cc} Max	16	V	
Power dissipation	P_d	400	mW	$T_a \leq 85^{\circ}\text{C}$
Operating temperature	T_{opr}	-40 to $+85$	$^{\circ}\text{C}$	
Storage temperature	T_{stg}	-55 to $+125$	$^{\circ}\text{C}$	

HA12228F/HA12229F

Electrical Characteristics

HA12228F

(Ta = 25°C, V _{CC} = 9 V, Dolby level 0 dB = PBOUT level 0 dB = PBOUT level 0 dB = 300 mVrms, EQOUT level 0 dB = 60 mVrms)																		
Item	Symbol	Test Condition										Application Terminal						
		IC Condition				Specification						Input		Output		COM Remark		
		NR ON/OFF	MUTE ON/OFF	120μ/70μ	SER/REP	FOR/REV	f _{in} (Hz)	PBOUT level (dB)	EQOUT level (dB)	Other	Min	Typ	Max	Unit	R		L	R
Quiescent current	I _Q	OFF	OFF	70μ	SER	FOR	—	—	No signal	4.0	9.5	15.0	mA	—	—	—	—	15
Input Amp. gain	G _v /A	OFF	OFF	—	—	—	1k	0	—	19.0	20.0	21.0	dB	27	4	25	6	
	DEC 2k (1)	ON	OFF	—	—	—	2k	-20	—	-5.8	-4.3	-2.8	dB	27	4	25	6	
	DEC 2k (2)	ON	OFF	—	—	—	2k	-30	—	-10.0	-8.5	-7.0	dB	27	4	25	6	
	DEC 5k (1)	ON	OFF	—	—	—	5k	-20	—	-4.7	-3.2	-1.7	dB	27	4	25	6	
DEC 5k (2)	ON	OFF	—	—	—	5k	-30	—	—	-9.7	-8.2	-6.7	dB	27	4	25	6	
	PBOUT offset	OFF	OFF→ON	—	—	—	—	—	No signal	-150	0	150	mV	—	—	25	6	1
Signal handling	V _o max	ON	OFF	—	—	—	1k	—	THD=1%	12.0	13.0	—	dB	27	4	25	6	2
Signal to noise ratio	S/N	ON	OFF	—	—	—	1k	(0)	R _g =10kΩ, C ₀ I/R/ARM	70.0	80.0	—	dB	27	4	25	6	
Total Harmonic Distortion	THD	ON	OFF	—	—	—	1k	0	—	—	0.05	0.3	%	27	4	25	6	
Channel separation	CTRL (1)	—	—	—	—	FOR	1k	—	(+20)	50.0	60.0	—	dB	37	39	29→22→29		
MUTE attenuation	CTRL (2)	OFF	OFF	—	—	—	1k	(+12)	—	70.0	80.0	—	dB	27	4	25→6→25		
	CT MUTE	OFF	OFF→ON	—	—	—	1k	(+12)	—	70.0	80.0	—	dB	27	4	25	6	
PB-EQ gain	G _v EQ 1k	—	—	120μ	—	FOR/REV	1k	—	0	37.8	40.8	43.8	dB	37/35	39/33	29	2	
	G _v EQ 10k(1)	—	—	120μ	—	FOR	10k	—	0	33.9	36.9	39.9	dB	37	39	29	2	
	G _v EQ 10k(2)	—	—	70μ	—	FOR	10k	—	0	29.6	32.6	35.6	dB	37	39	29	2	
PB-EQ Maximum output level	V _{OM}	—	—	120μ	—	FOR	1k	—	—	300	600	—	mVrms	37	39	29	2	
PB-EQ T.H.D.	THD-EQ	—	—	120μ	—	FOR/REV	1k	—	+14dB	—	0.1	0.3	%	37/35	39/33	29	2	
PB-EQ input conversion noise	V _N	—	—	120μ	—	FOR/REV	(1k)	—	—	—	0.7	1.5	μVrms	37/35	39/33	29	2	
MS sensing level	V _{ON} (1)	OFF	OFF	—	SER	—	5k	—	—	-36.0	-32.0	-28.0	dB	27	4	25	6	16 3
	V _{ON} (2)	OFF	OFF	—	REP	—	5k	—	—	-18.0	-14.0	-10.0	dB	27	4	25	6	16 3
MS output low level	V _{OL}	OFF	OFF	—	SER	—	5k	0	—	—	1.0	1.5	V	27	4	—	—	16
MS output leakage current	I _{OH}	—	—	—	—	—	—	—	No signal	—	0.0	2.0	μA	—	—	—	—	16
Control voltage	V _{LH}	—	—	—	—	—	—	—	—	-0.2	—	1.0	V	—	—	—	—	17 to 21
	V _{IL}	—	—	—	—	—	—	—	—	3.5	—	V _{CC}	V	—	—	—	—	21

Notes: 1. VCC = 12V
2. VCC = 6.5V
3. For inputting signal to one side channel

HA12229F

(Ta = 25°C, V_{CC} = 9 V, P_{BO}UT level 0 dB = 300 mVrms, EQOUT level 0 dB = 60 mVrms)


Item	Symbol	Test Condition					Specification			Application Terminal		
		IC Condition			f _{in} (Hz)	P _{BO} UT level (dB)	EQOUT level (dB)	Other	Min	Typ	Max	Unit
		MUTE ON/OFF	SER/ REP	FOR/ REV								
Quiescent current	I _Q	OFF	70μ	SER	FOR	—	—	No signal	3.0	5.0	8.0	mA
Input Amp. gain	G _V /A	OFF	—	—	1k	0	—	—	19.0	20.0	21.0	dB
P _{BO} UT offset	V _{ofs}	OFF→ ON	—	—	—	—	—	No signal	-150	0	150	mV
Signal handling	V _O max	OFF	—	—	1k	—	—	THD=1%	12.0	13.0	—	dB
Signal to noise ratio	S/N	OFF	—	—	1k	(0)	—	Rg=10kΩ, CCIR/ARM	70.0	80.0	—	dB
Total Harmonic Distortion	THD	OFF	—	—	1k	0	—	—	—	0.05	0.3	%
Channel separation	CTRL (1)	—	—	FOR	1k	—	(+20)	—	50.0	60.0	—	dB
	CTRL (2)	OFF	—	—	1k	(+12)	—	—	70.0	80.0	—	dB
MUTE attenuation	CT MUTE	OFF→ ON	—	—	1k	(+12)	—	—	70.0	80.0	—	dB
PB-EQ gain	G _V EQ 1k	—	120μ	FOR/ REV	1k	—	0	—	37.8	40.8	43.8	dB
	G _V EQ 10k(1)	—	120μ	FOR	10k	—	0	—	33.9	36.9	39.9	dB
	G _V EQ 10k(2)	—	70μ	FOR	10k	—	0	—	29.6	32.6	35.6	dB
PB-EQ Maximum output level	V _{OM}	—	120μ	FOR	1k	—	—	THD=1%	300	600	—	mVrms
PB-EQ T.H.D.	THD-EQ	—	120μ	FOR/ REV	1k	—	+14dB	—	—	0.1	0.3	%
PB-EQ input conversion noise	V _N	—	120μ	FOR/ REV	(1k)	—	—	Rg=680Ω, DIN-AUDIO	—	0.7	1.5	μVrms
MS sensing level	V _{ON} (1)	OFF	—	SER	5k	—	—	—	-36.0	-32.0	-28.0	dB
	V _{ON} (2)	OFF	—	REP	5k	—	—	—	-18.0	-14.0	-10.0	dB
MS output low level	V _{OL}	OFF	—	SER	5k	0	—	—	—	1.0	1.5	V
MS output leakage current	I _{OH}	—	—	—	—	—	—	No signal	—	0.0	2.0	μA
Control voltage	V _{IL}	—	—	—	—	—	—	—	-0.2	—	1.0	V
	V _{IH}	—	—	—	—	—	—	—	3.5	—	V _{CC}	V

Notes: 1. V_{CC} = 12V2. V_{CC} = 6.5V



3. For inputting signal to one side channel



HA12228F/HA12229F



Test Circuit







Characteristic Curves












































































































Package Dimensions

Unit: mm



*Dimension including the plating thickness
Base material dimension

Hitachi Code	FP-40B
JEDEC	—
EIAJ	Conforms
Mass (reference value)	0.2 g

Disclaimer

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

Sales Offices

HITACHI

Hitachi, Ltd.

Semiconductor & Integrated Circuits.

Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

URL	NorthAmerica	: http://semiconductor.hitachi.com/
	Europe	: http://www.hitachi-eu.com/hel/ecg
	Asia	: http://sicapac.hitachi-asia.com
	Japan	: http://www.hitachi.co.jp/Sicd/indx.htm

For further information write to:

Hitachi Semiconductor
(America) Inc.
179 East Tasman Drive,
San Jose, CA 95134
Tel: <1> (408) 433-1990
Fax: <1> (408) 433-0223

Hitachi Europe GmbH
Electronic Components Group
Dornacher Straße 3
D-85622 Feldkirchen, Munich
Germany
Tel: <49> (89) 9 9180-0
Fax: <49> (89) 9 29 30 00

Hitachi Europe Ltd.
Electronic Components Group.
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA, United Kingdom
Tel: <44> (1628) 585000
Fax: <44> (1628) 585160

Hitachi Asia Ltd.
Hitachi Tower
16 Collyer Quay #20-00,
Singapore 049318
Tel: <65>-538-6533/538-8577
Fax: <65>-538-6933/538-3877
URL: <http://www.hitachi.com.sg>

Hitachi Asia Ltd.
(Taipei Branch Office)
4/F, No. 167, Tun Hwa North Road,
Hung-Kuo Building,
Taipei (105), Taiwan
Tel: <886>-(2)-2718-3666
Fax: <886>-(2)-2718-8180
Telex: 23222 HAS-TP
URL: <http://www.hitachi.com.tw>

Hitachi Asia (Hong Kong) Ltd.
Group III (Electronic Components)
7/F., North Tower,
World Finance Centre,
Harbour City, Canton Road
Tsim Sha Tsui, Kowloon,
Hong Kong
Tel: <852>-(2)-735-9218
Fax: <852>-(2)-730-0281
URL: <http://www.hitachi.com.hk>

Copyright © Hitachi, Ltd., 2000. All rights reserved. Printed in Japan.
Colophon 2.0