

TMS-SCE-3/16-2.0-S1-9 Product Details

Share Print Email



Active

Heat Shrink Sleeve

TMS-SCE-3/16-2.0-S1-9

TMS-SCE-3/16-2.0-S1-9

TE Internal Number: 3573650001

Product Highlights View All

- TMS-SCE Series
- Military Grade
- Radiation Cross-Linked Polyolefin Material
- Format = Ladder
- Shrink Ratio = 3:1

Pricing & Availability

Request Sample

Add to My Part List

Buy Product through Distributor

Feedback

Documents Features Compliance

Please Note:
Use the Product Drawing for all design activity

Product Type Features	
Grade	Military
Color	White

Dimensions	
Expanded ID, Min. (mm [in])	4.75 [0.187]
Recovered ID, Max. (mm [in])	1.57 [0.062]
Sleeve Length, Nominal (mm [in])	50.8 [2]
Recommended Wire/Cable OD Use Range (mm [in])	1.75 - 4.06 [0.069 - 0.16]

Body Features	
Material	Radiation Cross-Linked Polyolefin
Shrink Ratio	3:1
Wall Thickness - Full Recovery (Nominal) (mm [in])	0.58 [0.023]

Industry Standards	
RoHS/ELV Compliance	RoHS compliant, ELV compliant
Lead Free Solder Processes	Not relevant for lead free process
RoHS/ELV Compliance History	Always was RoHS compliant

Printer/Label Features	
Number of Prescores	1
Number of Markers per Sleeve	2
Recommended Printer	See Printer Ribbon Matrix
Recommended Ribbon	See Printer Ribbon Matrix

Environmental	
Operating Temperature (°C [°F])	-55 - +135 [-67 - +275]

Conditions for Usage	
Format	Ladder

Packaging Features	
Packaging Quantity	250

Other	
Series	TMS-SCE
Brand	Raychem
Comment	Other colours available, contact TE.

Related Products

Not quite the product you're looking for?
Find Similar Products

View Part in Product Feature Selector

Check for Tooling