

# Single and Dual Low Voltage, Rail-to-Rail Input and Output, Operational Amplifiers

## LMV931, LMV932

The LMV931 Single and LMV932 Dual are CMOS low-voltage operational amplifiers which can operate on single-sided power supplies (1.8 V to 5.0 V) with rail-to-rail input and output swing. Both devices come in small state-of-the-art packages and require very low quiescent current making them ideal for battery-operated, portable applications such as notebook computers and hand-held instruments. Rail-to-Rail operation provides improved signal-to-noise performance plus the small packages allow for closer placement to signal sources thereby reducing noise pickup.

The single LMV931 is offered in space saving SC70-5 package. The dual LMV932 is in either a Micro8 or SOIC package. These small packages are very beneficial for crowded PCB's.

### Features

- Performance Specified on Single-Sided Power Supply: 1.8 V, 2.7 V, and 5 V
- Small Packages:  
LMV931 in a SC-70  
LMV932 in a Micro8 or SOIC-8
- No Output Crossover Distortion
- Extended Industrial Temperature Range:  $-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$
- Low Quiescent Current 210  $\mu\text{A}$ , Max Per Channel
- No Output Phase-Reversal from Overdriven Input
- These are Pb-Free Devices

### Typical Applications

- Notebook Computers, Portable Battery-Operated Instruments, PDA's
- Active Filters, Low-Side Current Monitoring




Figure 1. Output Voltage Swing vs. Supply Voltage

### MARKING DIAGRAMS



#### LMV931 (Single)



SC-70  
CASE 419A




TSOP-5  
CASE 483



M = Date Code  
A = Assembly Location  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)



#### LMV932 (Dual)



Micro8  
CASE 846A



SOIC-8  
CASE 751





A = Assembly Location  
Y = Year  
L = Wafer Lot  
W = Work Week  
▪ = Pb-Free Package  
(Note: Microdot may be in either location)

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 14 of this data sheet.

# LMV931, LMV932

## PIN CONNECTIONS



## MAXIMUM RATINGS

| Symbol        | Rating                                                                                  | Value                           | Unit               |
|---------------|-----------------------------------------------------------------------------------------|---------------------------------|--------------------|
| $V_S$         | Supply Voltage (Operating Range $V_S = 1.8\text{ V to }5.5\text{ V}$ )                  | 5.5                             | V                  |
| $V_{IDR}$     | Input Differential Voltage                                                              | $\pm$ Supply Voltage            | V                  |
| $V_{ICR}$     | Input Common Mode Voltage Range                                                         | $-0.5\text{ to }(V_{CC}) + 0.5$ | V                  |
|               | Maximum Input Current                                                                   | 10                              | mA                 |
| $t_{SO}$      | Output Short Circuit (Note 1)                                                           | Continuous                      |                    |
| $T_J$         | Maximum Junction Temperature (Operating Range $-40^\circ\text{C to }85^\circ\text{C}$ ) | 150                             | $^\circ\text{C}$   |
| $\theta_{JA}$ | Thermal Resistance:                                                                     | SC-70<br>TSOP-5<br>Micro8       | $^\circ\text{C/W}$ |
| $T_{stg}$     | Storage Temperature                                                                     | $-65\text{ to }150$             | $^\circ\text{C}$   |
|               | Mounting Temperature (Infrared or Convection $\leq 30\text{ sec}$ )                     | 260                             | $^\circ\text{C}$   |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

ESD data available upon request.

1. Continuous short-circuit operation to ground at elevated ambient temperature can result in exceeding the maximum allowed junction temperature of  $150^\circ\text{C}$ . Output currents in excess of 45 mA over long term may adversely affect reliability. Shorting output to either  $V_{CC}$  or  $V_{EE}$  will adversely affect reliability.

# LMV931, LMV932

**1.8 V DC ELECTRICAL CHARACTERISTICS** (Note 2) Unless otherwise noted, all min/max limits are guaranteed for  $T_A = 25^\circ\text{C}$ ,  $V_S = 1.8\text{ V}$ ,  $V_{CM} = V_S/2$ ,  $V_O = V_S/2$  and  $R_L > 1\text{ M}\Omega$ . Typical specifications represent the most likely parametric norm.

| Parameter                                 | Symbol     | Condition                                                                                                     | Min            | Typ             | Max            | Unit                         |
|-------------------------------------------|------------|---------------------------------------------------------------------------------------------------------------|----------------|-----------------|----------------|------------------------------|
| Input Offset Voltage                      | $V_{IO}$   | LMV931 (Single) ( $-40^\circ\text{C}$ to $+125^\circ\text{C}$ )                                               |                | 1               | 6              | mV                           |
|                                           |            | LMV932 (Dual) ( $-40^\circ\text{C}$ to $+125^\circ\text{C}$ )                                                 |                | 1               | 7.5            |                              |
| Input Offset Voltage Average Drift        | $TCV_{IO}$ |                                                                                                               |                | 5.5             |                | $\mu\text{V}/^\circ\text{C}$ |
| Input Bias Current                        | $I_B$      | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   |                | < 1             |                | nA                           |
| Input Offset Current                      | $I_{IO}$   | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   |                | < 1             |                | nA                           |
| Supply Current (per Channel)              | $I_{CC}$   | In Active Mode                                                                                                |                | 75              | 185            | $\mu\text{A}$                |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   |                |                 | 205            |                              |
| Common Mode Rejection Ratio               | CMRR       | $0\text{ V} \leq V_{CM} \leq 0.6\text{ V}$ , $1.4\text{ V} \leq V_{CM} \leq 1.8\text{ V}$                     | 50             | 70              |                | dB                           |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   | 50             |                 |                |                              |
|                                           |            | $-0.2\text{ V} \leq V_{CM} \leq 0\text{ V}$ , $1.8\text{ V} \leq V_{CM} \leq 2\text{ V}$                      | 50             | 70              |                |                              |
| Power Supply Rejection Ratio              | PSRR       | $1.8\text{ V} \leq V^+ \leq 5\text{ V}$ , $V_{CM} = 0.5\text{ V}$                                             | 50             | 70              |                | dB                           |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   | 50             |                 |                |                              |
| Input Common-Mode Voltage Range           | $V_{CM}$   | For CMRR $\geq 50\text{ dB}$ and $T_A = 25^\circ\text{C}$                                                     | $V_{EE} - 0.2$ | $-0.2$ to $2.1$ | $V_{CC} + 0.2$ | V                            |
|                                           |            | For CMRR $\geq 50\text{ dB}$ and $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$                             | $V_{EE}$       |                 | $V_{CC}$       |                              |
|                                           |            | For CMRR $\geq 50\text{ dB}$ and $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$                            | $V_{EE} + 0.2$ |                 | $V_{CC} - 0.2$ |                              |
| Large Signal Voltage Gain LMV931 (Single) | $A_V$      | $R_L = 600\ \Omega$ to $0.9\text{ V}$ , $V_O = 0.2\text{ V}$ to $1.6\text{ V}$ , $V_{CM} = 0.5\text{ V}$      | 77             | 101             |                | dB                           |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   | 73             |                 |                |                              |
|                                           |            | $R_L = 2\text{ k}\Omega$ to $0.9\text{ V}$ , $V_O = 0.2\text{ V}$ to $1.6\text{ V}$ , $V_{CM} = 0.5\text{ V}$ | 80             | 105             |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   | 75             |                 |                |                              |
| Large Signal Voltage Gain LMV932 (Dual)   | $A_V$      | $R_L = 600\ \Omega$ to $0.9\text{ V}$ , $V_O = 0.2\text{ V}$ to $1.6\text{ V}$ , $V_{CM} = 0.5\text{ V}$      | 75             | 90              |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   | 72             |                 |                |                              |
|                                           |            | $R_L = 2\text{ k}\Omega$ to $0.9\text{ V}$ , $V_O = 0.2\text{ V}$ to $1.6\text{ V}$ , $V_{CM} = 0.5\text{ V}$ | 78             | 100             |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   | 75             |                 |                |                              |
| Output Swing                              | $V_{OH}$   | $R_L = 600\ \Omega$ to $0.9\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                                          | 1.65           | 1.72            |                | V                            |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   | 1.63           |                 |                |                              |
|                                           | $V_{OL}$   | $R_L = 600\ \Omega$ to $0.9\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                                          |                | 0.077           | 0.105          |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   |                |                 | 0.12           |                              |
|                                           | $V_{OH}$   | $R_L = 2\text{ k}\Omega$ to $0.9\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                                     | 1.75           | 1.77            |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   | 1.74           |                 |                |                              |
|                                           | $V_{OL}$   | $R_L = 2\text{ k}\Omega$ to $0.9\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                                     |                | 0.24            | 0.035          |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   |                |                 | 0.04           |                              |
| Output Short Circuit Current              | $I_O$      | Sourcing, $V_O = 0\text{ V}$ , $V_{IN} = +100\text{ mV}$                                                      | 4.0            | 30              |                | mA                           |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   | 3.3            |                 |                |                              |
|                                           |            | Sinking, $V_O = 1.8\text{ V}$ , $V_{IN} = -100\text{ mV}$                                                     | 7.0            | 60              |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                   | 5.0            |                 |                |                              |

2. Guaranteed by design and/or characterization.

## LMV931, LMV932

**1.8 V AC ELECTRICAL CHARACTERISTICS** Unless otherwise specified, all limits are guaranteed for  $T_A = 25^\circ\text{C}$ ,  $V_S = 1.8\text{ V}$ ,  $V_{CM} = V_S/2$ ,  $V_O = V_S/2$  and  $R_L > 1\text{ M}\Omega$ . Typical specifications represent the most likely parametric norm. Min/Max specifications are guaranteed by testing, characterization, or statistical analysis.

| Parameter                        | Symbol     | Condition                                                                       | Min | Typ   | Max | Unit                   |
|----------------------------------|------------|---------------------------------------------------------------------------------|-----|-------|-----|------------------------|
| Slew Rate                        | SR         | (Note 3)                                                                        |     | 0.35  |     | V/ $\mu\text{S}$       |
| Gain Bandwidth Product           | GBWP       |                                                                                 |     | 1.4   |     | MHz                    |
| Phase Margin                     | $\Theta_m$ |                                                                                 |     | 67    |     | $^\circ$               |
| Gain Margin                      | Gm         |                                                                                 |     | 7     |     | dB                     |
| Input-Referred Voltage Noise     | $e_n$      | $f = 50\text{ kHz}$ , $V_{CM} = 0.5\text{ V}$                                   |     | 60    |     | nV/ $\sqrt{\text{Hz}}$ |
| Total Harmonic Distortion        | THD        | $f = 1\text{ kHz}$ , $A_V = +1$ , $R_L = 600\ \Omega$ , $V_O = 1\text{ V}_{PP}$ |     | 0.023 |     | %                      |
| Amplifier-to-Amplifier Isolation |            | (Note 4)                                                                        |     | 123   |     | dB                     |

3. Connected as voltage follower with input step from  $V_{EE}$  to  $V_{CC}$ . Number specified is the slower of the positive and negative slew rates.
4. Input referred,  $R_L = 100\text{ k}\Omega$  connected to  $V_S/2$ . Each amp excited in turn with 1 kHz to produce  $V_O = 3\text{ V}_{PP}$ . (For Supply Voltages  $< 3\text{ V}$ ,  $V_O = V_{CC}$ ).

## LMV931, LMV932

**2.7 V DC ELECTRICAL CHARACTERISTICS** (Note 5) Unless otherwise noted, all min/max limits are guaranteed for  $T_A = 25^\circ\text{C}$ ,  $V_S = 2.7\text{ V}$ ,  $V_{CM} = V_S/2$ ,  $V_O = V_S/2$  and  $R_L > 1\text{ M}\Omega$ . Typical specifications represent the most likely parametric norm.

| Parameter                                 | Symbol     | Condition                                                                                  | Min            | Typ             | Max            | Unit                         |
|-------------------------------------------|------------|--------------------------------------------------------------------------------------------|----------------|-----------------|----------------|------------------------------|
| Input Offset Voltage                      | $V_{IO}$   | LMV931 (Single) ( $-40^\circ\text{C}$ to $+125^\circ\text{C}$ )                            |                | 1               | 6              | mV                           |
|                                           |            | LMV932 (Dual) ( $-40^\circ\text{C}$ to $+125^\circ\text{C}$ )                              |                | 1               | 7.5            |                              |
| Input Offset Voltage Average Drift        | $TCV_{IO}$ |                                                                                            |                | 5.5             |                | $\mu\text{V}/^\circ\text{C}$ |
| Input Bias Current                        | $I_B$      | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                |                | < 1             |                | nA                           |
| Input Offset Current                      | $I_{IO}$   | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                |                | < 1             |                | nA                           |
| Supply Current (per Channel)              | $I_{CC}$   | In Active Mode                                                                             |                | 80              | 190            | $\mu\text{A}$                |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                |                |                 | 210            |                              |
| Common Mode Rejection Ratio               | CMRR       | $0\text{ V} \leq V_{CM} \leq 1.5\text{ V}$ , $2.3\text{ V} \leq V_{CM} \leq 2.7\text{ V}$  | 50             | 70              |                | dB                           |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 50             |                 |                |                              |
|                                           |            | $-0.2\text{ V} \leq V_{CM} \leq 0\text{ V}$ , $2.7\text{ V} \leq V_{CM} \leq 2.9\text{ V}$ | 50             | 70              |                |                              |
| Power Supply Rejection Ratio              | PSRR       | $1.8\text{ V} \leq V^+ \leq 5\text{ V}$ , $V_{CM} = 0.5\text{ V}$                          | 50             | 70              |                | dB                           |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 50             |                 |                |                              |
| Input Common-Mode Voltage Range           | $V_{CM}$   | For CMRR $\geq 50\text{ dB}$ and $T_A = 25^\circ\text{C}$                                  | $V_{EE} - 0.2$ | $-0.2$ to $3.0$ | $V_{CC} + 0.2$ | V                            |
|                                           |            | For CMRR $\geq 50\text{ dB}$ and $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$          | $V_{EE}$       |                 | $V_{CC}$       |                              |
|                                           |            | For CMRR $\geq 50\text{ dB}$ and $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$         | $V_{EE} + 0.2$ |                 | $V_{CC} - 0.2$ |                              |
| Large Signal Voltage Gain LMV931 (Single) | $A_V$      | $R_L = 600\ \Omega$ to $1.35\text{ V}$ , $V_O = 0.2\text{ V}$ to $2.5\text{ V}$            | 87             | 104             |                | dB                           |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 86             |                 |                |                              |
|                                           |            | $R_L = 2\text{ k}\Omega$ to $1.35\text{ V}$ , $V_O = 0.2\text{ V}$ to $2.5\text{ V}$       | 92             | 110             |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 91             |                 |                |                              |
| Large Signal Voltage Gain LMV932 (Dual)   | $A_V$      | $R_L = 600\ \Omega$ to $1.35\text{ V}$ , $V_O = 0.2\text{ V}$ to $2.5\text{ V}$            | 78             | 90              |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 75             |                 |                |                              |
|                                           |            | $R_L = 2\text{ k}\Omega$ to $1.35\text{ V}$ , $V_O = 0.2\text{ V}$ to $2.5\text{ V}$       | 81             | 100             |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 78             |                 |                |                              |
| Output Swing                              | $V_{OH}$   | $R_L = 600\ \Omega$ to $1.35\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                      | 2.55           | 2.62            |                | V                            |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 2.53           |                 |                |                              |
|                                           | $V_{OL}$   | $R_L = 600\ \Omega$ to $1.35\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                      |                | 0.083           | 0.11           |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                |                |                 | 0.13           |                              |
|                                           | $V_{OH}$   | $R_L = 2\text{ k}\Omega$ to $1.35\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                 | 2.65           | 2.675           |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 2.64           |                 |                |                              |
|                                           | $V_{OL}$   | $R_L = 2\text{ k}\Omega$ to $1.35\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                 |                | 0.025           | 0.04           |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                |                |                 | 0.045          |                              |
| Output Short Circuit Current              | $I_O$      | Sourcing, $V_O = 0\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                                | 20             | 65              |                | mA                           |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 15             |                 |                |                              |
|                                           |            | Sinking, $V_O = 0\text{ V}$ , $V_{IN} = -100\text{ mV}$                                    | 18             | 75              |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 12             |                 |                |                              |

5. Guaranteed by design and/or characterization.

## LMV931, LMV932

**2.7 V AC ELECTRICAL CHARACTERISTICS** Unless otherwise specified, all limits are guaranteed for  $T_A = 25^\circ\text{C}$ ,  $V_S = 2.7\text{ V}$ ,  $V_{CM} = V_S/2$ ,  $V_O = V_S/2$  and  $R_L > 1\text{ M}\Omega$ . Typical specifications represent the most likely parametric norm. Min/Max specifications are guaranteed by testing, characterization, or statistical analysis.

| Parameter                        | Symbol     | Condition                                                                       | Min | Typ   | Max | Unit                   |
|----------------------------------|------------|---------------------------------------------------------------------------------|-----|-------|-----|------------------------|
| Slew Rate                        | SR         | (Note 6)                                                                        |     | 0.4   |     | V/ $\mu\text{S}$       |
| Gain Bandwidth Product           | GBWP       |                                                                                 |     | 1.4   |     | MHz                    |
| Phase Margin                     | $\Theta_m$ |                                                                                 |     | 70    |     | $^\circ$               |
| Gain Margin                      | Gm         |                                                                                 |     | 7.5   |     | dB                     |
| Input-Referred Voltage Noise     | $e_n$      | $f = 50\text{ kHz}$ , $V_{CM} = 1.0\text{ V}$                                   |     | 57    |     | nV/ $\sqrt{\text{Hz}}$ |
| Total Harmonic Distortion        | THD        | $f = 1\text{ kHz}$ , $A_V = +1$ , $R_L = 600\ \Omega$ , $V_O = 1\text{ V}_{PP}$ |     | 0.022 |     | %                      |
| Amplifier-to-Amplifier Isolation |            | (Note 7)                                                                        |     | 123   |     | dB                     |

6. Connected as voltage follower with input step from  $V_{EE}$  to  $V_{CC}$ . Number specified is the slower of the positive and negative slew rates.  
 7. Input referred,  $R_L = 100\text{ k}\Omega$  connected to  $V_S/2$ . Each amp excited in turn with  $1\text{ kHz}$  to produce  $V_O = 3\text{ V}_{PP}$ . (For Supply Voltages  $< 3\text{ V}$ ,  $V_O = V_{CC}$ ).

## LMV931, LMV932

**5 V DC ELECTRICAL CHARACTERISTICS** (Note 8) Unless otherwise noted, all min/max limits are guaranteed for  $T_A = 25^\circ\text{C}$ ,  $V_S = 5\text{ V}$ ,  $V_{CM} = V_S/2$ ,  $V_O = V_S/2$  and  $R_L > 1\text{ M}\Omega$ . Typical specifications represent the most likely parametric norm.

| Parameter                                 | Symbol     | Condition                                                                                  | Min            | Typ             | Max            | Unit                         |
|-------------------------------------------|------------|--------------------------------------------------------------------------------------------|----------------|-----------------|----------------|------------------------------|
| Input Offset Voltage                      | $V_{IO}$   | LMV931 (Single) ( $-40^\circ\text{C}$ to $+125^\circ\text{C}$ )                            |                | 1               | 6              | mV                           |
|                                           |            | LMV932 (Dual) ( $-40^\circ\text{C}$ to $+125^\circ\text{C}$ )                              |                | 1               | 7.5            |                              |
| Input Offset Voltage Average Drift        | $TCV_{IO}$ |                                                                                            |                | 5.5             |                | $\mu\text{V}/^\circ\text{C}$ |
| Input Bias Current                        | $I_B$      | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                |                | < 1             |                | nA                           |
| Input Offset Current                      | $I_{IO}$   | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                |                | < 1             |                | nA                           |
| Supply Current (per Channel)              | $I_{CC}$   | In Active Mode                                                                             |                | 95              | 210            | $\mu\text{A}$                |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                |                |                 | 230            |                              |
| Common-Mode Rejection Ratio               | CMRR       | $0\text{ V} \leq V_{CM} \leq 3.8\text{ V}$ , $4.6\text{ V} \leq V_{CM} \leq 5.0\text{ V}$  | 50             | 70              |                | dB                           |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 50             |                 |                |                              |
|                                           |            | $-0.2\text{ V} \leq V_{CM} \leq 0\text{ V}$ , $5.0\text{ V} \leq V_{CM} \leq 5.2\text{ V}$ | 50             | 70              |                |                              |
| Power Supply Rejection Ratio              | PSRR       | $1.8\text{ V} \leq V^+ \leq 5\text{ V}$ , $V_{CM} = 0.5\text{ V}$                          | 50             | 70              |                | dB                           |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 50             |                 |                |                              |
| Input Common-Mode Voltage Range           | $V_{CM}$   | For CMRR $\geq 50\text{ dB}$ and $T_A = 25^\circ\text{C}$                                  | $V_{EE} - 0.2$ | $-0.2$ to $5.3$ | $V_{CC} + 0.2$ | V                            |
|                                           |            | For CMRR $\geq 50\text{ dB}$ and $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$          | $V_{EE}$       |                 | $V_{CC}$       |                              |
|                                           |            | For CMRR $\geq 50\text{ dB}$ and $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$         | $V_{EE} + 0.3$ |                 | $V_{CC} - 0.3$ |                              |
| Large Signal Voltage Gain LMV931 (Single) | $A_V$      | $R_L = 600\ \Omega$ to $2.5\text{ V}$ , $V_O = 0.2\text{ V}$ to $4.8\text{ V}$             | 88             | 102             |                | dB                           |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 87             |                 |                |                              |
|                                           |            | $R_L = 2\text{ k}\Omega$ to $2.5\text{ V}$ , $V_O = 0.2\text{ V}$ to $4.8\text{ V}$        | 94             | 113             |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 93             |                 |                |                              |
| Large Signal Voltage Gain LMV932 (Dual)   | $A_V$      | $R_L = 600\ \Omega$ to $2.5\text{ V}$ , $V_O = 0.2\text{ V}$ to $4.8\text{ V}$             | 81             | 90              |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 78             |                 |                |                              |
|                                           |            | $R_L = 2\text{ k}\Omega$ to $2.5\text{ V}$ , $V_O = 0.2\text{ V}$ to $4.8\text{ V}$        | 85             | 100             |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 82             |                 |                |                              |
| Output Swing                              | $V_{OH}$   | $R_L = 600\ \Omega$ to $2.5\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                       | 4.855          | 4.89            |                | V                            |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 4.835          |                 |                |                              |
|                                           | $V_{OL}$   | $R_L = 600\ \Omega$ to $2.5\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                       |                | 0.12            | 0.16           |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                |                |                 | 0.18           |                              |
|                                           | $V_{OH}$   | $R_L = 2\text{ k}\Omega$ to $2.5\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                  | 4.945          | 4.967           |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 4.935          |                 |                |                              |
|                                           | $V_{OL}$   | $R_L = 2\text{ k}\Omega$ to $2.5\text{ V}$ , $V_{IN} = \pm 100\text{ mV}$                  |                | 0.037           | 0.065          |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                |                |                 | 0.075          |                              |
| Output Short-Circuit Current              | $I_O$      | Sourcing, $V_O = 0\text{ V}$ , $V_{IN} = +100\text{ mV}$                                   | 55             | 65              |                | mA                           |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 45             |                 |                |                              |
|                                           |            | Sinking, $V_O = 5\text{ V}$ , $V_{IN} = -100\text{ mV}$                                    | 58             | 80              |                |                              |
|                                           |            | $-40^\circ\text{C}$ to $+125^\circ\text{C}$                                                | 45             |                 |                |                              |

8. Guaranteed by design and/or characterization.

## LMV931, LMV932

**5 V AC ELECTRICAL CHARACTERISTICS** Unless otherwise specified, all limits are guaranteed for  $T_A = 25^\circ\text{C}$ ,  $V_S = 5\text{ V}$ ,  $V_{CM} = V_S/2$ ,  $V_O = V_S/2$  and  $R_L > 1\text{ M}\Omega$ . Typical specifications represent the most likely parametric norm.

| Parameter                        | Symbol     | Condition                                                                       | Min | Typ   | Max | Unit                   |
|----------------------------------|------------|---------------------------------------------------------------------------------|-----|-------|-----|------------------------|
| Slew Rate                        | SR         | (Note 9)                                                                        |     | 0.48  |     | V/ $\mu\text{S}$       |
| Gain Bandwidth Product           | GBWP       |                                                                                 |     | 1.5   |     | MHz                    |
| Phase Margin                     | $\Theta_m$ |                                                                                 |     | 65    |     | °                      |
| Gain Margin                      | Gm         |                                                                                 |     | 8     |     | dB                     |
| Input-Referred Voltage Noise     | $e_n$      | $f = 50\text{ kHz}$ , $V_{CM} = 2\text{ V}$                                     |     | 50    |     | nV/ $\sqrt{\text{Hz}}$ |
| Total Harmonic Distortion        | THD        | $f = 1\text{ kHz}$ , $A_V = +1$ , $R_L = 600\ \Omega$ , $V_O = 1\text{ V}_{PP}$ |     | 0.022 |     | %                      |
| Amplifier-to-Amplifier Isolation |            | (Note 10)                                                                       |     | 123   |     | dB                     |

9. Connected as voltage follower with input step from  $V_{EE}$  to  $V_{CC}$ . Number specified is the slower of the positive and negative slew rates.

10. Input referred,  $R_L = 100\text{ k}\Omega$  connected to  $V_S/2$ . Each amp excited in turn with 1 kHz to produce  $V_O = 3\text{ V}_{PP}$ . (For Supply Voltages  $< 3\text{ V}$ ,  $V_O = V_{CC}$ ).



# LMV931, LMV932

## TYPICAL CHARACTERISTICS

( $T_A = 25^\circ\text{C}$  and  $V_S = 5\text{ V}$  unless otherwise specified)




Figure 2. Supply Current vs. Supply Voltage




Figure 3. Supply Current vs. Supply Voltage




Figure 4. Sourcing Current vs. Output Voltage  
( $T_A = 25^\circ\text{C}$ )




Figure 5. Sinking Current vs. Output Voltage  
( $T_A = 25^\circ\text{C}$ )




Figure 6. Output Voltage Swing vs. Supply Voltage




Figure 7. Output Voltage vs. Supply Voltage

# LMV931, LMV932

## TYPICAL CHARACTERISTICS

( $T_A = 25^\circ\text{C}$  and  $V_S = 5\text{ V}$  unless otherwise specified)




Figure 8. Open Loop Gain and Phase




Figure 9. Frequency Response vs. CL




Figure 10. Frequency Response vs. CL




Figure 11. Gain and Phase vs. Temp




Figure 12. Gain and Phase vs. Temp

# LMV931, LMV932

## TYPICAL CHARACTERISTICS

( $T_A = 25^\circ\text{C}$  and  $V_S = 5\text{ V}$  unless otherwise specified)




Figure 13. CMRR vs. Frequency




Figure 14. PSRR vs. Frequency




Figure 15. Input Voltage Noise vs. Frequency




Figure 16. THD vs. Frequency




Figure 17. Slew Rate vs. Supply Voltage

# LMV931, LMV932

## TYPICAL CHARACTERISTICS

( $T_A = 25^\circ\text{C}$  and  $V_S = 5\text{ V}$  unless otherwise specified)




Figure 18. Small Signal Transient Response




Figure 19. Small Signal Transient Response




Figure 20. Small Signal Transient Response




Figure 21. Large Signal Transient Response




Figure 22. Large Signal Transient Response






Figure 23. Large Signal Transient Response

## TYPICAL CHARACTERISTICS


( $T_A = 25^\circ\text{C}$  and  $V_S = 5\text{ V}$  unless otherwise specified)




**Figure 24. Short-Circuit vs. Temperature (Sinking)**




**Figure 25. Short-Circuit vs. Temperature (Sourcing)**



**Figure 26. Offset Voltage vs. Common Mode Range  $V_{DD}$**



**Figure 27. Offset Voltage vs. Common Mode Range**



**Figure 28. Offset Voltage vs. Common Mode Range**

# LMV931, LMV932

## APPLICATION INFORMATION




Figure 29. Voltage Reference




Figure 30. Wien Bridge Oscillator





Figure 31. Comparator with Hysteresis



Given:  $f_o$  = center frequency  
 $A(f_o)$  = gain at center frequency

Choose value  $f_o$ ,  $C$   
 Then:  $R3 = \frac{Q}{\pi f_o C}$   
 $R1 = \frac{R3}{2 A(f_o)}$   
 $R2 = \frac{R1 R3}{4Q^2 R1 - R3}$

For less than 10% error from operational amplifier,  
 $((Q_0 f_o)/BW) < 0.1$  where  $f_o$  and  $BW$  are expressed in Hz.  
 If source impedance varies, filter may be preceded with  
 voltage follower buffer to stabilize filter parameters.

Figure 32. Multiple Feedback Bandpass Filter

## ORDERING INFORMATION

| Order Number | Number of Channels | Number of Pins | Package Type     | Shipping <sup>†</sup> |
|--------------|--------------------|----------------|------------------|-----------------------|
| LMV931SQ3T2G | Single             | 5              | SC70-5 (Pb-Free) | 3000 / Tape & Reel    |
| LMV931SN3T1G | Single             | 5              | TSOP-5 (Pb-Free) | 3000 / Tape & Reel    |
| LMV932DMR2G  | Dual               | 8              | Micro8 (Pb-Free) | 4000 / Tape & Reel    |
| LMV932DR2G   | Dual               | 8              | SOIC-8 (Pb-Free) | 2500 / Tape & Reel    |




<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.



SCALE 2:1

SC-88A (SC-70-5/SOT-353)  
CASE 419A-02  
ISSUE M

DATE 11 APR 2023



RECOMMENDED  
MOUNTING FOOTPRINT


\* For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS
3. 419A-01 OBSOLETE. NEW STANDARD 419A-02
4. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.1016MM PER SIDE.

| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN.        | NOM. | MAX. |
| A   | 0.80        | 0.95 | 1.10 |
| A1  | ---         | ---  | 0.10 |
| A3  | 0.20 REF    |      |      |
| b   | 0.10        | 0.20 | 0.30 |
| c   | 0.10        | ---  | 0.25 |
| D   | 1.80        | 2.00 | 2.20 |
| E   | 2.00        | 2.10 | 2.20 |
| E1  | 1.15        | 1.25 | 1.35 |
| e   | 0.65 BSC    |      |      |
| L   | 0.10        | 0.15 | 0.30 |

GENERIC MARKING  
DIAGRAM\*



\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

XXX = Specific Device Code

M = Date Code

▪ = Pb-Free Package

(Note: Microdot may be in either location)

STYLE 1:

- PIN 1. BASE
2. EMITTER
3. BASE
4. COLLECTOR
5. COLLECTOR

STYLE 2:

- PIN 1. ANODE
2. EMITTER
3. BASE
4. COLLECTOR
5. CATHODE

STYLE 3:

- PIN 1. ANODE 1
2. N/C
3. ANODE 2
4. CATHODE 2
5. CATHODE 1

STYLE 4:

- PIN 1. SOURCE 1
2. DRAIN 1/2
3. SOURCE 1
4. GATE 1
5. GATE 2

STYLE 5:

- PIN 1. CATHODE
2. COMMON ANODE
3. CATHODE 2
4. CATHODE 3
5. CATHODE 4

STYLE 6:

- PIN 1. EMITTER 2
2. BASE 2
3. EMITTER 1
4. COLLECTOR
5. COLLECTOR 2/BASE 1

STYLE 7:

- PIN 1. BASE
2. EMITTER
3. BASE
4. COLLECTOR
5. COLLECTOR

STYLE 8:

- PIN 1. CATHODE
2. COLLECTOR
3. N/C
4. BASE
5. EMITTER


STYLE 9:

- PIN 1. ANODE
2. CATHODE
3. ANODE
4. ANODE
5. ANODE






Note: Please refer to datasheet for style callout. If style type is not called out in the datasheet refer to the device datasheet pinout or pin assignment.

|                  |                          |                                                                                                                                                                                  |
|------------------|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98ASB42984B              | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | SC-88A (SC-70-5/SOT-353) | PAGE 1 OF 1                                                                                                                                                                      |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.


**TSOP-5 3.00x1.50x0.95, 0.95P**  
**CASE 483**  
**ISSUE P**

DATE 01 APR 2024


**GENERIC**  
**MARKING DIAGRAM\***

**Analog**

**Discrete/Logic**

XXX = Specific Device Code    XXX = Specific Device Code  
A = Assembly Location    M = Date Code  
Y = Year    ■ = Pb-Free Package  
W = Work Week  
■ = Pb-Free Package



(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "■", may or may not be present. Some products may not follow the Generic Marking.

**NOTES:**

1. DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5-2018.
2. ALL DIMENSION ARE IN MILLIMETERS (ANGLES IN DEGREES).
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OF GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.15 PER SIDE. DIMENSION D.
5. OPTIONAL CONSTRUCTION: AN ADDITIONAL TRIMMED LEAD IS ALLOWED IN THIS LOCATION. TRIMMED LEAD NOT TO EXTEND MORE THAN 0.2 FROM BODY.

| DIM | MILLIMETERS |       |       |
|-----|-------------|-------|-------|
|     | MIN.        | NOM.  | MAX.  |
| A   | 0.900       | 1.000 | 1.100 |
| A1  | 0.010       | 0.055 | 0.100 |
| A2  | 0.950 REF.  |       |       |
| b   | 0.250       | 0.375 | 0.500 |
| c   | 0.100       | 0.180 | 0.260 |
| D   | 2.850       | 3.000 | 3.150 |
| E   | 2.500       | 2.750 | 3.000 |
| E1  | 1.350       | 1.500 | 1.650 |
| e   | 0.950 BSC   |       |       |
| L   | 0.200       | 0.400 | 0.600 |
| θ   | 0°          | 5°    | 10°   |



**RECOMMENDED MOUNTING FOOTPRINT\***

\* FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERM/D.

|                         |                                     |                                                                                                                                                                                  |
|-------------------------|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98ARB18753C</b>                  | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>TSOP-5 3.00x1.50x0.95, 0.95P</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.






SCALE 1:1

**SOIC-8 NB**  
CASE 751-07  
ISSUE AK



DATE 16 FEB 2011



## NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. 751-01 THRU 751-06 ARE OBSOLETE. NEW STANDARD IS 751-07.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.80        | 5.00 | 0.189     | 0.197 |
| B   | 3.80        | 4.00 | 0.150     | 0.157 |
| C   | 1.35        | 1.75 | 0.053     | 0.069 |
| D   | 0.33        | 0.51 | 0.013     | 0.020 |
| G   | 1.27 BSC    |      | 0.050 BSC |       |
| H   | 0.10        | 0.25 | 0.004     | 0.010 |
| J   | 0.19        | 0.25 | 0.007     | 0.010 |
| K   | 0.40        | 1.27 | 0.016     | 0.050 |
| M   | 0°          | 8°   | 0°        | 8°    |
| N   | 0.25        | 0.50 | 0.010     | 0.020 |
| S   | 5.80        | 6.20 | 0.228     | 0.244 |

**GENERIC**  
**MARKING DIAGRAM\***


XXXXXX = Specific Device Code  
A = Assembly Location  
L = Wafer Lot  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

XXXXXX = Specific Device Code  
A = Assembly Location  
Y = Year  
WW = Work Week  
▪ = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

\*For additional information on our Pb-Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

**STYLES ON PAGE 2**

|                         |                    |                                                                                                                                                                                     |
|-------------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB42564B</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOIC-8 NB</b>   | <b>PAGE 1 OF 2</b>                                                                                                                                                                  |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**SOIC-8 NB**  
**CASE 751-07**  
**ISSUE AK**

DATE 16 FEB 2011

|                                                                                                                                                                                                   |                                                                                                                                                                                          |                                                                                                                                                                                    |                                                                                                                                                                                                        |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>STYLE 1:</b><br>PIN 1. EMITTER<br>2. COLLECTOR<br>3. COLLECTOR<br>4. EMITTER<br>5. EMITTER<br>6. BASE<br>7. BASE<br>8. EMITTER                                                                 | <b>STYLE 2:</b><br>PIN 1. COLLECTOR, DIE, #1<br>2. COLLECTOR, #1<br>3. COLLECTOR, #2<br>4. COLLECTOR, #2<br>5. BASE, #2<br>6. EMITTER, #2<br>7. BASE, #1<br>8. EMITTER, #1               | <b>STYLE 3:</b><br>PIN 1. DRAIN, DIE #1<br>2. DRAIN, #1<br>3. DRAIN, #2<br>4. DRAIN, #2<br>5. GATE, #2<br>6. SOURCE, #2<br>7. GATE, #1<br>8. SOURCE, #1                            | <b>STYLE 4:</b><br>PIN 1. ANODE<br>2. ANODE<br>3. ANODE<br>4. ANODE<br>5. ANODE<br>6. ANODE<br>7. ANODE<br>8. COMMON CATHODE                                                                           |
| <b>STYLE 5:</b><br>PIN 1. DRAIN<br>2. DRAIN<br>3. DRAIN<br>4. DRAIN<br>5. GATE<br>6. GATE<br>7. SOURCE<br>8. SOURCE                                                                               | <b>STYLE 6:</b><br>PIN 1. SOURCE<br>2. DRAIN<br>3. DRAIN<br>4. SOURCE<br>5. SOURCE<br>6. GATE<br>7. GATE<br>8. SOURCE                                                                    | <b>STYLE 7:</b><br>PIN 1. INPUT<br>2. EXTERNAL BYPASS<br>3. THIRD STAGE SOURCE<br>4. GROUND<br>5. DRAIN<br>6. GATE 3<br>7. SECOND STAGE Vd<br>8. FIRST STAGE Vd                    | <b>STYLE 8:</b><br>PIN 1. COLLECTOR, DIE #1<br>2. BASE, #1<br>3. BASE, #2<br>4. COLLECTOR, #2<br>5. COLLECTOR, #2<br>6. EMITTER, #2<br>7. EMITTER, #1<br>8. COLLECTOR, #1                              |
| <b>STYLE 9:</b><br>PIN 1. EMITTER, COMMON<br>2. COLLECTOR, DIE #1<br>3. COLLECTOR, DIE #2<br>4. EMITTER, COMMON<br>5. EMITTER, COMMON<br>6. BASE, DIE #2<br>7. BASE, DIE #1<br>8. EMITTER, COMMON | <b>STYLE 10:</b><br>PIN 1. GROUND<br>2. BIAS 1<br>3. OUTPUT<br>4. GROUND<br>5. GROUND<br>6. BIAS 2<br>7. INPUT<br>8. GROUND                                                              | <b>STYLE 11:</b><br>PIN 1. SOURCE 1<br>2. GATE 1<br>3. SOURCE 2<br>4. GATE 2<br>5. DRAIN 2<br>6. DRAIN 2<br>7. DRAIN 1<br>8. DRAIN 1                                               | <b>STYLE 12:</b><br>PIN 1. SOURCE<br>2. SOURCE<br>3. SOURCE<br>4. GATE<br>5. DRAIN<br>6. DRAIN<br>7. DRAIN<br>8. DRAIN                                                                                 |
| <b>STYLE 13:</b><br>PIN 1. N.C.<br>2. SOURCE<br>3. SOURCE<br>4. GATE<br>5. DRAIN<br>6. DRAIN<br>7. DRAIN<br>8. DRAIN                                                                              | <b>STYLE 14:</b><br>PIN 1. N-SOURCE<br>2. N-GATE<br>3. P-SOURCE<br>4. P-GATE<br>5. P-DRAIN<br>6. P-DRAIN<br>7. N-DRAIN<br>8. N-DRAIN                                                     | <b>STYLE 15:</b><br>PIN 1. ANODE 1<br>2. ANODE 1<br>3. ANODE 1<br>4. ANODE 1<br>5. CATHODE, COMMON<br>6. CATHODE, COMMON<br>7. CATHODE, COMMON<br>8. CATHODE, COMMON               | <b>STYLE 16:</b><br>PIN 1. EMITTER, DIE #1<br>2. BASE, DIE #1<br>3. EMITTER, DIE #2<br>4. BASE, DIE #2<br>5. COLLECTOR, DIE #2<br>6. COLLECTOR, DIE #2<br>7. COLLECTOR, DIE #1<br>8. COLLECTOR, DIE #1 |
| <b>STYLE 17:</b><br>PIN 1. VCC<br>2. V2OUT<br>3. V1OUT<br>4. TXE<br>5. RXE<br>6. VEE<br>7. GND<br>8. ACC                                                                                          | <b>STYLE 18:</b><br>PIN 1. ANODE<br>2. ANODE<br>3. SOURCE<br>4. GATE<br>5. DRAIN<br>6. DRAIN<br>7. CATHODE<br>8. CATHODE                                                                 | <b>STYLE 19:</b><br>PIN 1. SOURCE 1<br>2. GATE 1<br>3. SOURCE 2<br>4. GATE 2<br>5. DRAIN 2<br>6. MIRROR 2<br>7. DRAIN 1<br>8. MIRROR 1                                             | <b>STYLE 20:</b><br>PIN 1. SOURCE (N)<br>2. GATE (N)<br>3. SOURCE (P)<br>4. GATE (P)<br>5. DRAIN<br>6. DRAIN<br>7. DRAIN<br>8. DRAIN                                                                   |
| <b>STYLE 21:</b><br>PIN 1. CATHODE 1<br>2. CATHODE 2<br>3. CATHODE 3<br>4. CATHODE 4<br>5. CATHODE 5<br>6. COMMON ANODE<br>7. COMMON ANODE<br>8. CATHODE 6                                        | <b>STYLE 22:</b><br>PIN 1. I/O LINE 1<br>2. COMMON CATHODE/VCC<br>3. COMMON CATHODE/VCC<br>4. I/O LINE 3<br>5. COMMON ANODE/GND<br>6. I/O LINE 4<br>7. I/O LINE 5<br>8. COMMON ANODE/GND | <b>STYLE 23:</b><br>PIN 1. LINE 1 IN<br>2. COMMON ANODE/GND<br>3. COMMON ANODE/GND<br>4. LINE 2 IN<br>5. LINE 2 OUT<br>6. COMMON ANODE/GND<br>7. COMMON ANODE/GND<br>8. LINE 1 OUT | <b>STYLE 24:</b><br>PIN 1. BASE<br>2. EMITTER<br>3. COLLECTOR/ANODE<br>4. COLLECTOR/ANODE<br>5. CATHODE<br>6. CATHODE<br>7. COLLECTOR/ANODE<br>8. COLLECTOR/ANODE                                      |
| <b>STYLE 25:</b><br>PIN 1. VIN<br>2. N/C<br>3. REXT<br>4. GND<br>5. IOUT<br>6. IOUT<br>7. IOUT<br>8. IOUT                                                                                         | <b>STYLE 26:</b><br>PIN 1. GND<br>2. dv/dt<br>3. ENABLE<br>4. ILIMIT<br>5. SOURCE<br>6. SOURCE<br>7. SOURCE<br>8. VCC                                                                    | <b>STYLE 27:</b><br>PIN 1. ILIMIT<br>2. OVLO<br>3. UVLO<br>4. INPUT+<br>5. SOURCE<br>6. SOURCE<br>7. SOURCE<br>8. DRAIN                                                            | <b>STYLE 28:</b><br>PIN 1. SW_TO_GND<br>2. DASIC_OFF<br>3. DASIC_SW_DET<br>4. GND<br>5. V_MON<br>6. VBULK<br>7. VBULK<br>8. VIN                                                                        |
| <b>STYLE 29:</b><br>PIN 1. BASE, DIE #1<br>2. EMITTER, #1<br>3. BASE, #2<br>4. EMITTER, #2<br>5. COLLECTOR, #2<br>6. COLLECTOR, #2<br>7. COLLECTOR, #1<br>8. COLLECTOR, #1                        | <b>STYLE 30:</b><br>PIN 1. DRAIN 1<br>2. DRAIN 1<br>3. GATE 2<br>4. SOURCE 2<br>5. SOURCE 1/DRAIN 2<br>6. SOURCE 1/DRAIN 2<br>7. SOURCE 1/DRAIN 2<br>8. GATE 1                           |                                                                                                                                                                                    |                                                                                                                                                                                                        |

|                         |                    |                                                                                                                                                                                     |
|-------------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB42564B</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOIC-8 NB</b>   | <b>PAGE 2 OF 2</b>                                                                                                                                                                  |


**onsemi** and **onsemi** are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.



SCALE 2:1


**Micro8**  
**CASE 846A-02**  
**ISSUE K**

DATE 16 JUL 2020




TOP VIEW


NOTE 3



SIDE VIEW



END VIEW

**GENERIC**  
**MARKING DIAGRAM\***



XXXX = Specific Device Code  
A = Assembly Location  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

**NOTES:**

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE PROTRUSION SHALL BE 0.10 mm IN EXCESS OF MAXIMUM MATERIAL CONDITION.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSION OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.15 mm PER SIDE. DIMENSION E DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 mm PER SIDE. DIMENSIONS D AND E ARE DETERMINED AT DATUM F.
5. DATUMS A AND B ARE TO BE DETERMINED AT DATUM F.
6. A1 IS DEFINED AS THE VERTICAL DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE BODY.


**RECOMMENDED**  
**MOUNTING FOOTPRINT**

■ For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERM-10.

| DIM            | MILLIMETERS |      |      |
|----------------|-------------|------|------|
|                | MIN.        | NOM. | MAX. |
| A              | ---         | ---  | 1.10 |
| A1             | 0.05        | 0.08 | 0.15 |
| b              | 0.25        | 0.33 | 0.40 |
| c              | 0.13        | 0.18 | 0.23 |
| D              | 2.90        | 3.00 | 3.10 |
| E              | 2.90        | 3.00 | 3.10 |
| e              | 0.65 BSC    |      |      |
| H <sub>E</sub> | 4.75        | 4.90 | 5.05 |
| L              | 0.40        | 0.55 | 0.70 |

**STYLE 1:**

1. SOURCE
2. SOURCE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

**STYLE 2:**

1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. GATE 2
5. DRAIN 2
6. DRAIN 2
7. DRAIN 1
8. DRAIN 1

**STYLE 3:**

1. N-SOURCE
2. N-GATE
3. P-SOURCE
4. P-GATE
5. P-DRAIN
6. P-DRAIN
7. N-DRAIN
8. N-DRAIN

|                         |                    |                                                                                                                                                                                  |
|-------------------------|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB14087C</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>MICRO8</b>      | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)