

PANDUIT FINISHED GOODS PIN	CONDUCTOR RANGE	HEX KEY	SCREW QTY.	CAP (SCREW PORT) QTY.	CAP (WIREPORT) QTY.	A	L	N	TIG HTEN IN G TORQUE
PC SB 3 50 -2 S-4 Y	350 kcmil - # 10 STR	5/16	2	2	2	2 .17	1.920	2	275 in/lb
PC SB 3 50 -3 S-4 Y		5/16	3	3	3	3 .17	2.920	3	
PCSB350-4S-3Y		5/16	4	4	4	4 .17	3.920	4	
PCSB350-5S-3Y		5 / 16	5	5	5	5.17	4.920	5	
PC SB 350-6 S-2 Y		5 / 16	6	6	6	6.17	5.920	6	
PC SB 350-8 S-2 Y		5 / 16	8	8	8	8 .17	7.920	8	
PC SB 350-10 S-2 Y		5 / 16	10	10	2 0	10 .17	9.920	10	
PC SB 350-12 S-1Y		5/16	12	12	2 4	12 .17	11.9 2 0	12	
PC SB 3 50 -14 S-1Y		5/16	14	1.4	2 8	14 .17	13.920	14	



NOTEC:

- 1. UL486A-UL486B LISTED, DUAL RATED CU9AL FOR ALUMINUM OR COPPER CONDUCTORS. MEETS OR EXCEEDS ANSI C119.4
- 2. SEE TABLE FOR WIRE RANGE.
- 3. STRIP LENGTH: 1.06 +.06/-0
- 4. FOR TIGHTENING TORQUE SEE TABLE
- 5. VOLTAGE RATING: 600 V. MAX. BUILDING WIRE, 1000 V. MAX. IN SIGNS & FIXTURES.
- 6. TEMPERATURE RATING: 90 °C (CU9AL).
- 7. CONNECTOR BLOCK BODY ARE MADE FROM ALUMINUM. CONDUCTOR PORTS IN CONNECTOR BLOCK ARE PREFILLED WITH AN OXIDE-INHIBITING COMPOUND.
- 8. CONNECTOR TO INCLUDE TIN PLATED ALUMINUM CLAMPING SCREWS FOR EACH CONDUCTOR PORT.
- 9. INSULATION MATERIAL IS CLEAR PVC.
- 10. CLAMPING SCREW ACCESS PORTS AND ALL WIRE ENTRY PORTS ARE PROVIDED WITH REMOVABLE PLASTIC CLOSURE PLUGS.
- 11. ALL DIMENSIONS SHOWN ARE NOMINAL.
- 12 ONLY ONE CONDUCTOR PER PORT ALLOWED.

13 PACKAGE QTY: -12 = 12 PCS.

-6 = 6 PCS.

-4 = 4 PCS.

-3 = 3 PCS. -2 = 2 PCS.

14 THIS PART IS ROHS COMPLIANT

