



1-port omni antenna, 824–896 MHz, 360° HPBW, fixed electrical tilt

- Omnidirectional antenna
- Rugged, durable design, heavy duty radome for minimum tip deflection
- Invert mountable

Electrical Specifications

Frequency Band, MHz	824–896
Gain, dBi	11.1
Beamwidth, Horizontal, degrees	360
Beamwidth, Vertical, degrees	8.0
Beam Tilt, degrees	3
VSWR Return Loss, dB	1.5 14.0
PIM, 5th Order, 2 x 20 W, dBc	-150
Input Power per Port, maximum, watts	500
Polarization	Vertical
Impedance	50 ohm

General Specifications

Operating Frequency Band	824 – 896 MHz
Antenna Type	Omni
Band	Single band
Performance Note	Outdoor usage

Mechanical Specifications

RF Connector Quantity, total	1
RF Connector Quantity, low band	1
RF Connector Interface	7-16 DIN Female
Color	Light gray
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Radiator Material	Brass
Radome Material	Fiberglass, UV resistant
RF Connector Location	Bottom
Wind Loading, maximum	355.9 N @ 100 mph 80.0 lbf @ 100 mph
Wind Speed, maximum	362 km/h 225 mph

Dimensions

Length 3657.0 mm | 144.0 in

Outer Diameter 76.0 mm | 3.0 in

Net Weight, without mounting kit 12.0 kg | 26.5 lb

Regulatory Compliance/Certifications

Agency **Classification**

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system



Included Products

DB5091-3 — Pipe Mounting Kit for 3.5 in (88.9 mm) OD round members

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance