

## FEATURES


- Driver integrated 10Gb/s MI-DFB module for 800ps/nm optical transmission
- MI-DFB-LD (Modulator Integrated DFB Laser Diode) is included
- Modulator driver IC is included
- Built-in optical isolator, PIN-Photo diode for monitor, thermistor and thermo-electric cooler
- 800ps/nm (40km)

## DESCRIPTION

The FTM1141GF was developed to reduce the size and technical complexity of 10Gb/s optical board designs. This product, which includes a driver and modulator integrated laser in one package, eliminates the customer concerns regarding how to handle the RF interfacing between these two components on his board. By co-packaging these components a solution has also been achieved that offers greatly reduced board space.

This reduction in space is critical for next generation transponder applications.

The FTM1141GF has been designed with a differential co-planar electrical interface which allows for easy interfacing to RF lines on PC boards. The package and pinout are part of a multi-source agreement. This product is designed for 40km SONET/SDM applications and single channel drop links in DWDM systems.



## ABSOLUTE MAXIMUM RATINGS (Top=25°C, Unless otherwise specified)

| Parameter                                  | Symbol                               | Condition                    | Rating                            |                                  | Unit            |
|--------------------------------------------|--------------------------------------|------------------------------|-----------------------------------|----------------------------------|-----------------|
|                                            |                                      |                              | Min.                              | Max.                             |                 |
| Storage Temperature                        | T <sub>stg</sub>                     |                              | -40                               | 85                               | °C              |
| Operating Case Temperature                 | T <sub>op</sub> (T <sub>c</sub> )    |                              | 0                                 | 75                               | °C              |
| Optical Output Power                       | P <sub>f</sub>                       | CW                           | -                                 | 5                                | mW              |
| Laser Forward Current                      | I <sub>f</sub>                       | CW                           | -                                 | 150                              | mA              |
| Laser Reverse Voltage                      | V <sub>R</sub>                       | CW                           | -                                 | 2                                | V               |
| Power Supply Voltage                       | V <sub>SS</sub>                      |                              | -6.5                              | 0.3                              | V               |
| Modulator (Mod) modulation Control Voltage | V <sub>m</sub>                       |                              | -6.5                              | V <sub>SS</sub> +1.2<br>(max0.3) | V               |
| Mod Bias Control Voltage                   | V <sub>b</sub>                       |                              | -6.5                              | V <sub>SS</sub> +2.4<br>(max0.3) | V               |
| Cross Point Control Voltage                | V <sub>x1</sub> , (V <sub>x2</sub> ) |                              | V <sub>SS</sub> -4.8<br>(min-6.5) | V <sub>SS</sub> +2.4<br>(max0.3) | V               |
| Data Input Voltage                         | D <sub>in</sub> , D <sub>inB</sub>   | Differential<br>(AC-coupled) | -                                 | 1.6                              | V <sub>pp</sub> |
| ESD Tolerance                              | V <sub>esd</sub>                     | Note (1-1)                   | -                                 | 50                               | V               |
| ESD Tolerance                              | V <sub>esd</sub>                     | Note (1-2)                   | -                                 | 200                              | V               |
| Photodiode Forward Current                 | I <sub>DF</sub>                      |                              | -                                 | 1                                | mA              |
| Photodiode Reverse Voltage                 | V <sub>DR</sub>                      |                              | -                                 | 10                               | V               |
| TEC Voltage                                | V <sub>c</sub>                       | Cooling                      | -                                 | 2.5                              | V               |
|                                            |                                      | Heating                      | -2.5                              | -                                |                 |
| TEC Current                                | I <sub>c</sub>                       | Cooling                      | -                                 | 1.5                              | A               |
|                                            |                                      | Heating                      | -0.9                              | -                                |                 |
| Thermistor Temperature                     | T <sub>th</sub>                      | ATC operation                | 0                                 | +75                              | °C              |
| Lead Soldering Time                        |                                      | 260°C MAX                    | -                                 | 10                               | sec             |

OPTICAL SPECIFICATIONS (TLD=25°C, Tc=0 to 75°C and BOL, unless otherwise specified)  
LASER DIODE AND MODULATOR CHARACTERISTICS

| Parameter                   | Symbol           | Condition                | Limit |            |      | Unit |
|-----------------------------|------------------|--------------------------|-------|------------|------|------|
|                             |                  |                          | Min.  | Typ.       | Max. |      |
| Threshold Current           | I <sub>th</sub>  | CW                       | -     | -          | 25   | mA   |
| Operating Current           | I <sub>op</sub>  | Pf=Pop                   | 40    | 70         | 100  | mA   |
| Optical Output Power        | Pop              | Note (2a)                | -1    | -          | +2   | dBm  |
| Forward Voltage             | V <sub>F</sub>   | CW                       | -     | -          | 2.2  | V    |
| Extinction Ratio            | R <sub>ext</sub> | Pf=Pop, Note (2a)        | 8.2   | -          | -    | dB   |
| Peak Wavelength             | W <sub>p</sub>   | Pf=Pop, Note (2a)        | 1530  | -          | 1565 | nm   |
| Side Mode Suppression Ratio | SSR              | Pf=Pop, CW               | 35    | -          | -    | dB   |
| Optical Rise Time           | t <sub>r</sub>   | Note (3), 20% to 80%     | -     | -          | 30   | psec |
| Optical Fall Time           | t <sub>f</sub>   | Note (3), 20% to 80%     | -     | -          | 30   | psec |
| Optical Isolation           | I <sub>s</sub>   |                          | 25    | -          | -    | dB   |
| Tracking Error              | TE               | Note (2a)                | -0.5  | -          | +0.5 | dB   |
| Input Return Loss           | S <sub>11</sub>  | 130MHz to 10GHz, Tc=25°C | 6     | 10         | -    | dB   |
| Dispersion Penalty          | dP               | Note (2)                 | -     | -          | 2.0  | dB   |
| Eye Pattern Mask            | Msk              | Note (2a), 500 counts    |       | Error Free |      |      |

## MONITOR DIODE CHARACTERISTICS

| Parameter                 | Symbol         | Condition                                             | Limit |      |      | Unit |
|---------------------------|----------------|-------------------------------------------------------|-------|------|------|------|
|                           |                |                                                       | Min.  | Typ. | Max. |      |
| Monitor Current           | I <sub>m</sub> | I <sub>F</sub> =I <sub>op</sub> , V <sub>DR</sub> =5V | 100   | -    | 1500 | μA   |
| Monitor Dark Current      | I <sub>d</sub> | V <sub>DR</sub> =5V                                   | -     | 2    | 100  | nA   |
| Monitor Diode Capacitance | C <sub>t</sub> | V <sub>DR</sub> =5V, f=1MHz                           | -     | 5    | 15   | pF   |

## TEC &amp; THERMISTOR CHARACTERISTICS

| Parameter             | Symbol          | Condition | Limit |      |      | Unit |
|-----------------------|-----------------|-----------|-------|------|------|------|
|                       |                 |           | Min.  | Typ. | Max. |      |
| TEC Current           | I <sub>c</sub>  | Note (4)  | -     | -    | 1.4  | A    |
| TEC Voltage           | V <sub>c</sub>  | Note (4)  | -     | -    | 2.5  | V    |
| TEC Power Consumption | P <sub>c</sub>  | Note (4)  | -     | -    | 3.5  | W    |
| Thermistor Resistance | R <sub>th</sub> | TLD=25°C  | -     | 10   | -    | kΩ   |
| Thermistor B Constant | B               |           | 3270  | 3450 | 4000 | K    |

## DRIVER IC CHARACTERISTICS

| Parameter                                  | Symbol                               | Condition                 | Limit                |      |                      | Unit            |
|--------------------------------------------|--------------------------------------|---------------------------|----------------------|------|----------------------|-----------------|
|                                            |                                      |                           | Min.                 | Typ. | Max.                 |                 |
| Driver IC Supply Voltage                   | V <sub>SS</sub>                      |                           | -5.5                 | -5.2 | -5.0                 | V               |
| Driver IC Supply Current                   | I <sub>SS</sub>                      |                           | -                    | -    | 285                  | mA              |
| Modulator (Mod) Modulation Control Voltage | V <sub>m</sub>                       |                           | V <sub>SS</sub>      | -    | V <sub>SS</sub> +1.0 | V               |
| Mod Bias Control Voltage                   | V <sub>b</sub>                       |                           | V <sub>SS</sub>      | -    | V <sub>SS</sub> +2.2 | V               |
| Cross Point (XP) Control Voltage           | V <sub>x1</sub> , (V <sub>x2</sub> ) | X <sub>p</sub> =50%       | V <sub>SS</sub> +0.8 | -    | V <sub>SS</sub> +2.2 | V               |
| Data Input Voltage                         | Din, DinB                            | Differential (AC Coupled) | 0.5                  | -    | 1.0                  | V <sub>pp</sub> |

Note (1-1): Pin No. 3,4,5,6,7,9,11

Note (1-2): Pin No. 1,2,8,10,12-19

Note (2): Eudyna Test System

(a) Drive Condition

Bit Rate: 9.95328 Gb/s

Word Pattern: PRBS=2<sup>31</sup>-1

Mark Density: 50%

Laser Bias Current: I<sub>op</sub>

Laser Temperature(TLD): 25°C

Eye Pattern Mask: ITU-T Eye mask for STM-64

(b) Fiber Dispersion

800ps/nm

(c) Dispersion Penalty

Bit Error Rate=10<sup>-12</sup>

Note (3): Eudyna Test System

V<sub>b</sub>, V<sub>m</sub>, V<sub>x1</sub>(V<sub>x2</sub>) is set to make Pop and Rext within the specification

Note (4): Eudyna Test System

Operating Case Temperature: T<sub>c</sub>=+75°C


Laser Temperature:

25°C

Optical Output Power:


P<sub>f</sub>=Pop, Note (2a)

Typical Output Waveform  
Back to Back (with Filter)



9.95328Gb/s, NRZ, PRBS=2<sup>31</sup>-1, TLD=TC=25°C

Typical Application for Driver IC




For stable operation:

- 8-1. To prevent a dependence of "Cross point" on the supply voltage VSS,
  - (1) Use an external voltage source of -3.8V for "Vx2", or
  - (2) Control the voltage of "Vx1", so that the voltage difference "Vx1-Vx2" remain constant.
- 8-2. To prevent a dependence of "Modulation control voltage" on the supply voltage VSS, control the voltage of "Vm", so that the difference "Vm-VSS" remain constant.
- 8-3. To prevent a dependence of "Bias control voltage" on the supply voltage VSS, control the voltage of "Vb", so that the difference "Vb-VSS" remain constant.

# Driver Integrated 10Gb/s MI-DFB LD Module

# FTM1141GF



For further information please contact:

## Eudyna Devices USA Inc.

2355 Zanker Rd.  
San Jose, CA 95131-1138, U.S.A.  
TEL: (408) 232-9500  
FAX: (408) 428-9111  
[www.us.eudyna.com](http://www.us.eudyna.com)

## Eudyna Devices Europe Ltd.

Network House  
Norreys Drive  
Maidenhead, Berkshire SL6 4FJ  
United Kingdom  
TEL: +44 (0) 1628 504800  
FAX: +44 (0) 1628 504888

## Eudyna Devices Asia Pte Ltd.

Hong Kong Branch  
Rm. 1101, Ocean Centre, 5 Canton Rd.  
Tsim Sha Tsui, Kowloon, Hong Kong  
TEL: +852-2377-0227  
FAX: +852-2377-3921

## Eudyna Devices Inc.

Sales Division  
1, Kanai-cho, Sakae-ku  
Yokohama, 244-0845, Japan  
TEL: +81-45-853-8156  
FAX: +81-45-853-8170

## CAUTION

Eudyna Devices Inc. products contain **gallium arsenide (GaAs)** which can be hazardous to the human body and the environment. For safety, observe the following procedures:

- Do not put this product into the mouth.
- Do not alter the form of this product into a gas, powder, or liquid through burning, crushing, or chemical processing as these by-products are dangerous to the human body if inhaled, ingested, or swallowed.
- Observe government laws and company regulations when discarding this product. This product must be discarded in accordance with methods specified by applicable hazardous waste procedures.

Eudyna Devices Inc. reserves the right to change products and specifications without notice. The information does not convey any license under rights of Eudyna Devices Inc. or others.

© 2004 Eudyna Devices USA Inc.  
Printed in U.S.A.