



## HUBBELL USB Charger Receptacle Tamper-Resistant Duplex

### More Power - Charge Faster

- 3 Amps of USB Power
  - Charge Two Tablets Simultaneously
- Duplex Outlets
  - More Capacity

#### FEATURES

- Two USB ports 3 Amp, 5VDC, Type A, 2.0
- Tamper-Resistant (TR) decorator duplex
- Green LED indicator to show USB power available
- Spec grade design - impact and chemical resistant
- Back and side wire for solid or stranded wire
- Flush fit design

#### SPECIFICATIONS

- Electrical ratings: 15 Amp, 125VAC, USB 3 Amp, 5VDC
- Input voltage: 125VAC, 60Hz
- Circuit feed-through 20 Amp, 125 Volt
- #10-14 AWG gauge wire terminals
- Dielectric withstand: 2000V
- Operating temperature: maximum continuous 75° C; minimum -40° C (without impact)
- Meets UL94 for 5V flammability rating
- Complies with battery charging specification USB BC1.2
- Compatible with USB 1.1/2.0/3.0 devices, including Apple products
- Complies with Part 15 of the FCC rules
- cULus listed to UL498 and UL1310



Hubbell's USB Charger Receptacle provides both USB and electrical power in a standard single gang electrical opening. Designed to provide more charging options for personal electronics, the USB ports are capable of charging two tablets simultaneously. The 15 Amp tamper-resistant Style Line® decorator outlets provide additional power for appliance use.

#### APPLICATIONS

Ideal for use in renovation and replacement of existing receptacles to add capacity for USB charging. Especially suited for use in universities, dormitories, hotels, restaurants, airports, classrooms and homes. Perfect for new construction.

Designed for use with:

■ Apple® Products	■ Tablet computers
— iPad®	■ GPS
— iPod®	■ Smart Phones
— iPhone®	■ Mobile Phones
■ other USB compatible products	■ Digital Readers
	■ MP3 Players



*Apple, iPad, iPod and iPhone are registered trademarks of Apple, inc.*



## ORDERING INFORMATION

Description	Color	Catalog Number
USB Charger Tamper-Resistant Receptacle	Black	USB15X2BK
Two USB Type 2.0 Ports 3 Amp, 5 Volt DC	Gray	USB15X2GY
15 Amp, 125 Volt AC Decorator Duplex	Ivory	USB15X2I
	Light Almond	USB15X2LA
	White	USB15X2W



## Energy Information

USB Port Output	Energy consumed when USBs are not in use, per hour		Energy consumed when USBs are fully used, per hour	
	No Load Current	.0013A	Full Load Current	3.23A
	No load Watts	.63W	Full Load Watts	19.7W


Time to charge an iPAD® or similar tablet with the Hubbell USB Charger, from 0% battery charge to 100%, is estimated between 5 to 6 hours

Estimated annual cost to use a USB Charger Receptacle, charging 2 devices (tablets drawing maximum power), for 6 hours a day, at a Kilowatt cost of \$0.10

Hours of use (6)	x	kilowatt cost (\$0.10)	x	kilowatt usage per hour (19.7w/1000*)	x	365 days =	\$4.31
Hours of non-use (18)	x	kilowatt cost (\$0.10)	x	kilowatt usage per hour (.63w/1000*)	x	365 days =	\$0.41
Total hours (24)						Total cost per year	\$4.72

\* to convert watts to kilowatts, divide watts by 1000.

## DIMENSIONS



Note: For use with boxes deeper than 1.5" with internal AC/MC clamps.

**HUBBELL®**  
Wiring Device-Kellems

[www.hubbell-wiring.com](http://www.hubbell-wiring.com)

