




592 SERIES


3mm Bi-level Prism^{fi} CBI^{fi} Surface Mount LED BRIGHT SINGLE COLOR



FEATURES / BENEFITS

- ▲ Incorporates latest LED technology, specifically designed for surface mounting.
- ▲ Compatible with automatic placement equipment.
- ▲ Compatible with surface mount reflow soldering processes.
- ▲ Black housing enhances contrast ratio.
- ▲ Housing material meet UL-94V-0 flammability ratings.
- ▲ Patented Bi-level design provides increased indication without increased space.
- ▲ Illumination areas compatible with industry standard 3mm through-hole Bi-level Circuit Board Indicators.
- ▲ Packaged in moisture barrier bags for dry packaging per IPC/JEDEC J-STD-033.
- ▲ Helps to eliminate mixed technology pc board processing.

SPECIFICATIONS




PART NUMBER CODE

SERIES	Position 1	Package option
592	2X 2X	0XX
Position 2		
Color = 21) AlGaAs Red, 22) Green 24) AlInGaP Yellow, 00) blank		
Package Size Options -002 = 10 piece strip -013 = 13" reel dia.		

Note: Custom color combinations available upon request.
Check with factory for details.

PART NUMBER	COLOR COMBO
592-2121-0XX	AlGaAs Red/AlGaAs Red
592-2222-0XX	GREEN/GREEN
592-2727-0XX	AlInGaP Yellow/AlInGaP Yellow



Dialight Corporation

1501 Route 34 South • Farmingdale, NJ 07727 USA
Tel: (1) 732.919.3119 • Fax: (1) 732.751.5778 • www.dialight.com

a Roxboro Group Company

MDEF592D001_A





3mm Bi-level Prism^{fi} CBI^{fi}
Surface Mount LED, Bright Single Color

ABSOLUTE MAXIMUM RATINGS (T_A= 25°C)

Parameter	21	22	27
COLOR	AlGaAs Red	Green	AlInGaP Yellow
POWER DISSIPATION (derate linearly from 25°C mW/°C)	100mA 0.8	100mA 0.6	100mA 0.6
FORWARD DC CURRENT	40mW	30mW	50mW
PEAK FORWARD CURRENT (10 µsec)	200mW	120mW	160mW
OPERATING TEMPERATURE	-55°C to +100°C		
STORAGE TEMPERATURE	-55°C to +100°C		
SOLDERING TEMPERATURES CONVECTION IR VAPOR PHASE	235°C Peak, above 185°C for 90 sec., 215°C for 3 min.		

OPERATING CHARACTERISTICS (T_A= 25°C)

Parameters	Part No.	Color	Min	Typ	Max	Units	Test Cond.
FORWARD VOLTAGE V _F	21	AlGaAs Red		1.8	2.4	V	I _F =10mA
	22	Green		2.1	2.6		
	27	AlInGaP Yellow		2	2.4		
REVERSE VOLTAGE V _R	21	AlGaAs Red	5			V	I _F =10µA
	22	Green	5				
	27	AlInGaP Yellow	5				
DOMINANT WAVELENGTH Dom	21	AlGaAs Red		638		nm	
	22	Green		569			
	27	AlInGaP Yellow		595			
LUMINOUS INTENSITY I _v	21	AlGaAs Red		23.9		mcd	I _F =10mA
	22	Green		9.1			
	27	AlInGaP Yellow		33.6			
VIEWING ANGLE (2Θ _{1/2})	21	AlGaAs Red		40		deg.	
	22	Green		40			
	27	AlInGaP Yellow		40			

DIALIGHT RESERVES THE RIGHT TO MAKE CHANGES AT ANY TIME IN ORDER TO SUPPLY THE BEST PRODUCT POSSIBLE.



A4703



ISO 9001

Dialight Corporation

1501 Route 34 South • Farmingdale, NJ 07727 USA

Tel: (1) 732.919.3119 • Fax: (1) 732.751.5778 • www.dialight.com

●●●●●●●●●●●●●●●●●●●●
a Roxboro Group Company

MDEF592D001_A