

PART NO. ENG. NO.


02-06-2101	1560-(P901)
02-06-2103	1560-(P901)L
02-06-6101	1560-(561)
02-06-6102	1560-(561)L
02-06-6118	1560-(228)
02-06-6119	1560-(228)L
02-06-6116	1560-(231)
02-06-6112	1560-(231)L
02-06-6100	1560-(550)
02-06-6103	1560-(550)L
02-06-6105	1560-(591)
02-06-6104	1560-(591)L

LEGEND


1560-(****)*
P=PREPLATE
BLANK=POSTPLATE
FINISH CODE
FORM
BLANK=CHAIN
L=LOOSE

NOTES:

- MATERIAL: BRASS
- FINISHES:
 - HOT TIN DIP (.00051)/.000020 MIN.
 - SELECT GOLD PLATE (.00075)/.000030 MIN. IN CONTACT AREA, SELECT TIN (.00250)/.000100 MIN. IN CRIMP AREA OVER (.00125)/.000050 MIN. NICKEL OVERALL.
 - SELECT GOLD PLATE (.00125)/.000050 MIN. IN CONTACT AREA, SELECT TIN (.00250)/.000100 MIN. IN CRIMP AREA OVER (.00125)/.000050 MIN. NICKEL OVERALL.
 - SELECT GOLD PLATE (.00076)/.000030 MIN. IN CONTACT AREA, OVER (.00127)/.000050 MIN. NICKEL OVERALL.
 - SELECT GOLD PLATE (.00127)/.000050 MIN. IN CONTACT AREA, OVER (.00127)/.000050 MIN. NICKEL OVERALL WITH (.000025)/.000010 MAX. GOLD FLASH OVERALL.
 - SELECT GOLD PLATE (.00038)/.000015 MIN. IN CONTACT AREA, OVER (.00076)/.000030 MIN. NICKEL OVERALL WITH (.000025)/.000010 MAX. GOLD FLASH OVERALL.
- THE PRIMARY SHIPPING CARTON WILL BE LABELED, "COMPLIANT TO RoHS DIRECTIVE" 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC, AND CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH TIN-LEAD.
- PRODUCT SPECIFICATION: PS-02-06
- PACKAGING INFORMATION: NOT AVAILABLE
- TERMINAL FOR USE WITH (157)/.062 DIA. SERIES HOUSINGS AND WILL ACCEPT 18 THRU 24 AWG WIRE.




SECT. "A-A"




SECT. "B-B"

SCALE:10X



SECT. "C-C"

SCALE:10X



CARRIER VIEW
ACTUAL SIZE

AP	REVSE Sn/Pb PLATE REDRAWN TO ME10 UCP2004-2097 RHOLTS 5/07/04
A0	REINSTATE 02066105 UCP2003-1827 ELHAG, 03/02/24
AN	OBSOLETE P/N UCR2002-0270 COMERC 01/9/25
AM1	ADDED ISO VIEW UCR1998-0228 WANG 98-05-21
AM	REV. & REDRAWN PER ECR 10372 GEP 8-19-87 RW

QUALITY SYMBOLS		GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE 8:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		REVISE ON CAD ONLY	
		mm	INCH	DIMENSION STYLE		TITLE			
4 PLACES ± ---		± ---	± ---	IN/MM		DRAWN BY DATE		CRIMP TERMINAL, MALE	
3 PLACES ± ---		± .010	± .010	DRAWN BY DATE		GEP 1987/08/19		.062 DIA. FOR 18-24 AWG	
2 PLACES ± 0.25		± .014	± .014	CHECKED BY DATE		RW 1987/08/19		WIRE	
1 PLACE ± 0.35		± ---	± ---	APPROVED BY DATE		RAS 1987/08/19		MOLEX MOLEX INCORPORATED	
ANGULAR ± 1/2°		± ---	± ---	MATERIAL NO.		SEE CHART		SD-1560-*	
DRAFT WHERE APPLICABLE		MUST REMAIN WITHIN DIMENSIONS		SHEET NO.		1 OF 1			
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									

REFER TO REVISION BLOCK	EC NO: 2002/05/05	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14
EC NO: 2002/05/05	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14
CHKD: 2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14
APPR: FSMITH	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14
AP	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14	2004/05/14

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

02-06-6105