REV.
 CNN
 CNN DESCRIPTION
 Date
 Check in

 06
 TABLE ADDED
 17/02/2010
 Shoun Barron


 06
 TABLE ADDED
 18/02/2010
 Shoun Barron

A standard 4mm plug, with a rigid, screw on acetal body which comes in a range of colours for easy identification.

This range of product caters for a broad range of test instrumentation and speaker applications.

The plug pin comes with a solder bucket for secure cable fixing.

## Dimensions



Part	550	
	A cetal-LG chemical LUCEL	
Insulant	N127-LD/DN127-LD	A cetal C27021 R
Socket	Brass BS 2874 silver plated	
Spring		
Amps	10A	
Nominal working Voltage	50V	
Contact Resistance	10mΩ	
Maximum Temperature		
RTI	+ 110°C	
Minimum temperature	- 20°C	
Recommended		
Temperature	10A @55°C	
Voltage Breakdown	5000∨	
Conductor size	1.5m m²	
Colours	550-0100	Black
	550-0200	Blue
	550-0300	Brown
	550-0400	Green
	550-0500	Red
	550-0600	White
	550-0700	Yellow

## STANDARD 4mm PLUG - SOLDER BUCKET

A4



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF

AUPHA 3 MANUFACTURING.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION C

OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF RECHIBITED.

DEM Manufacturing, Dellton Emcon House

Horgreoves Way, Sawcillfe Ind. Park, Scunthorpe, North Lincolnhie, DNI15 8RF, UK

ANGULAR TOLERANCE: ±1\*

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETRES LINEAR TOLERANCE: NO DECIMAL PLACES :0.5mm 1 DECIMAL PLACE :0.25mm

FINISH - DEBURR AND BREA SHARP EDGES

IF IN DOUBT ASK
DO NOT SCALE DRAWING

MATERIAL -

DEBURR AND BREAK SHARP EDGES

DRAWN BY

APPROVED BY

THIRD ANGLE PROJECTION

SCALE 1:1

GENERAL SPECIFICATION 550 SERIES 4mm PLUG

550 SERIES

06 Release

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Deltron:

550-0100 550-0500 550-0700 550-0400 550-0600 550-0200