



**2N5484**  
**2N5485**  
**2N5486**

**MMBF5484**  
**MMBF5485**  
**MMBF5486**



NOTE: Source & Drain  
are interchangeable

## N-Channel RF Amplifier

This device is designed primarily for electronic switching applications such as low On Resistance analog switching. Sourced from Process 50.

### Absolute Maximum Ratings\*

TA = 25°C unless otherwise noted

| Symbol         | Parameter                                        | Value       | Units |
|----------------|--------------------------------------------------|-------------|-------|
| $V_{DG}$       | Drain-Gate Voltage                               | 25          | V     |
| $V_{GS}$       | Gate-Source Voltage                              | - 25        | V     |
| $I_{GF}$       | Forward Gate Current                             | 10          | mA    |
| $T_J, T_{stg}$ | Operating and Storage Junction Temperature Range | -55 to +150 | °C    |

\*These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

#### NOTES:

- 1) These ratings are based on a maximum junction temperature of 150 degrees C.
- 2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

### Thermal Characteristics

TA = 25°C unless otherwise noted

| Symbol          | Characteristic                          | Max         |                | Units |
|-----------------|-----------------------------------------|-------------|----------------|-------|
|                 |                                         | 2N5484-5486 | *MMBF5484-5486 |       |
| $P_D$           | Total Device Dissipation                | 350         | 225            | mW    |
|                 | Derate above 25°C                       | 2.8         | 1.8            | mW/°C |
| $R_{\theta JC}$ | Thermal Resistance, Junction to Case    | 125         |                | °C/W  |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient | 357         | 556            | °C/W  |

\*Device mounted on FR-4 PCB 1.6" X 1.6" X 0.06."

2N5484 / 5485 / 5486 / MMBF5484 / 5485 / 5486

# N-Channel RF Amplifier

(continued)

## Electrical Characteristics

TA = 25°C unless otherwise noted

| Symbol                              | Parameter                        | Test Conditions                                                                                                                                                                                          | Min                                        | Typ                  | Max                     | Units                                  |
|-------------------------------------|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|----------------------|-------------------------|----------------------------------------|
| <b>OFF CHARACTERISTICS</b>          |                                  |                                                                                                                                                                                                          |                                            |                      |                         |                                        |
| $V_{(BR)GSS}$                       | Gate-Source Breakdown Voltage    | $I_G = -1.0 \mu A, V_{DS} = 0$                                                                                                                                                                           | - 25                                       |                      |                         | V                                      |
| $I_{GSS}$                           | Gate Reverse Current             | $V_{GS} = -20 V, V_{DS} = 0$<br>$V_{GS} = -20 V, V_{DS} = 0, T_A = 100^\circ C$                                                                                                                          |                                            |                      | - 1.0<br>- 0.2          | nA<br>$\mu A$                          |
| $V_{GS(off)}$                       | Gate-Source Cutoff Voltage       | $V_{DS} = 15 V, I_D = 10 nA$                                                                                                                                                                             | - 0.3<br>- 0.5<br>- 2.0                    |                      | - 3.0<br>- 4.0<br>- 6.0 | V<br>V<br>V                            |
| <b>ON CHARACTERISTICS</b>           |                                  |                                                                                                                                                                                                          |                                            |                      |                         |                                        |
| $I_{DSS}$                           | Zero-Gate Voltage Drain Current* | $V_{DS} = 15 V, V_{GS} = 0$                                                                                                                                                                              | 5484<br>5485<br>5486                       | 1.0<br>4.0<br>8.0    | 5.0<br>10<br>20         | mA<br>mA<br>mA                         |
| <b>SMALL SIGNAL CHARACTERISTICS</b> |                                  |                                                                                                                                                                                                          |                                            |                      |                         |                                        |
| $g_{fs}$                            | Forward Transfer Conductance     | $V_{DS} = 15 V, V_{GS} = 0, f = 1.0 kHz$                                                                                                                                                                 | 5484<br>5485<br>5486                       | 3000<br>3500<br>4000 | 6000<br>7000<br>8000    | $\mu mhos$<br>$\mu mhos$<br>$\mu mhos$ |
| $Re(y_{is})$                        | Input Conductance                | $V_{DS} = 15 V, V_{GS} = 0, f = 100 MHz$<br>$V_{DS} = 15 V, V_{GS} = 0, f = 400 MHz$                                                                                                                     | 5484<br>5485 / 5486                        |                      | 100<br>1000             | $\mu mhos$<br>$\mu mhos$               |
| $g_{os}$                            | Output Conductance               | $V_{DS} = 15 V, V_{GS} = 0, f = 1.0 kHz$                                                                                                                                                                 | 5484<br>5485<br>5486                       |                      | 50<br>60<br>75          | $\mu mhos$<br>$\mu mhos$<br>$\mu mhos$ |
| $Re(y_{os})$                        | Output Conductance               | $V_{DS} = 15 V, V_{GS} = 0, f = 100 MHz$<br>$V_{DS} = 15 V, V_{GS} = 0, f = 400 MHz$                                                                                                                     | 5484<br>5485 / 5486                        |                      | 75<br>100               | $\mu mhos$<br>$\mu mhos$               |
| $Re(y_{fs})$                        | Forward Transconductance         | $V_{DS} = 15 V, V_{GS} = 0, f = 100 MHz$<br>$V_{DS} = 15 V, V_{GS} = 0, f = 400 MHz$                                                                                                                     | 5484<br>5485<br>5486                       | 2500<br>3000<br>3500 |                         | $\mu mhos$<br>$\mu mhos$<br>$\mu mhos$ |
| $C_{iss}$                           | Input Capacitance                | $V_{DS} = 15 V, V_{GS} = 0, f = 1.0 MHz$                                                                                                                                                                 |                                            |                      | 5.0                     | pF                                     |
| $C_{rss}$                           | Reverse Transfer Capacitance     | $V_{DS} = 15 V, V_{GS} = 0, f = 1.0 MHz$                                                                                                                                                                 |                                            |                      | 1.0                     | pF                                     |
| $C_{oss}$                           | Output Capacitance               | $V_{DS} = 15 V, V_{GS} = 0, f = 1.0 MHz$                                                                                                                                                                 |                                            |                      | 2.0                     | pF                                     |
| NF                                  | Noise Figure                     | $V_{DS} = 15 V, R_G = 1.0 k\Omega, f = 100 MHz$<br>$V_{DS} = 15 V, R_G = 1.0 k\Omega, f = 400 MHz$<br>$V_{DS} = 15 V, R_G = 1.0 k\Omega, f = 100 MHz$<br>$V_{DS} = 15 V, R_G = 1.0 k\Omega, f = 400 MHz$ | 5484<br>5484<br>5485 / 5486<br>5485 / 5486 | 4.0                  | 3.0<br><br>2.0<br>4.0   | dB<br>dB<br>dB<br>dB                   |


\*Pulse Test: Pulse Width  $\leq 300 ms$ , Duty Cycle  $\leq 2\%$

2N5484 / 5485 / 5486 / MMBF5484 / 5485 / 5486


# N-Channel RF Amplifier (continued)

## Typical Characteristics


### Transfer Characteristics




### Channel Resistance vs Temperature




### Transconductance Characteristics




### Common Drain-Source Characteristics



### Output Conductance vs Drain Current



### Transconductance Parameter Interactions




2N5484 / 5485 / 5486 / MMBF5484 / 5485 / 5486


# N-Channel RF Amplifier (continued)

## Typical Characteristics (continued)


Transconductance vs  
Drain Current




Noise Voltage vs Frequency




Capacitance vs Voltage



Noise Figure Frequency







Power Dissipation vs.  
Ambient Temperature







2N5484 / 5485 / 5486 / MMBF5484 / 5485 / 5486

Common Source Characteristics



Common Gate Characteristics



## TO-92 Tape and Reel Data




### TO-92 Packaging Configuration: Figure 1.0

FSCINT Label sample



F63TNR Label sample




### TO-92 TNR/AMMO PACKING INFORMATION

| Packing | Style | Quantity | EOL code |
|---------|-------|----------|----------|
| Reel    | A     | 2,000    | D26Z     |
|         | E     | 2,000    | D27Z     |
| Ammo    | M     | 2,000    | D74Z     |
|         | P     | 2,000    | D75Z     |

Unit weight = 0.22 gm  
 Reel weight with components = 1.04 kg  
 Ammo weight with components = 1.02 kg  
 Max quantity per intermediate box = 10,000 units

### AMMO PACK OPTION

See Fig 3.0 for 2 Ammo Pack Options




### (TO-92) BULK PACKING INFORMATION

| EOL CODE    | DESCRIPTION                                                                           | LEADCLIP DIMENSION | QUANTITY    |
|-------------|---------------------------------------------------------------------------------------|--------------------|-------------|
| J18Z        | TO-18 OPTION STD                                                                      | NO LEAD CLIP       | 2.0 K / BOX |
| J05Z        | TO-5 OPTION STD                                                                       | NO LEAD CLIP       | 1.5 K / BOX |
| NO EOL CODE | TO-92 STANDARD STRAIGHT FOR: PKG 92, 94 (NON PROELECTRON SERIES), 96                  | NO LEADCLIP        | 2.0 K / BOX |
| L34Z        | TO-92 STANDARD STRAIGHT FOR: PKG 94 (PROELECTRON SERIES BCXXX, BFXXX, BSRXXX), 97, 98 | NO LEADCLIP        | 2.0 K / BOX |



### BULK OPTION

See Bulk Packing Information table





# TO-92 Tape and Reel Data, continued

## TO-92 Reeling Style Configuration: Figure 2.0




## TO-92 Radial Ammo Packaging Configuration: Figure 3.0



# TO-92 Tape and Reel Data, continued


TO-92 Tape and Reel Taping  
Dimension Configuration: Figure 4.0



| ITEM DESCRIPTION                   | SYMBOL | DIMENSION              |
|------------------------------------|--------|------------------------|
| Base of Package to Lead Bend       | b      | 0.098 (max)            |
| Component Height                   | Ha     | 0.928 (+/- 0.025)      |
| Lead Clinch Height                 | HO     | 0.630 (+/- 0.020)      |
| Component Base Height              | H1     | 0.748 (+/- 0.020)      |
| Component Alignment ( side/side )  | Pd     | 0.040 (max)            |
| Component Alignment ( front/back ) | Hd     | 0.031 (max)            |
| Component Pitch                    | P      | 0.500 (+/- 0.020)      |
| Feed Hole Pitch                    | PO     | 0.500 (+/- 0.008)      |
| Hole Center to First Lead          | P1     | 0.150 (+0.009, -0.010) |
| Hole Center to Component Center    | P2     | 0.247 (+/- 0.007)      |
| Lead Spread                        | F1/F2  | 0.104 (+/- 0.010)      |
| Lead Thickness                     | d      | 0.018 (+0.002, -0.003) |
| Cut Lead Length                    | L      | 0.429 (max)            |
| Taped Lead Length                  | L1     | 0.209 (+0.051, -0.052) |
| Taped Lead Thickness               | t      | 0.032 (+/- 0.006)      |
| Carrier Tape Thickness             | t1     | 0.021 (+/- 0.006)      |
| Carrier Tape Width                 | W      | 0.708 (+0.020, -0.019) |
| Hold - down Tape Width             | WO     | 0.236 (+/- 0.012)      |
| Hold - down Tape position          | W1     | 0.035 (max)            |
| Feed Hole Position                 | W2     | 0.360 (+/- 0.025)      |
| Sprocket Hole Diameter             | DO     | 0.157 (+0.008, -0.007) |
| Lead Spring Out                    | S      | 0.004 (max)            |

Note : All dimensions are in inches.

TO-92 Reel  
Configuration: Figure 5.0





| ITEM DESCRIPTION                 | SYMBOL | MINIMUM | MAXIMUM |
|----------------------------------|--------|---------|---------|
| Reel Diameter                    | D1     | 13.975  | 14.025  |
| Arbor Hole Diameter (Standard)   | D2     | 1.160   | 1.200   |
| Arbor Hole Diameter (Small Hole) | D3     | 0.650   | 0.700   |
| Core Diameter                    | D4     | 3.100   | 3.300   |
| Hub Recess Inner Diameter        | D5     | 2.700   | 3.100   |
| Hub Recess Depth                 | W1     | 0.370   | 0.570   |
| Flange to Flange Inner Width     | W2     | 1.630   | 1.690   |
| Hub to Hub Center Width          | W3     |         | 2.090   |

Note: All dimensions are inches

## TO-92 Package Dimensions



### TO-92 (FS PKG Code 92, 94, 96)




Scale 1:1 on letter size paper

Dimensions shown below are in:  
inches [millimeters]

Part Weight per unit (gram): 0.1977

TO-92 (92,94,96)


| PIN | 92 |   | 94 |   | 96 |   |
|-----|----|---|----|---|----|---|
|     | B  | F | B  | F | B  | F |
| 1   | E  | D | E  | D | B  | S |
| 2   | B  | S | C  | G | E  | D |
| 3   | C  | G | B  | S | C  | G |



## SOT-23 Tape and Reel Data



### SOT-23 Packaging Configuration: Figure 10




#### Packaging Description:


SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 177mm diameter reel. The reels are dark blue in color and are made of polystyrene plastic (anti-static coated). Other option comes in 10,000 units per 13" or 330mm diameter reel. This and some other options are described in the Packaging Information table.

These full reels are individually labeled and placed inside a standard intermediate made of recyclable corrugated brown paper with a Fairchild logo printing. One pizza box contains eight reels maximum. And these intermediate boxes are placed inside a labeled shipping box which comes in different sizes depending on the number of parts shipped.

| SOT-23 Packaging Information |                         |            |
|------------------------------|-------------------------|------------|
| Packaging Option             | Standard (no flow code) | D87Z       |
| Packaging type               | TNR                     | TNR        |
| Qty per Reel/Tube/Bag        | 3,000                   | 10,000     |
| Reel Size                    | 7" Dia                  | 13"        |
| Box Dimension (mm)           | 187x107x183             | 343x343x64 |
| Max qty per Box              | 24,000                  | 30,000     |
| Weight per unit (gm)         | 0.0082                  | 0.0082     |
| Weight per Reel (kg)         | 0.1175                  | 0.4006     |
| Note/Comments                |                         |            |




#### SOT-23 Unit Orientation



#### Human Readable Label sample




### SOT-23 Tape Leader and Trailer Configuration: Figure 20



## SOT-23 Tape and Reel Data, continued


### SOT-23 Embossed Carrier Tape

Configuration: Figure 3.0




| Dimensions are in millimeter |                 |                 |               |                 |                   |                 |             |                 |               |               |                 |                   |               |                 |
|------------------------------|-----------------|-----------------|---------------|-----------------|-------------------|-----------------|-------------|-----------------|---------------|---------------|-----------------|-------------------|---------------|-----------------|
| Pkg type                     | A0              | B0              | W             | D0              | D1                | E1              | E2          | F               | P1            | P0            | K0              | T                 | Wc            | Tc              |
| SOT-23 (8mm)                 | 3.15<br>+/-0.10 | 2.77<br>+/-0.10 | 8.0<br>+/-0.3 | 1.55<br>+/-0.05 | 1.125<br>+/-0.125 | 1.75<br>+/-0.10 | 6.25<br>min | 3.50<br>+/-0.05 | 4.0<br>+/-0.1 | 4.0<br>+/-0.1 | 1.30<br>+/-0.10 | 0.228<br>+/-0.013 | 5.2<br>+/-0.3 | 0.06<br>+/-0.02 |


Notes: A0, B0, and K0 dimensions are determined with respect to the EIA/Jedec RS-481 rotational and lateral movement requirements (see sketches A, B, and C).



Sketch A (Side or Front Sectional View)  
Component Rotation




Sketch B (Top View)  
Component Rotation



Sketch C (Top View)  
Component lateral movement

### SOT-23 Reel Configuration: Figure 4.0





| Dimensions are in inches and millimeters |             |               |              |                                   |               |             |                                   |               |                             |
|------------------------------------------|-------------|---------------|--------------|-----------------------------------|---------------|-------------|-----------------------------------|---------------|-----------------------------|
| Tape Size                                | Reel Option | Dim A         | Dim B        | Dim C                             | Dim D         | Dim N       | Dim W1                            | Dim W2        | Dim W3 (LSL-USL)            |
| 8mm                                      | 7" Dia      | 7.00<br>177.8 | 0.059<br>1.5 | 512 +0.020/-0.008<br>13 +0.5/-0.2 | 0.795<br>20.2 | 2.165<br>55 | 0.331 +0.059/-0.000<br>8.4 +1.5/0 | 0.567<br>14.4 | 0.311 - 0.429<br>7.9 - 10.9 |
| 8mm                                      | 13" Dia     | 13.00<br>330  | 0.059<br>1.5 | 512 +0.020/-0.008<br>13 +0.5/-0.2 | 0.795<br>20.2 | 4.00<br>100 | 0.331 +0.059/-0.000<br>8.4 +1.5/0 | 0.567<br>14.4 | 0.311 - 0.429<br>7.9 - 10.9 |

## SOT-23 Package Dimensions




### SOT-23 (FS PKG Code 49)



Scale 1:1 on letter size paper

Dimensions shown below are in:  
inches [millimeters]

Part Weight per unit (gram): 0.0082



NOTE : UNLESS OTHERWISE SPECIFIED

1. STANDARD LEAD FINISH 150 MICROINCHES / 3.81 MICROMETERS  
MINIMUM TIN / LEAD (SOLDER) ON ALLOY 42
2. REFERENCE JEDEC REGISTRATION TO-236, VARIATION AB, ISSUE G, DATED JUL 1993

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                      |                     |                     |            |
|----------------------|---------------------|---------------------|------------|
| ACEx™                | FASTr™              | PowerTrench®        | SyncFET™   |
| Bottomless™          | GlobalOptoisolator™ | QFET™               | TinyLogic™ |
| CoolFET™             | GTO™                | QS™                 | UHC™       |
| CROSSVOLT™           | HiSeC™              | QT Optoelectronics™ | VCX™       |
| DOVE™                | ISOPLANAR™          | Quiet Series™       |            |
| E <sup>2</sup> CMOS™ | MICROWIRE™          | SILENT SWITCHER®    |            |
| EnSigna™             | OPTOLOGIC™          | SMART START™        |            |
| FACT™                | OPTOPLANAR™         | SuperSOT™-3         |            |
| FACT Quiet Series™   | PACMAN™             | SuperSOT™-6         |            |
| FAST®                | POP™                | SuperSOT™-8         |            |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                                            |
|--------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                                    |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.                                                       |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.                                                   |