

f	F	F	F	F	F	F	F	F	F	F		F	F	F	F	F	F	F	F	F	F	F	F													
e	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9														
d	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9														
c	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9														
b	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9														
a	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9														
z	F	F	F	F	F	F	F	F	F	F		F	F	F	F	F	F	F	F	F	F	F	F													
P O S	0 1							0 5							1 0							1 5							2 0							2 5

Technical drawings of the connector showing dimensions in millimeters.

Top View (Left):

- Overall width: 15.40 ± 0.50
- Pin pitch: 11.70 ± 0.10 (NOTE 3)
- Pin height: $13.45^{+0.15}_{-0.10}$
- Pin diameter: $3.00^{+0}_{-0.10}$
- Pin pitch (bottom): 2.00 ± 0.05 (24X)

Side View (Right):

- Overall height: 12.00
- Pin pitch: 2.00 ± 0.05 (6X)
- Overall length: 50.00 MAX.

Top View (Right):

- Overall length: 48.00
- Pin pitch: 2.00 ± 0.05 (24X)

Notes:

- NOTE 3: Points to the pin pitch dimension.
- NOTE 5: Points to the dashed rectangle in the top view.
- NOTE 6: Points to the pin pitch dimension.

Technical drawing showing two catheters, labeled 9 and F, with dimensions and a seating plane indicated.

Catheter 9:

- Dimension 8.2 (mm) is shown from the left end to the seating plane.
- Dimension 16.0 (mm) is shown from the seating plane to the right end.

Catheter F:

- Dimension 9.7 (mm) is shown from the left end to the seating plane.
- Dimension 16.0 (mm) is shown from the seating plane to the right end.

The seating plane is indicated by a vertical line and labeled "SEATING PLANE FOR CONNECTOR".

A diagram of a rectangular field with a width of 48.00 and a height of 12.00. The field is filled with a grid of small circles, representing points. The grid is 12 columns wide and 12 rows high, with a total of 144 points. The points are arranged in a regular pattern, with a dashed line indicating the center of the field.

LEAD FREE INDICATOR : LF = LEAD FREE
(DIGIT 15 & 16)

PLATING CODE (DIGIT 13 AND 14)
(REF DRW NO. BS,C , 201844 , 003)

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON
PRODUCTION LOCATION
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001

CATALOG NO: HM2P65PN5115----

[illegible]