



TECHNICAL CHARACTERISTICS

MATERIAL  
INSULATOR: NYLON 66  
FLAMMABILITY RATING: UL94-V0  
COLOR: WHITE  
PITCH: 2.00MM

ENVIRONMENTAL  
OPERATING TEMPERATURE: -25°C UP TO 85°C  
COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL  
INSULATOR RESISTANCE: >1000 MOHM  
DIELECTRIC WITHSTANDING VOLTAGE: 800V AC/MN

STANDARD  
CERTIFIED: E323964

PACKAGING  
BAG

DIMENSION  
A = 2.00 x (NB. PIN - 1)  
B = 2.00 x (NB. PIN) + 0.60  
C = 2.00 x (NB. PIN) + 1.70

RoHS Compliant								
G	20-NOV-15	C DIMENTION	ES	<div>PROJECTION:</div>	<div>GENERAL TOLERANCE</div> <div>.X = <math>\pm</math> 0.2</div> <div>.XX = <math>\pm</math> 0.15</div>	<div></div>		
F	26-MAY-14	OPE TEMPERATURE	QL					
E	06-AUG-13	CHARACTERISTIC	QL					
D	17-NOV-09	STANDARD	JP					
C	28-OCT-09	W. VOLTAGE	JP	<div>APPROVAL: BBu</div>	UNIT: MM	<div>DESCRIPTION: 2.00 MM FEMALE TERMINAL HOUSING</div>		<div>SIZE</div> <div>A4</div>
B	02-JUN-09	C DIMENSION	JP		SCALE:			
A	01-NOV-08	PDF	CH		SHEET: 1/2	<div>WERI PART NO: 620 0xx 113 322</div>		
REV	DATE	FILE	BY		DRAW: JERRY CHEN			

[illegible]