

Features

- ◆ 2" x 1" metal package
- ◆ Ultra wide 4:1 input voltage range
9–36, 18–75, 43–160 VDC
- ◆ EN 50155 approval for railway
applications
- ◆ Thermal shock and vibration resistant
according EN 61373
- ◆ Input filter meets EN 55022 class B
without external components
- ◆ High efficiency up to 89%
- ◆ No minimum load required
- ◆ Operating temperature range
–40°C to +85°C
- ◆ Under voltage lock-out circuit
- ◆ Remote On/Off
- ◆ Output voltage adjustable
- ◆ Lead free design, RoHS compliant
- ◆ 3-year product warranty



The TEN 20WIR series is a family of high performance 20 Watt dc/dc converter modules featuring ultra wide 4:1 input voltage ranges in a 2" x 1" package with industry-standard footprint. Input voltages up to 160 VDC, excellent EMC characteristics and EN 50155 approval make this product the best choice for many demanding applications in railroad and transportation systems. Further standard features include remote On/Off, over voltage protection, under voltage lockout and short circuit protection. Low input current characteristics at minimal load make these converters also the ideal solution for battery-operated systems. Typical applications are in wireless networks, telecom/datacom, industry control systems and measurement equipments.

Models

Order code	Input voltage range	Output voltage	Output current max.	Efficiency typ.
TEN 20-2410WIR	9 – 36 VDC (24 VDC nominal)	3.3 VDC	4500 mA	85 %
TEN 20-2411WIR		5.0 VDC	4000 mA	88 %
TEN 20-2412WIR		12 VDC	1670 mA	89 %
TEN 20-2413WIR		15 VDC	1330 mA	88 %
TEN 20-2422WIR		±12 VDC	±833 mA	88 %
TEN 20-2423WIR		±15 VDC	±667 mA	89 %
TEN 20-4810WIR	18 – 75 VDC (48 VDC nominal)	3.3 VDC	4500 mA	85 %
TEN 20-4811WIR		5.0 VDC	4000 mA	88 %
TEN 20-4812WIR		12 VDC	1670 mA	89 %
TEN 20-4813WIR		15 VDC	1330 mA	89 %
TEN 20-4822WIR		±12 VDC	±833 mA	88 %
TEN 20-4823WIR		±15 VDC	±667 mA	89 %
TEN 20-7210WIR	43 – 160 VDC (110 VDC nominal)	3.3 VDC	4500 mA	85 %
TEN 20-7211WIR		5.0 VDC	4000 mA	87 %
TEN 20-7212WIR		12 VDC	1670 mA	88 %
TEN 20-7213WIR		15 VDC	1330 mA	89 %
TEN 20-7222WIR		±12 VDC	±833 mA	88 %
TEN 20-7223WIR		±15 VDC	±667 mA	89 %

Input Specifications

Input current (no load)	24 Vin models: 6 mA typ. 48 Vin models: 4 mA typ. 110 Vin models: 3 mA typ.
Input current (full load)	24 Vin, 3.3 VDC models: 730 mA typ. 24 Vin, other models: 950 mA typ. 48 Vin, 3.3 VDC models: 365 mA typ. 48 Vin, other models: 475 mA typ. 110 Vin, 3.3 VDC models: 160 mA typ. 110 Vin, other models: 210 mA typ.
Start-up voltage	24 Vin models: 9.0 VDC (or lower) 48 Vin models: 18 VDC (or lower) 110 Vin models: 43 VDC (or lower)
Under voltage shut down (lock-out circuit)	24 Vin models: 8.0 VDC typ. 48 Vin models: 16 VDC typ. 110 Vin models: 40 VDC typ.
Surge voltage (1 sec.)	24 Vin models: 50 V max. 48 Vin models: 100 V max. 110 Vin models: 170 V max.
Reflected ripple current	300 mA _{p-p} typ.
Conducted noise	24 & 48 Vin models: EN 55022 class B without external components 110 Vin models: EN 55022 class A without external components
ESD (electrostatic discharge)	EN 61000-4-2, air ±8 kV, contact ±6 kV, perf. criteria A
Radiated immunity	EN 61000-4-3, 20 V/m, perf. criteria A
Fast transient / surge (with external input capacitor)	EN 61000-4-4, ±2 kV, perf. criteria A EN 61000-4-5, ±2 kV perf. criteria A
– external input capacitor	24 & 48 Vin models: Nippon chemi-con KY 220 µF, 100 V, ESR 48 mOhm 110 Vin models: Rubycon BXF series, 100 µF / 250 V
Conducted immunity	EN 61000-4-6, 10 V _{rms} , perf. criteria A

Output Specifications

Voltage set accuracy	±1 %
Voltage adjustment range	±10 % (single output models only)
Regulation	– Input variation Vin min. to Vin max. 0.2 % max. – Load variation 0 – 100 % single output models: 0.5 % max. dual output models: 1 % max. – Load cross variation 25 % / 100 % 5 % max.
Minimum load	not required
Temperature coefficient	±0.02 %/K
Ripple and noise (20 MHz bandwidth, measured with 1 µF/ 50 V MLCC)	3.3 & 5.0 VDC models: 75 mV _{p-p} typ. other models: 100 mV _{p-p} typ.
Start up time	– Power On 30 ms typ. (constant resistive load) – Remote On 30 ms typ.
Transient response (25% load step change)	250 µs typ.
Short circuit protection	indefinite (automatic recovery)
Over load protection	150 % of I _{out} max. typ.
Over voltage protection (only single output models)	3.3 VDC models: 3.7 – 5.4 V 5 VDC models: 5.6 – 7.0 V 12 VDC models: 13.5 – 19.6 V 15 VDC models: 16.8 – 20.5 V

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Output Specifications


Capacitive load	3.3 VDC models:	7000 μ F
	5.0 VDC models:	5000 μ F
	12 VDC models:	850 μ F
	15 VDC models:	700 μ F
	± 12 VDC models:	500 μ F (each output)
	± 15 VDC models:	350 μ F (each output)

General Specifications


Temperature ranges	– Operating	–40°C to +85°C (with derating)
	– Case temperature	+105°C max.
	– Storage	–55°C to +125°C
Power derating	– Natural convection	4.5 %/K above 73°C
	– Natural convection with heat sink (optional)	5.3 %/K above 78°C
Thermal impedance	– Natural convection	12°C/W
	– Natural convection with heat sink (optional)	10°C/W
Humidity (non condensing)		5 – 95 % rel. H max.
Isolation voltage (60 sec.)	– Input / Output	1500 VDC
Isolation resistance	– Input / Output	>1000 M Ohm
Isolation capacitance	– Input / Output	3000 pF max.
Switching frequency		330 kHz typ. (pulse width modulation PWM)
Thermal shock, mechanical shock & vibration		EN 61373, MIL-STD-810F
– Test conditions		www.tracopower.com/products/mil810.pdf
Safety standards		UL/cUL 60950-1, IEC/EN 60950-1, EN 50155
Safety approvals	– UL/cUL	www.ul.com -> certifications -> File e188913
	– Railway	www.tracopower.com/products/ten20wir-coc.pdf
Remote On/Off	– On:	3.0 ... 15 VDC or open circuit
	– Off:	0 ... 1.2 VDC or short circuit pin 2 and pin 6
	– Off idle current:	2.5 mA
Reliability, calculated MTBF (MIL-HDBK-217F, at +25°C, ground benign)		500'000 Mio. h
Environmental compliance	– Reach	www.tracopower.com/products/ten20wir-reach.pdf
	– RoHS	RoHS directive 2011/65/EU

Output Voltage Adjustment (for single output models only)

Trim up



Trim down



Nominal output voltage at open Trim input
 adjustment range $\pm 10\%$, R_u , R_d to be advised


Application note: www.tracopower.com/products/ten20wir-application.pdf

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Physical Specifications

Casing material	copper, nickel plated
Baseplate material	non conductive FR4
Potting material	silicon (UL94V-0 rated)
Weight	30 g (1.06 oz)
Soldering temperature	max. +265°C / 10 sec.

Outline Dimensions



Pin-Out

Pin	Single	Dual
1	+Vin (Vcc)	+Vin (Vcc)
2	-Vin (GND)	-Vin (GND)
3	+Vout	+Vout
4	Trim	Common
5	-Vout	-Vout
6	Remote On/Off	

Dimensions in [mm], () = Inch
Pin diameter: 1.0 ±0.1 (0.04 ±0.004)
Pin pitch tolerances: ±0.25 (±0.01)
Case tolerances: ±0.5 (±0.02)

Heat-Sink (Option)

Order code: TEN-HS1
(cont.: heat-sink, thermal pad, 2 clamps)

Material: Aluminum

Finish: Anodic treatment (black)

Weight: 17g (0.60oz) without converter




Thermal impedance after assembling: 10 K/W



Note:

Before attaching the heatsink, the product label on converter has to be removed for optimal performance.

For volume orders we can supply the converters with heatsink already mounted. Please contact us for a relative quotation.



Dimensions in mm, () = Inch

Specifications can be changed without notice! Make sure you are using the latest documentation, downloadable at www.tracopower.com