



THESE DRAWINGS ARE THE PROPERTY OF QUALTEK ELECTRONICS AND NOT TO BE REPRODUCED FOR OR COMMUNICATED TO A THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AN OFFICER OF QUALTEK ELECTRONICS.


Revision					
Rev.	Description	Date	Approved		














CONTROLLED

5	Cover back of the body, NYLON Black Color	1
4	Contact PIN Brass Strip t=0.7mm Tin Plated	1
3	Contact PIN Brass Strip t=0.7mm Tin Plated	1
2	Contact PIN Brass Strip t=0.7mm Tin Plated	1
1	Body Insulator NYLON Black Color	1

Dim range	Tolerance +/-	Qualtek Electronics Corp. PPC DIVISION			
(mm)	(mm)	Part Number: 739W-X2/30 ROHS Compliant			
0-1	0.15	/ 39VV-AZ/ 30 Compliant			
1-6	0.20	Description: SNAP-IN 20 AMP T-SLOT RECEPTACLE			
6-18	0.30				
18-50	0.50		UNIT: mm		
50-120	0.70				
		Drawn / Date	Checked / Date	Approved / Date	
120-250	0.90	D.Povozhaev 05-14-07 05-14-07		JJH / 05-14-07	
250-500	1.20				

NOTE:

RATING: 20A 125V AC

RECOMMENDED TO USE SOLID WIRE ONLY

PANEL THICKNESS: 0.8~1.8mm

APPROVALS: UL, cUL RoHS COMPLIANT

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Qualtek: 739W-X2/30