

LOC	DIST	REVISIONS				
A1	-	P	LTR	DESCRIPTION		DATE
				SEE SHEET 1 OF 2		

21	6	38.5	30	45	42.5	38.5	36.5	B (GROOVES) Nuten A-C A (GROOVES B-C) (Nuten B_C)		5-966140-6 A 	4-966140-6 A 	18.3g	4	7	TAB (43.4mm)	CuSn0.15/0.20	SEL. SILVER PLATED
									3	7	TAB (34.4mm)		CuSn0.15/0.20	SEL. SILVER PLATED			
									2	7	TAB (25.4mm)		CuSn0.15/0.20	SEL. SILVER PLATED			
									5	1	21 POS. HOUSING		PA66-GF13	NATURAL/natur			
18	5	33.5	25	40	37.5	33.5	31.5			6-966140-6 C 	3-966140-6 C 	18.3g	4	7	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
									3	7	TAB (34.4mm)		CuSn4	SEL. SILVER PLATED			
									2	7	TAB (25.4mm)		CuSn4	SEL. SILVER PLATED			
									1	1	21 POS. HOUSING		PA66-GF13	BLACK/schwarz			
15	4	28.5	20	35	32.5	28.5	26.5			6-966140-1 C 	3-966140-1 C 	16.0g	4	6	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
									3	6	TAB (34.4mm)		CuSn4	SEL. SILVER PLATED			
									2	6	TAB (25.4mm)		CuSn4	SEL. SILVER PLATED			
									1	1	18 POS. HOUSING		PA66-GF13	BLACK/schwarz			
12	3	23.5	15	30	27.5	23.5	21.5			6-966140-2 C 	3-966140-2 C 	13.6g	4	5	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
									3	5	TAB (34.4mm)		CuSn4	SEL. SILVER PLATED			
									2	5	TAB (25.4mm)		CuSn4	SEL. SILVER PLATED			
									1	1	15 POS. HOUSING		PA66-GF13	BLACK/schwarz			
9	2	18.5	10	25	22.5	18.5	16.5		6-966140-3 C 	3-966140-3 C 	11.2g	4	4	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED	
								3	4	TAB (34.4mm)		CuSn4	SEL. SILVER PLATED				
								2	4	TAB (25.4mm)		CuSn4	SEL. SILVER PLATED				
								5	1	12 POS. HOUSING		PA66-GF13	NATURAL/natur				
6	1	13.5	5	20	17.5	13.5	11.5		6-966140-4 C 	3-966140-4 C 	8.9g	4	3	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED	
								3	3	TAB (34.4mm)		CuSn4	SEL. SILVER PLATED				
								2	3	TAB (25.4mm)		CuSn4	SEL. SILVER PLATED				
								1	1	9 POS. HOUSING		PA66-GF13	BLACK/schwarz				
									6-966140-5 C 	3-966140-5 C 	6.6g	4	2	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED	
								3	2	TAB (34.4mm)		CuSn4	SEL. SILVER PLATED				
								2	2	TAB (25.4mm)		CuSn4	SEL. SILVER PLATED				
								1	1	6 POS. HOUSING		PA66-GF13	BLACK/schwarz				
POSITIONS Polzahl	n	a±0.2	b	c	d _{0.2}	e _{0.25}	f	CODING Kodierung	CAVITY NUMBERING Kammerbezeichnung	ORDER NO. REV. Bestell-Nr.	ORDER NO. REV. Bestell-Nr.	WEIGHT Gewicht	POS.	QTY Stueck	DESCRIPTION Benennung Einzelteil	MATERIAL Werkstoff	SURFACE/Oberflaeche COLOUR/ Farbe

21	6	38.5	30	45	42.5	38.5	36.5	B (GROOVES) Nuten A-C	A (GROOVES B-C) (Nuten B_C)		8-966140-6 A 	1-966140-6 A 	18.3g	4	7	TAB (43.4mm)	CuSn4	TINNED/verzinkt						
										3	7	TAB (34.4mm)		CuSn4	TINNED/verzinkt									
										2	7	TAB (25.4mm)		CuSn4	TINNED/verzinkt									
18	5	33.5	25	40	37.5	33.5	31.5			A (GROOVES B-C) (Nuten B_C)		9-966140-6 F 	966140-6 F 	18.3g	4	7	TAB (43.4mm)	CuSn4	TINNED/verzinkt					
												3	7		TAB (34.4mm)	CuSn4	TINNED/verzinkt							
												2	7		TAB (25.4mm)	CuSn4	TINNED/verzinkt							
15	4	28.5	20	35	32.5	28.5	26.5					A (GROOVES B-C) (Nuten B_C)		9-966140-1 F 	966140-1 F 	16.0g	1	1	21 POS. HOUSING	PA66-GF13	BLACK/schwarz			
														4	6		TAB (43.4mm)	CuSn4	TINNED/verzinkt					
														3	6		TAB (34.4mm)	CuSn4	TINNED/verzinkt					
														A (GROOVES B-C) (Nuten B_C)		9-966140-2 F 	966140-2 F 	13.6g	2	6	TAB (25.4mm)	CuSn4	TINNED/verzinkt	
																1	1		18 POS. HOUSING	PA66-GF13	BLACK/schwarz			
																4	5		TAB (43.4mm)	CuSn4	TINNED/verzinkt			
								A (GROOVES B-C) (Nuten B_C)								9-966140-3 F 	966140-3 F 	11.2g	3	5	TAB (34.4mm)	CuSn4	TINNED/verzinkt	
																2	5		TAB (25.4mm)	CuSn4	TINNED/verzinkt			
																1	1		15 POS. HOUSING	PA66-GF13	BLACK/schwarz			
12	3	23.5	15	30	27.5	23.5	21.5			B (GROOVES) Nuten A-C	A (GROOVES B-C) (Nuten B_C)						8-966140-3 A 	1-966140-3 A 	11.2g	4	4	TAB (43.4mm)	CuSn4	TINNED/verzinkt
																3	4	TAB (34.4mm)		CuSn4	TINNED/verzinkt			
																2	4	TAB (25.4mm)		CuSn4	TINNED/verzinkt			
												A (GROOVES B-C) (Nuten B_C)				9-966140-1 F 	966140-1 F 	11.2g	5	1	12 POS. HOUSING	PA66-GF13	NATURAL/natur	
																4	4		TAB (43.4mm)	CuSn4	TINNED/verzinkt			
																3	4		TAB (34.4mm)	CuSn4	TINNED/verzinkt			
9	2	18.5	10	25	22.5	18.5	16.5							A (GROOVES B-C) (Nuten B_C)		9-966140-4 F 	966140-4 F 	8.9g	2	4	TAB (25.4mm)	CuSn4	TINNED/verzinkt	
																1	1		12 POS. HOUSING	PA66-GF13	BLACK/schwarz			
																4	3		TAB (43.4mm)	CuSn4	TINNED/verzinkt			
6	1	13.5	5	20	17.5	13.5	11.5	A (GROOVES B-C) (Nuten B_C)								9-966140-5 F 	966140-5 F 	6.6g	3	3	TAB (34.4mm)	CuSn4	TINNED/verzinkt	
																2	3		TAB (25.4mm)	CuSn4	TINNED/verzinkt			
																1	1		9 POS. HOUSING	PA66-GF13	BLACK/schwarz			
POSITIONS Polzahl	n	a±0.2	b	c	d_0.2	e_0.25	f			CODING Kodierung	CAVITY NUMBERING Kammerbezeichnung						ORDER NO. REV. Bestell-Nr.	ORDER NO. REV. Bestell-Nr.	WEIGHT Gewicht	POS.	QTY Stueck	DESCRIPTION Benennung Einzelteil	MATERIAL Werkstoff	SURFACE/Oberflaeche
																								COLOUR/ Farbe