

Part Number: SL15 8R006

### Ordering Different Lead Types:

Inside Kinked Leads	Use <b>-A</b> after Ametherm's part #
Outside Kinked Leads	Use <b>-B</b> after Ametherm's part #

For example: to order an inside kinked lead use part number SL15 8R006-A



### Electrical Specifications:

Resistance @ 25°C	8.0 $\Omega$ $\pm$ 20%
Max Steady State Current Up to 65°C	6.0 A
Max Recommended Energy Rating (Joules)	55.0 J
Actual Failure Point of Instantaneous Energy (Joules)	120.0 J
Resistance @ 100% of Max Current	0.078 $\Omega$
Resistance @ 50% of Max Current	0.160 $\Omega$
Body Temperature @ 100% Current Rating	182 °C
Dissipation Constant	18mW/°C
Thermal Time Constant	54 seconds
Material Type	"C"
Max Recommended Capacitance @ 120VAC/265VAC	3800 $\mu$ F/780 $\mu$ F

### Mechanical Specifications:

D	15.0 $\pm$ 0.5 mm
T	4.5 $\pm$ 0.2 mm
Lead Diameter	0.8 $\pm$ 0.1 mm
S	7.8 $\pm$ 2.0 mm
L	38.0 $\pm$ 9.0 mm
Straight Leads Coating Run Down	5.0 $\pm$ 1.0 mm
B	7.50 $\pm$ 0.70 mm
C	2.82 $\pm$ 0.5 mm
Coating Run Down on the Straight Leads	5.00 $\pm$ 0.5 mm