




TRG25 SERIES

25W SWITCHING ADAPTER



Features

- * Universal Input: 90~264Vac
 - * Meets EMI Meets EN55022 Class "B" and CISPR/FCC Class B
 - * Continuous Short Circuit Protection
 - * Over Voltage Protection
 - * Meet CEC & ErP Level V
- (Output Cable Length $\leq$ 1800mm)
 (TRG25033: Output Cable Length $\leq$ 720mm)
 (TRG25050: Output Cable Length $\leq$ 1220mm)



Ordering information

TRG25XXX	- X	XX	X	XX
Model No.	AC Plug Type	DC Plug Type	OVP	DC Cable Length and Type
	A: USA 2 Pin		E: With OVP	01: 720mm
	E: Europe 2 Pin			02: 1220mm
	U: British 3 Pin			03: 1800mm
	S: Australia 2 Pin			11: 720mm with Ferrite Core
				12: 1220mm with Ferrite Core
				13: 1800mm with Ferrite Core
				* 18AWG / UL1185
				* 16AWG / UL1185 for Vo:5V,3.3V

MODEL	OUTPUT VOLTAGE	OUTPUT CURRENT	RIPPLE & NOISE NOTE 1	VOLTAGE ACCURACY NOTE 2	LINE REGULATION NOTE 3	LOAD REGULATION NOTE 4	(%) EFF. (Typ.) NOTE 5
TRG25033	3.3V	4.0A	50mV	$\pm 2\%$	$\pm 1\%$	$\pm 6\%$	74%
TRG25050	5V	4.0A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 6\%$	76%
TRG25090	9V	2.5A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 5\%$	79%
TRG25120	12V	2.1A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 5\%$	83%
TRG25150	15V	1.67A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 3\%$	84%
TRG25180	18V	1.4A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 2\%$	85%
TRG25240	24V	1.05A	1%	$\pm 2\%$	$\pm 1\%$	$\pm 2\%$	85%

Specifications

INPUT SPECIFICATIONS:

Voltage	90~264Vac
Frequency	47 to 63Hz
Inrush Current	0.7A max.
Inrush Current	50A max. @240Vac
Conducted EMI	CISPR/FCC Class B
Leakage Current	0.25mA max.

OUTPUT SPECIFICATIONS:

Holdup Time	10ms typ. @115Vac
Short Circuit Protection	Continuous(Auto Recovery)
Over Voltage Protection	TVS Component to Clamp
Temperature Coefficient	±0.05%/°C

GENERAL SPECIFICATIONS:

Isolation	Input to output = 4,242VDC
Operating Temperature	0 ~ 60°C (see derating curve)
Storage Temperature	-20~85°C
Humidity	93% RH max. Non condensing
Cooling	Natural Convection
Switching Frequency	65KHz Typical
MTBF	MIL-HDBK-217F, GB, 25°C/115VAC 300K hrs min.
Altitude	2000m
Dimensions	3.169x1.932x2.205Inches (80.5x49.06x56.00mm)
Weight	280g(0.62 Pounds)

SAFETY AND EMC:


Emission and Immunity	EN55022 Class B, FCC Part 15 Class B
	EN61000-6-3, EN61000-3-2, EN61000-3-3
	EN55024, EN61204-3, EN61000-6-1
Safety	IEC60950-1, EN60950-1, UL60950-1

NOTE:

1. Add a 0.1uF ceramic capacitor and a 10uF E.L. capacitor to output for Ripple & Noise measuring @20MHz BW.
2. Voltage setpoint at 60% full load.
3. Line regulation measured from 100Vac to 240Vac, full load.
4. Load regulation measured from 60% to 100% full load and from 60% to 20% load (60% +/- 40% full load).
5. Typical efficiency at 230VAC and full load at 25°C.
6. "Various TR Series adapters are PSE certified. PSE certification alone is not sufficient for importation into Japan. A valid PSE mark must contain the name of the importer as shown in the example below. If PSE mark is required, the name of the registered importer must be supplied to Cincon on order placement. Product labels will not contain PSE mark if importer name is not supplied. Consult factory or local representative for details".



TRG25 Series Derating Curve




Typical at 25°C, nominal line and 75% load, unless otherwise Specified

Mechanical Specification

All Dimensions are in inches(mm)

Tolerance: Inches: X. XXX±0.02

Millimeters: X. XX±0.5



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cincon:

[TRG25050-E-11E02](#) [TRG25033-A-11E01](#) [TRG25033-E-12E01](#) [TRG25033-E-11E01](#) [TRG25050-A-11E02](#)
[TRG25033-S-12E01](#) [TRG25033-U-12E01](#) [TRG25050-E-12E02](#) [TRG25050-A-12E02](#) [TRG25033-S-11E01](#)
[TRG25050-S-12E02](#) [TRG25050-U-12E02](#) [TRG25033-U-11E01](#) [TRG25050-S-11E02](#) [TRG25050-U-11E02](#)
[TRG250120-A-11E03-Level-V](#) [TRG250120-A-12E03-Level-V](#) [TRG250150-A-11E03-Level-V](#) [TRG250150-A-12E03-](#)
[Level-V](#) [TRG250180-A-11E03-Level-V](#) [TRG250180-A-12E03-Level-V](#) [TRG250240-A-11E03-Level-V](#) [TRG250240-A-](#)
[12E03-Level-V](#) [TRG25050-A-11E02-Level-V](#) [TRG25050-A-12E02-Level-V](#) [TRG250120-A-35E03-Level-V](#)
[TRG250120-A-36E03-Level-V](#) [TRG250120-A-39E03-Level-V](#) [TRG250120-A-40E03-Level-V](#) [TRG250120-A-48E03-](#)
[Level-V](#) [TRG250120-A-49E03-Level-V](#) [TRG250240-A-35E03-Level-V](#) [TRG250240-A-36E03-Level-V](#) [TRG250240-A-](#)
[39E03-Level-V](#) [TRG250240-A-40E03-Level-V](#) [TRG250240-A-48E03-Level-V](#) [TRG250240-A-49E03-Level-V](#)
[TRG25033-A-35E01-Level-V](#) [TRG25033-A-36E01-Level-V](#) [TRG25033-A-39E01-Level-V](#) [TRG25033-A-40E01-Level-V](#)
[TRG25033-A-48E01-Level-V](#) [TRG25033-A-49E01-Level-V](#) [TRG25050-A-35E02-Level-V](#) [TRG25050-A-36E02-Level-](#)
[V](#) [TRG25050-A-39E02-Level-V](#) [TRG25050-A-40E02-Level-V](#) [TRG25050-A-48E02-Level-V](#) [TRG25050-A-49E02-](#)
[Level-V](#) [TRG250240-A-12E03](#) [TRG250150-A-12E03](#) [TRG250120-A-12E03](#) [TRG250180-A-11E03](#) [TRG250240-A-](#)
[11E03](#) [TRG250120-A-11E03](#) [TRG250150-A-11E03](#) [TRG250180-A-12E03](#) [TRG250120-E-11E03-Level-V](#)
[TRG250120-E-12E03-Level-V](#) [TRG250120-S-11E03-Level-V](#) [TRG250120-S-12E03-Level-V](#) [TRG250120-U-11E03-](#)
[Level-V](#) [TRG250120-U-12E03-Level-V](#) [TRG250150-E-11E03-Level-V](#) [TRG250150-E-12E03-Level-V](#) [TRG250150-S-](#)
[11E03-Level-V](#) [TRG250150-S-12E03-Level-V](#) [TRG250150-U-11E03-Level-V](#) [TRG250150-U-12E03-Level-V](#)
[TRG250180-E-11E03-Level-V](#) [TRG250180-E-12E03-Level-V](#) [TRG250180-S-11E03-Level-V](#) [TRG250180-S-12E03-](#)
[Level-V](#) [TRG250180-U-11E03-Level-V](#) [TRG250180-U-12E03-Level-V](#) [TRG250240-E-11E03-Level-V](#) [TRG250240-E-](#)
[12E03-Level-V](#) [TRG250240-S-11E03-Level-V](#) [TRG250240-S-12E03-Level-V](#) [TRG250240-U-11E03-Level-V](#)
[TRG250240-U-12E03-Level-V](#) [TRG25033-A-11E01-Level-V](#) [TRG25033-E-11E01-Level-V](#) [TRG25033-E-12E01-Level-V](#)
[TRG25033-S-11E01-Level-V](#) [TRG25033-S-12E01-Level-V](#) [TRG25033-U-11E01-Level-V](#) [TRG25033-U-12E01-Level-](#)
[V](#) [TRG25050-E-11E02-Level-V](#) [TRG25050-E-12E02-Level-V](#) [TRG25050-S-11E02-Level-V](#) [TRG25050-S-12E02-](#)
[Level-V](#) [TRG25050-U-11E02-Level-V](#) [TRG25050-U-12E02-Level-V](#) [TRG25033-A-12E01-LEVEL-V](#) [TRG250120-A-](#)
[01E03-Level-V](#) [TRG250120-A-02E03-Level-V](#) [TRG250120-E-01E03-Level-V](#) [TRG250120-E-02E03-Level-V](#)
[TRG250120-S-01E03-Level-V](#)