


Inductive Sensor uproX®

Bi10U-EM30H-AP6X-H1141




- Threaded barrel, M30x1
- Stainless steel
- Duroplast front cap, high mechanical and thermal resistance
- Factor 1 for all metals
- Degree of protection IP68
- Magnetic field immune
- Increased temperature range
- High switching frequency

Type	Bi10U-EM30H-AP6X-H1141
Ident-No.	1636412
Rated operating distance Sn	10,0 mm
Mounting mode	flush
Hysteresis H	3...15 %
Max. relative temperature drift	≤ 15 % v.E
Min. repeat accuracy	≤ 2 % v.E
Operation temperature	-30...85 °C
Rated operational voltage (DC) U_e	10...30 VDC
Max. ripple	≤ 10 % U _{SS}
Rated operational current (DC) I _e	200 mA
No-load current I ₀	≤ 15,0 mA
Max. OFF-state current	≤ 0,1 mA
Max. switching frequency	≤ 2,0 kHz
Rated insulation voltage	0,5 kV
Output function	normally open, PNP
Short-circuit protection	yes, cyclic
Max. voltage drop at I _e	≤ 1,8 V
Wire brakage and reverse polarity protection	yes, complete
Degree of protection / protection class	IP 68; 2
Housing style	threaded barrel; EM30H
Housing diameter	30,0 mm
Dimensions	62,0 mm
Housing material	stainless steel; V2A 1.4301
Active face	plastic; Duroplast
Max. fixing torque of coupling nut	≤ 90,0 Nm
Wiring	connector; M12x1 eurocon
Vibration resistance	55 Hz (1 mm)
Shock resistance	30 x g (11 ms)

Switching status indication LED; yellow

3-wire DC, 10-30VDC
Normally open, PNP-output
Connector, M12x1 eurocon

Wiring diagram





Function principles

Inductive sensors serve for wear-free and non contact detection of metal objects. Uprox Factor 1-sensors have considerable advantages because of their patented fer-rite-less 3-coil system. They detect all metals with the same operating distance, are magnetic field immune and have high operating distances.

Inductive Sensor uproX®

Bi10U-EM30H-AP6X-H1141

Mounting accessories

Typ	Ident-No.	Text	Dimension drawing
SKN/M30	69664	Protective teflon caps; Material PTFE; For use in welding facilities and grinding machines with strong sparking	
QM-30	6945103	Fixing clamps; Material: chrome-plated brass	
BST-30B	6947216	Fixing clamps; Material: PA6	