


Axial Lead Fuses



Slow Blow



Mechanical Dimensions



Dimensions : Millimetres

Electrical Characteristics

Rated Current	1 Inches	2 Inches
	Minimum	Maximum
0.5 A to 5 A	4 Hours	120 Seconds

Interrupting Ratings:

50 A at 125 V ac

50 A at 125 V dc

Environmental Specifications:

Operating Temperature : -55°C to +125°C

Shock : MIL-STD-202, method 213, condition 1 (100 G's peak for 6 milliseconds)

Vibration : MIL-STD-202, method 201 (10 - 55 Hz); method 204, test condition C (55 - 200 Hz at 10 G's peak)

Moisture Resistance : MIL-STD-202, method 106

Physical Specifications:

Materials

Encapsulated, epoxy-coated body and solder coated copper wire leads

Lead Wire : Diameter : 0.64 mm

Part Number Table

Description	Part Number
Fuse, Axial, Slow Blow, 0.5 A	MCPSP 0.5A 125V
Fuse, Axial, Slow Blow, 1 A	MCPSP 1A 125V
Fuse, Axial, Slow Blow, 1.5 A	MCPSP 1.5A 125V
Fuse, Axial, Slow Blow, 2 A	MCPSP 2A 125V
Fuse, Axial, Slow Blow, 2.5 A	MCPSP 2.5A 125V
Fuse, Axial, Slow Blow, 3 A	MCPSP 3A 125V
Fuse, Axial, Slow Blow, 4 A	MCPSP 4A 125V
Fuse, Axial, Slow Blow, 5 A	MCPSP 5A 125V

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.