




Tape is wound on a low-sloughing plastic core.

RoHS 2; REACH and Conflict Minerals Statement

None of the RoHS 2 restricted materials or REACH substances of very high concern as of 2014/06/16; or conflict minerals are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Desco [Limited Warranty at Desco.com](#)

No sulfur, surfactants amines; or silicone based material (adhesive, film backing, release material) is used in the manufacture of our cellulose tape.

Wescorp Tape Storage and Limited Warranty:

The user must determine the suitability for use of an ESD tape for his particular application. For best results, tape inventory should be continually replenished. It is recommended that rolls of tape be stored flat and rotated (flipped over to the other side) periodically. Tapes should be stored in a dry, well ventilated room with a reasonably consistent temperature of 68°F (20°C) and be protected from exposure to direct sunlight. Tape should not be stored in ultraviolet sunlight, moisture, or heat. Tape over one year old should be evaluated by the user to determine acceptability for the user's application. Desco Industries, Inc. recommends those tracking useful life of product to use shipping/invoice date as Desco Industries, Inc. expressly warrants that for a period of one (1) year from the date of purchase, our Wescorp Brand ESD Tape will be free of defects in material (parts) and workmanship (labor). See details of Limited Warranty online at [Desco.com/Warranty.aspx](#)

*Wescorp is a Desco Industries brand.

Note: Tape rolls may vary slightly in color.

ESD Cellulose Tape

For general purpose applications

- Meets ANSI/ESD S20.20 and packaging standard ANSI/ESD SS41
- Film Thickness: 1.9 mil 0.0019", (0.06 mm)
- Adhesive: Rubber based - non staining, absorbs moisture
- Film surface resistance: 1×10^9 to $< 1 \times 10^{11}$ ohms per ANSI/ESD STM11.11
- Temperature Range -10°C - 71°C (14°F - 160°F)
100°C for 10 min max
- Available in clear, clear with ESD symbols, and clear with ESD symbols with yellow stripe. Marking is approved symbols of Mil STD-1285* and ANSI/ESD S8.1.
- Symbols printed in between film and adhesive; will not rub off.



Tape	0.5"	.75"	1"	2"	Core	Length
Antistatic Clear Cellulose	79200	79201	79202		1"	36 yds
	79203	79204	79205	79206	3"	72 yds
Antistatic Clear Cellulose with Symbols	79209	79210	79211	79212	3"	72 yds
Antistatic Clear Cellulose w/Symbols w/ Yellow Stripe	79275	79276	79277	79278	3"	72 yds

Width tolerance $\pm 1/32"$

Tape widths are nominal metric ± 0.8 mm ($\pm 1/32"$)

1/4"	is	6 mm nominal	or	0.236"
1/2"	is	12 mm nominal	or	0.472"
3/4"	is	18 mm nominal	or	0.709"
1"	is	24 mm nominal	or	0.945"
2"	is	48 mm nominal	or	1.890"

*Military organizations sometimes use MIL-STD-1285 for hardware marking and that document once required the use of the "three arrows in a circle" symbol. That symbol has been changed for consistency with industry marking to the "hand in triangle" ESD Susceptibility symbol."
(Ref: ESD TR20.20 section 5.3.14.1)



Specifications and procedures subject to change without notice

DESCO

WESCORP* ESD CELLULOSE TAPE, PLASTIC CORE

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710
WEB SITE: [Desco.com](#) PHONE (909) 627-8178 FAX (909) 627-7449

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
WEB SITE: [Desco.com](#) PHONE (781) 821-8370 FAX (781) 575-0172

**DRAWING
NUMBER**
79200

DATE:
January
2015