




QRP 

PROTECTING PEOPLE, PRODUCTS
& PROCESSES WORLDWIDESM

Quality you expect.
Reliability you can count on.
Performance you require.



Founded in 1974, QRP, Incorporated is recognized worldwide as a leading producer and innovator of gloves and fingercots in a wide variety of applications. The Company emphasizes products for critical environments, including cleanrooms and ESD control. QRP has developed unique products for protection of employees against thermal extremes and against a wide array of chemicals. In addition to these highly specialized gloves and fingercots, QRP offers products for controlled environments and general use. All QRP products are engineered to the highest standards to increase process yields across a broad range of end uses.

www.QRPGloves.com

QRP adheres to all recommended requirements in the manufacturing of our gloves and fingercots:

Governmental

FED-STD-209E
Fed Test Method 101C
Fed Test Method 191
Fed Spec A-A-50855A
Fed Spec A-A-53134A
Cal OSHA Title 8, Art. 10.1

Military

MIL-HDBK-263B
MIL-G-82242C
MIL-STD-168B
MIL-STD-1246C

Nongovernmental

ANSI/ASQC-Z1.4
ANSI/ESD SP15.1
ASTM:
D130, D257, D412, D573,
D882, D991, D1353, D2420,
D3577, D3578, D3572,
D3772, D5250, D6319,
E595, F311, F312, F739
Title 21 CFR 170-199
IEST-RP-CC005
NSF P155
ESD STM 11.11, 12
US Pharmacopoeia Nat.
Formulary XX and XXI



GENERAL PURPOSE	3-6
CLEANROOM	7-10
KNIT	11-13
ESD & CHEMICAL INFO	14-15

GENERAL PURPOSE
APPLICATIONS

Qualatex
MIRACLE GRIP™

BIOTEK
LATEX AMBI GLOVES

Qualatrilite
NITRILE GLOVES

QualaSheer
VINYL GLOVES

QualatriliteSENS!



Biotek®
Premium Latex Glove

- Lightly powdered or powder-free for wearer comfort.
- Textured for enhanced wet/dry grip.
- USDA compliant for food handling and processing.
- Non-slip beaded cuff for easy donning; resists rolldown.
- Safety — exceeds ASTM D-3578.

609BP (Low Powder)

Size: S–XL 9" Length, Ambi

609BPF (Powder-Free)

Size: XS–XXL 9" Length, Ambi



Qualatex® Miracle Grip
Polymer Coated Latex Glove

- Double polymer coated.
- 6 mil powder-free latex.
- Textured fingers and palm for enhanced wet/dry grip.
- Non-slip beaded cuff.
- Non-sterile.

MG09

Size: XS–XL 9" Length, Ambi



Qualatex® Miracle Grip HP
High Performance Latex Glove

- Tough 13 mil thickness & 12" length for added protection
- More Cut/Puncture Resistant than normal 6 mil gloves.
- Textured fingers & palm.
- Non-slip beaded cuff.
- Strong & flexible.
- Maximum comfort.
- Distinctive blue color.

MGHR

Size: S–XXL 12" Length, Ambi



Qualatex® Indy
Latex Glove

- 4 mil
- Unique fit and feel.
- Wide range chemical protection.
- Beaded cuff.
- Geared for industrial, automotive and food service.
- Economical.
- Natural color.

609BYF (Powder-Free)

Size: S–XL 9" Length, Ambi



QualaSheer® FG
Vinyl Glove

- 4 mil
- Food Grade.
- Certified under NSF protocol P 155, disposable food contact gloves, to meet FDA requirements for food handling.
- Naturally Anti-static, surface resistance 10¹⁰ ohms.
- Beaded cuff.
- Economical.
- Clear color.

VCYF09 (Powder-Free)

VCYP09 (Powdered)

Size: S–XL 9" Length, Ambi



Qualatril® Indy
Nitrile Glove

- 4 mil - 3X puncture resistance of vinyl or natural rubber latex gloves.
- Naturally Anti-static, surface resistance 10⁹ ohms.
- Tough industrial grade.
- Economical protection from chemicals and petroleum.
- USDA compliant for food handling and processing.
- Distinctive blue color.

BQY09 (Powder-Free)

Size: S–XXL 9" Length, Ambi



Qualatril® Blue 4 mil
Premium Nitrile Glove

- 3X puncture resistance of vinyl or natural rubber latex gloves.
- Naturally Anti-static, surface resistance 10⁹ ohms.
- Geogrip 360sm fully textured fingers and palms.
- Meets ASTM D6319.

4BQF09 (9" Blue, 4 mil, Powder-Free)

Size: XS–XXL, Ambi



Qualatril® Blue 5 mil
Premium Nitrile Glove

- 3X puncture resistance of vinyl or natural rubber latex gloves.
- Naturally Anti-static, surface resistance 10⁹ ohms.
- Geogrip 360sm fully textured fingers and palms.
- Meets ASTM D6319.

BQP09 (9" Blue, 5 mil, Low Powder)

BQF09 (9" Blue, 5 mil, Powder-Free)

BQF12 (12" Blue, 5 mil, Powder-Free)

Size: XS–XXL, Ambi



Qualatril® Blue 8 mil
Extra Thick Nitrile Glove

- Rugged 8 mil thickness.
- 3X puncture resistance of vinyl or natural rubber latex gloves.
- Naturally Anti-static, surface resistance 10⁹ ohms.
- Geogrip 360sm fully textured fingers and palms.
- Meets ASTM D6319.

8BQP09 (9" Blue, 8 mil, Low Powder)

Size: S–XL, Ambi

8BQF09 (9" Blue, 8 mil, Powder-Free)

Size: S–XXL, Ambi



Qualatril®SENS! 3 mil
Soft Nitrile Glove

- Latex-free, powder-free.
- Exceptional tactile sensitivity with the toughness, durability and chemical resistance of nitrile.
- Naturally Anti-static, surface resistance 10⁹ ohms.
- Uniquely conforms to the wearer's hand.
- Textured fingertips, for reliable, safe, secure wet/dry grip.

SQWF09 (White)

SQBF09 (Blue)

SQWB09 (White Bagged)

Size: S–XL 9" Length, Ambi



Qualatex® Latex Fingercots

- For general, personal and product protection.
- Sheer film for maximum dexterity.
- Economical.
- For industrial use only!

2C (Low Powder, Textured, Natural Color)

5J (Powder-Free, Natural Color)

7J (Powder-Free, Pink, Anti-static)

8J (Powder-Free, Black, Static Dissipative)

Size: S–XL

Qualatril® Nitrile Fingercot

- Excellent tactile sensitivity.
- Washed.
- Anti-static.
- Skin thin.
- Economical.
- For industrial use only!

9J (Powder-Free)


Size: S–XL



Blü Food Latex Fingercot

- 100% natural latex, USDA compliant blue coloring.
- For food & poultry handling.
- Meets US Government 21-CFR specifications.
- Skin thin.

BF (Powder-Free)
Size: S–XL



CLEANROOM APPLICATIONS

QRP adheres to all requirements of IEST-RP-CC005.2, Recommended Practice for Gloves and Fingercots Used in Cleanrooms and Other Controlled Environments.



polar process
The Leading Edge in Cleanroom

We employ today's most advanced manufacturing practices. Our P3 Polar Process is today's most advanced halogenation and processing system, ensuring uniformity across our gloves and fingercots, with ultra-low extractables, non-volatile residues and particulates. Using only the finest materials paired with proprietary formulations, processing and packaging, QRP delivers the highest and most consistent levels of quality, reliability and performance.

Qualatril®XC

Qualatex®XC

Qualatex® HiPro XC.

QualaSheer®XC
VINYL GLOVES

PolyTuff®
PERFORMANCE GLOVES

Qualatherm
THERMAL PROTECTION



Qualatex® HiPro XC
Class 100 Latex Glove

- Premium natural rubber latex gloves for ISO 5 (Class 100) applications.
- Lowest extractibles and particulates.
- Free from plasticizers, silicone and powders.
- Meets or exceeds all applicable requirements of IEST-RP-CC005.2.

612HC

Size: S-XXL 12" Length, Ambi



Qualatrilite® XC White
Class 100 Nitrile Glove

- 100% nitrile (no latex) for ISO 5 (Class 100) applications.
- Naturally anti-static – 10^9 ohms.
- Manufactured without plasticizers, silicone or powders.
- Consistently low particulates and extractible ion levels.
- Meets or exceeds all applicable requirements of IEST-RP-CC005.2.

Q095

Size: S-XL 9" Length, Ambi

Q125

Size: XS-XXL 12" Length, Ambi



QualaSheer® XC
Class 100 Vinyl Glove

- 100% PVC co-polymer (no latex) for ISO 5 (Class 100) applications.
- Naturally anti-static – 10^{10} ohms.
- Microtextured.
- Meets or exceeds all applicable requirements of IEST-RP-CC005.2.

VHC12

Size: S-XL 12" Length, Ambi



PolyTuff® Acid & Alkali
CSM Glove

- Packaged for ISO 5 (Class 100) applications.
- Engineered for corrosive alkalis and ultra-strong acids using CSM, sulfur-free.
- Flexible for long wearing comfort.
- Handling for wet or dry environments.

41G

Size: Universal Large Only 14" Length
Hand Specific



PolyTuff® Superior Solvent
Silicon Elastomer Glove

- Packaged for ISO 5 (Class 100) applications.
- For industrial use with silicon-based adhesives and harsh solvents such as DMF, THF, cyclohexanone and ketones.
- Silicon elastomer formulation withstands flaking, puncture and abrasion.

90G

Size: Universal Large Only 12" Length
Hand Specific



Qualatex® XC
Natural Latex Fingercot

- Packaged for ISO 5 (Class 100) applications. Compliant with ASTM and IEST-RP-CC 005.3 standards.
- Eliminates contamination risks from silicone oils, skin salts, particulates and plasticizers.
- Packaged in gas-impermeable film flushed with semiconductor grade N2.
- Unique, Stand-Up pouch – easy product identification.

5C (Powder-Free)

Size: S-XXL



PolyTuff® Solvent Series
Polyurethane Glove

- Packaged for ISO 5 (Class 100) applications.
- Protection from chlorinated solvents (MeCL and TCE), acetone, xylene, freons and IPA.
- Tough, chemical & solvent resistant polyurethane, sulfur-free.
- Ergonomic Comfort Curve™ hand specific design.

20G (8 mil)

Size: S-XL 12" Length



PolyTuff® Anti-Static
Polyurethane Glove

- Packaged for ISO 5 (Class 100) applications.
- Anti-static 10^9 ohms per square surface unit.
- Resists common solvents such as MeCl, TCE and IPA.
- ESD safe for Class II devices.
- Ergonomic Comfort Curve™ hand specific design.

25G (4 mil)

Size: S-L 12" Length



PolyTuff® Static Dissipative
Polyurethane Glove

- Packaged for ISO 5 (Class 100) applications.
- Static dissipative 10^6 ohms per square surface unit.
- ESD-safe for Class I and II devices.
- Tough solvent process polyurethane, sulfur-free – no carbon shedding.
- Ergonomic Comfort Curve™ hand specific design.

27G (4 mil)

Size: S-L 12" Length

28G (8 mil)

Size: S-L 12" Length



Qualatex® XC Anti-Static
Pink Latex Fingercot

- Packaged for ISO 5 (Class 100) applications. Compliant with ASTM and IEST-RP-CC 005.3 standards.
- Average surface resistance of 5×10^{10} ohms per square unit.
- For use with Class II static sensitive devices (thresholds above 1000V).
- Packaged in gas-impermeable film flushed with semiconductor grade N2.
- Unique, Stand-Up pouch – easy product identification.

7C (Powder-Free)

Size: S-XXL




Qualatex® XC Static Dissipative
Black Latex Fingercot

- Packaged for ISO 5 (Class 100) applications. Compliant with ASTM and IEST-RP-CC 005.3 standards.
- Average surface resistance of 10^7 ohms per square surface unit.
- For use with Class I and Class II static sensitive devices.
- Packaged in gas-impermeable film flushed with semiconductor grade N2.
- Unique, Stand-Up pouch – easy product identification.

8C (Powder-Free)

Size: S-XXL



Qualatrilite® XC Anti-Static
White Nitrile Fingercot

- Packaged for ISO 5 (Class 100) applications.
- Average surface resistance of 5×10^9 ohms per square unit.
- For use with Class II static sensitive devices (thresholds above 1000V).
- Packaged in gas-impermeable film flushed with semiconductor grade N2.
- Unique, Stand-Up pouch – easy product identification.

9C (Powder-Free)

Size: S-XXL



Qualatherm® 1400
Dry Thermal Protection

- Packaged for ISO 5 (Class 100).
- Dry contact temperatures from 210°F to 1400°F (-134°C to 760°C) with no charring, ash or residue.
- ESD protection static dissipative 10⁹.
- No PCB, asbestos or fiberglass.

50G – 14" (Forearm Protection)
Size: M, L, XL

55G – 18" (Elbow Protection)
Size: Universal Large Only

57G – 27" (Shoulder Protection)
Size: Universal Large Only



Qualatherm® 1000
Dry Thermal Protection

- Packaged for ISO 5 (Class 100).
- Dry contact temperatures from 210°F to 1000°F (-134°C to 537°C) with no charring, ash or residue.
- No PCB, asbestos or fiberglass.

59G (Forearm Protection)
Size: L, XL 14" Length



Qualatherm® 450
Wet / Dry Thermal Protection

- Packaged for ISO 5 (Class 100).
- Wet or dry contact temperatures from 78°F to 450°F (-61.4°C to 232°C).
- PolyTuff silicone elastomer is sulfur-free. Excellent resistance to chemicals, solder and fluxes.

70G – 12" (Wrist Protection)
Size: Hand Specific – M, L, XL

73G – 10" (Mitt Style Hand Protection)
Size: Ambidextrous – One size fits all

75G – 23" (Elbow Protection)
Size: Hand Specific – One size fits all



Dry Box Gloves
Full Length Gloves

- Standard 8" plus 6" & 10" ports; 32" length.
- Thicknesses: 15 to 30 mils.
- Hand-specific or ambidextrous.
- Beaded cuffs for added strength.
- Hand sizes: 7, 8, 9, 10.

DBG – NR (Natural Rubber)
DBG – BT (Butyl) (also ESD)
DBG – NE (Chloroprene) (also ESD)
DBG – HY (CSM)
DBG – PHY (PU-CSM)
DBG – PU (Polyurethane)



Isolators
Gloves/Sleeves

- 13" glove (15 mil to 30 mil thickness) + 24" sleeve.
- Economical alternative to one piece dry box gloves – usually only glove needs to be replaced.
- Glove & sleeve can be different materials.
- Port sizes: 6", 8" 10"; gloves ambi, sizes 5-10.

GLOVES	SLEEVES
IG – BT	SL – BT (Butyl) (also ESD)
IG – NE	SL – NE (Chloroprene) (also ESD)
IG – HY	SL – HY (CSM)
IG – PHY	SL – PHY (PU-CSM)
IG – PU	SL – PU (Polyurethane)



KNIT
APPLICATIONS

Qualakote
LIGHTWEIGHT NYLON GLOVES

Qualaknit
ANTI-STATIC ASSEMBLY/INSPECTION

little RED GRIPPER



Qualakote® NY
Nylon / PU Palm Dipped

- Comfortable seamless nylon knit.
- Micro-foamed polyurethane palm dipped.
- Breathable, knitted seamless comfort.
- Washable for economy of reuse.

PDNY (White)
PDGNY (Gray)
PPDBNY (Black)
Size: S-XXL



Qualakote® NY
Nylon / Nitrile Palm Dipped

- Assembly-Inspection glove.
- Comfortable nylon knit.
- Micro-foamed nitrile palm dipped.
- Breathable, seamless comfort.
- Washable for economy of reuse.

NPDNY (White)
Size: S-XL

PDBNY (Black)
Size: S-XXL



Little Red Gripper
Nylon / Grippy Nitrile Palm

- Nitrile foam coated palm & fingers.
- Seamless knit shell for maximum comfort.
- Great tactile sensitivity
- Great replacement for leather gloves.
- Machine washable for repeated use.
- Non-marking & non-linting.

GNRN
Size: S-XL



Qualakote® C/R
Cut Resistant-All Purpose

- UHMWPE cut resistant yarn + black nylon knit. (GPSPD is branded yarn; GPSPN is equivalent non-branded yarn)
- Foam PU palm dipped for excellent grip.
- ANSI/SEA level 2, EN level 3.
- Highly flexible for dexterity, ergonomic fit.
- Easy laundering, for multiple reuses.

GPSPD (branded UHMWPE)
GPSPN (non-branded UHMWPE)
Size: XS-XXXL



Qualakote® ESD
Nylon / Carbon / PU Fingers

- Micro-foamed polyurethane finger tip coating for excellent grip.
- Nylon + conductive carbon/nylon yarn.
- Spandex cuff – no latex.
- Maximum uncoated area, seamless knit, for breathability, comfort.
- Human Body Model ANSI/ESD SP15.1 CAFÉ resistance: 10⁷ uncoated area; 10⁸⁻⁹ coated area.
- Machine washable for economy of repeated use.

TDESDNY
Size: XS-XXL



Qualakote® NY ESD
Nylon / Carbon / PU Palm Dipped

- Micro-foamed polyurethane palm coating for excellent grip.
- Nylon + conductive carbon/nylon yarn.
- Uncoated back, seamless knit, for breathability, comfort.
- Human Body Model ANSI/ESD SP15.1 CAFÉ resistance: 10⁷ uncoated area; 10⁸⁻⁹ coated area.
- Machine washable for economy of repeated use.

PDESDNY
Size: S-XXL



Qualakote® ESD
Wave Solder Glove

- Extra thick for thermal protection.
- Nylon + conductive carbon/nylon yarn.
- Nitrile foamed palm dip for extra toughness.
- Seamless knit, open back.
- Human Body Model ANSI/ESD SP15.1 CAFÉ resistance: 10⁷ uncoated area; 10⁸⁻⁹ coated area.
- Machine washable for economy of repeated use.

PDWS (Low Heat)
Size: XS-XXL
HWS (Medium Heat)
Size: S-XXL



Qualakote® ESD
Nylon / PU Palm Dipped

- Micro-foamed polyurethane palm coating for excellent grip.
- White nylon yarn for economy.
- Topical coating of glove for anti-static ESD protection.
- ANSI/ESD STM 11.11 Surface Resistance 10⁷⁻⁹.

PDESDEC
Size: XS-XXL



Qualaknit® ESD
Nylon / Carbon Uncoated

- Nylon + conductive carbon/nylon yarn.
- Micro-knit fingertips for maximum dexterity.
- Uncoated glove for maximum breathability, lowest resistance.
- Static dissipative HBM ANSI/ESD SP 15.1 CAFÉ resistance 10⁶⁻⁷.
- Seamless comfort.

KAS
Size: S-XXL

QRP's ESD PROTECTION PRODUCTS

STATIC DISSIPATIVE (10⁵ - 10⁷) ANTI-STATIC (10⁸ - 10¹²)

CLEANROOM GLOVES

STYLE	DESCRIPTION	STATIC DISSIPATIVE	ANTI-STATIC
Q095	9" White Nitrile		~10 ⁹
Q125	12" White Nitrile		~10 ⁹
VHC12	12" Clear Vinyl		~10 ¹⁰
25G	12" Clear Polyurethane		~10 ⁹
27G, 28G	12" Black Polyurethane	~10 ⁶	
DBG-NEESD	Dry Box Glove Anti-static Neoprene		~10 ⁸
DBG-BTESD	Dry Box Glove Anti-static Butyl		~10 ⁸

CLEANROOM FINGERCOTS

STYLE	DESCRIPTION	STATIC DISSIPATIVE	ANTI-STATIC
7C	Pink Anti-static Latex		~10 ¹⁰
8C	Black Static Dissipative Latex	~10 ⁷	
9C	White Anti-static Nitrile		~10 ⁹

KNITTED GLOVES

STYLE	DESCRIPTION	STATIC DISSIPATIVE	ANTI-STATIC
KAS	Nylon Carbon Knitted Static Dissipative	~10 ⁷	
PDES DNY	Nylon Carbon Knit/PU Palm Dipped		~10 ⁸
TDES DNY	Nylon Carbon Knit/PU Finger Tip Dipped		~10 ⁸
PDES DEC	White Nylon/PU Palm Dipped ESD Coated		~10 ⁸
PDWS	Medium Weight Nylon Carbon Knit/Nitrile Palm Dip		~10 ⁸
HWS	Heavy Weight Nylon Carbon Knit/Nitrile Palm Dip		~10 ⁸

GENERAL PURPOSE GLOVES

STYLE	DESCRIPTION	STATIC DISSIPATIVE	ANTI-STATIC
4BQF09	9" 4 mil Powder Free Blue Nitrile Exam Glove		~10 ⁹
BQP09	9" 5 mil Powdered Blue Nitrile Exam Glove		~10 ⁹
BQF09	9" 5 mil Powder Free Blue Nitrile Exam Glove		~10 ⁹
BQF12	12" 5 mil Powder Free Blue Nitrile Exam Glove		~10 ⁹
8BQP09	9" 8 mil Powdered Free Blue Nitrile Exam Glove		~10 ⁹
8BQF09	9" 8 mil Powder Free Blue Nitrile Exam Glove		~10 ⁹
BQY09	9" 5 mil Powder Free Industrial Blue Nitrile		~10 ⁹
SQWF09	9" 3 mil Powder Free White Nitrile Exam Glove		~10 ⁹
SQBF09	9" 3 mil Powder Free Blue Nitrile Exam Glove		~10 ⁹
VCYF09	9" 4 mil Powder Free Industrial Vinyl		~10 ¹⁰

GENERAL PURPOSE FINGERCOTS

STYLE	DESCRIPTION	STATIC DISSIPATIVE	ANTI-STATIC
7J	Pink Anti-static Latex		~10 ¹⁰
8J	Black Static Dissipative Latex	~10 ⁷	
9J	White Anti-static Nitrile		~10 ⁹

QRP CHEMICAL RESISTANCE CHART

CHEMICAL NAME	Material QRP BRAND	Latex QUALATEX, BIOTEK	Nitrile QUALATRILE	Vinyl QRP VINYL	Polyurethane POLYTUFF
Acetaldehyde		●	●	●	●
Acetic Acid		●	●	●	●
Acetic Anhydride		●	●	●	●
Acetone		●	●	●	●
Acetonitrile		●	●	●	●
Acrylic Acid		●	●	●	●
Ammonium Acetate		●	●	●	●
Ammonium Carbonate		●	●	●	●
Ammonium Fluoride, 30-70%		●	●	●	●
Ammonium Hydroxide 30-70%		●	●	●	●
Ammonium Hydroxide <30%		●	●	●	●
Amyl Alcohol		●	●	●	●
Aniline		●	●	●	●
Aqua Regia		●	●	●	●
Benzaldehyde		●	●	●	●
Benzene		●	●	●	●
Boric Acid		●	●	●	●
Bromopropionic Acid		●	●	●	●
Butyl Acrylate		●	●	●	●
Butyl Cellulose		●	●	●	●
Calcium Hydroxide		●	●	●	●
Carbon Disulfide		●	●	●	●
Carbon Tetrachloride		●	●	●	●
Chlorobenzene		●	●	●	●
Chlorobromomethane		●	●	●	●
Chloroform		●	●	●	●
Chloronaphthalenes		●	●	●	●
Chromic Acid		●	●	●	●
Cisplatin		●	●	●	●
Citric Acid, 30-70%		●	●	●	●
Cyclohexane		●	●	●	●
Cyclohexanol		●	●	●	●
Cyclohexanone		●	●	●	●
Cyclohexylamine		●	●	●	●
Di-N-Amylamine		●	●	●	●
Di-N-Butylamine		●	●	●	●
Di-N-Butyl Phthalate		●	●	●	●
Di-N-Octyl Phthalate		●	●	●	●

CHEMICAL NAME	Material QRP BRAND	Latex QUALATEX, BIOTEK	Nitrile QUALATRILE	Vinyl QRP VINYL	Polyurethane POLYTUFF
Diacetone Alcohol		●	●	●	●
Diallylamine		●	●	●	●
Dichloroacetyl Chloride		●	●	●	●
Diesel Fuel		●	●	●	●
Diethanolamine		●	●	●	●
Diethylamine		●	●	●	●
Diethylene Glycol		●	●	●	●
Diethylenetriamine		●	●	●	●
Diisobutyl Ketone		●	●	●	●
Diisobutylamine		●	●	●	●
Dimethyl Ether		●	●	●	●
Dimethyl Sulfoxide (DMSO)		●	●	●	●
Dimethylacetamide		●	●	●	●
Dimethylformamide (DMF)		●	●	●	●
1,3-Dioxne		●	●	●	●
1,4-Dioxne		●	●	●	●
Epichlorohydrin		●	●	●	●
Ethanol		●	●	●	●
Ethyl Acetate		●	●	●	●
Ethyl Ether		●	●	●	●
Ethylene Glycol Dimethyl Ether		●	●	●	●
Ethylene Dichloride		●	●	●	●
Ethylene Glycol		●	●	●	●
Formaldehyde 30-70%		●	●	●	●
Formic Acid		●	●	●	●
Freon 113 or TF		●	●	●	●
Freon TMC		●	●	●	●
Furfural		●	●	●	●
Gasoline 40-50% Aromatics		●	●	●	●
Gasoline, Unleaded		●	●	●	●
Glutaraldehyde, <5%		●	●	●	●
Glycerol		●	●	●	●
Heptanes		●	●	●	●
Hexamethyldisiloxane		●	●	●	●
Hexane		●	●	●	●
Hydrazine		●	●	●	●
Hydrochloric Acid, <30%		●	●	●	●
Hydrochloric Acid, 30-70%		●	●	●	●

CHEMICAL NAME	Material QRP BRAND	Latex QUALATEX, BIOTEK	Nitrile QUALATRILE	Vinyl QRP VINYL	Polyurethane POLYTUFF
Hydrofluoric Acid, <50%		●	●	●	●
Isobutyl Alcohol		●	●	●	●
Isooctane		●	●	●	●
Isopropyl Alcohol		●	●	●	●
Isopropylamine		●	●	●	●
Jet Fuel <30% Aromatics 73-248C		●	●	●	●
Kerosene		●	●	●	●
Lactic Acid		●	●	●	●
Lauric Acid		●	●	●	●
Malathion, 30-70%		●	●	●	●
Maleic Acid		●	●	●	●
Methanol		●	●	●	●
Methyl Acetate		●	●	●	●
Methyl Ethyl Ketone		●	●	●	●
Methyl Isobutyl Ketone		●	●	●	●
Methyl Methacrylate		●	●	●	●
Methylene Chloride		●	●	●	●
N-Amyl Acetate		●	●	●	●
N-Butyl Acetate		●	●	●	●
N-Butyl Alcohol		●	●	●	●
N-Methyl-2-Pyrrolidone		●	●	●	●
N-Propyl Alcohol		●	●	●	●
Naphtha, 15-20% Aromatics		●	●	●	●
Naphtha, <3% Aromatics		●	●	●	●
Nitric Acid, <30%		●	●	●	●
Nitric Acid, 30-70%		●	●	●	●
Nitrobenzene		●	●	●	●
Nitroethane		●	●	●	●
I-Nitropropane		●	●	●	●
2-Nitropropane		●	●	●	●
Octane		●	●	●	●
Octyl Alcohol		●	●	●	●
Oleic Acid		●	●	●	●
Oxalic Acid		●	●	●	●
Palmitic Acid		●	●	●	●
PCB (Polychlorinated Biphenyls)		●	●	●	●
Pentachlorophenol		●	●	●	●
Pentane		●	●	●	●

● Recommended

● Good to Fair

● Not Recommended

COLOR CODE:

QRP has compiled the information contained herein from what we believe are authoritative sources and believe are accurate and factual as of the date printed. It is offered solely as a convenience to our customers and is intended only as a guide concerning splash protection of the products mentioned. Since the users specific use applications and conditions of use are beyond QRP's control, QRP makes no warranty or representation regarding the results which may be obtained by the user. User assumes all risks and is solely responsible for the suitability and fitness of the product selected for a particular application. User should consider the benefits of double gloving in uncertain situations.

1.800.832.3882
QRPgloves.com



P.O. BOX 27466

TUCSON, AZ 85726-7466

TEL: 800-832-3882

FAX: 520-790-3530

www.QRPGloves.com

QRP has compiled the information contained herein from what we believe are authoritative sources and believe are accurate and factual as of the date printed. It is offered solely as a convenience to our customers and is intended only as a guide concerning the products mentioned. Since the users specific use applications and conditions of use are beyond QRP's control, QRP makes no warranty or representation regarding the results which may be obtained by the user. User assumes all risks and is solely responsible for the suitability and fitness of the product selected for a particular application. User should consider the benefits of double gloving in uncertain situations. In the interests of product improvement, specifications are subject to change without notice.