


GENERAL PURPOSE SNAP ACTION



Retail Part No.	Bulk Part No.	Fig. No.	Amps **VAC	Amps 125 VDC	Amps 250 VDC	HP 125 VAC	HP 250 VAC	PT Max. (In)	OT Min. (In)	DT Max. (In)	OF Max. Oz. (grams)	Actuator	Actuator Length (In)	Terminal Type	Spec Drawing Page No.
35-461	35-461-BU	1	15			3/4	1-1/2	0.050	0.050	0.010	20 (567)	PI		QC .250"	297-A
35-462	35-462-BU	2	15			3/4	1-1/2	0.050	0.187	0.010	20 (567)	PI w/OT		QC .250"	297-B
35-463	35-463-BU	3	15			3/4	1-1/2	0.281	0.062	0.094	20 (567)	Ro	1.50	QC .250"	297-C
35-464	35-464-BU	4	15			3/4	1-1/2	0.312	0.187	0.062	20 (567)	Lever	2.50	QC .250"	297-D
35-830	35-830-BU	5	15			3/4	1-1/2	0.050	0.050	0.010	20 (567)	Red Pb		QC .250"	297-E
35-831	35-831-BU	5	15			3/4	1-1/2	0.050	0.050	0.010	20 (567)	Black Pb		QC .250"	297-E
35-990	35-990-BU	*6	15			3/4	1-1/2	0.050	0.050	0.010	30 (850)	PI		QC .250"	297-F
35-992	35-992-BU	*7	15			3/4	1-1/2	0.312	0.187	0.062	30 (850)	Lever	2.50	QC .250"	297-F
35-3900	35-3900-BU	8	15			1/8	1/4	0.016	0.005	0.002	12.3 (350)	PP		Sc	297-G
35-3901	35-3901-BU	8	15	1/2	1/4			0.016	0.005	0.002	12.3 (350)	PP		Sc	297-G
35-3907	35-3907-BU	9	15					0.158	0.063	0.002	5.3 (151)	LRO	1.783	Sc	297-O
35-3910	35-3910-BU	10	20	1/2	1/4	1	2	0.028	0.140	0.008	22.9 (650)	RP		Sc	297-I
35-3911	35-3911-BU	10	15					0.016	0.140	0.002	12.3 (349)	RP		Sc	297-I
35-828	35-828-BU	11	20	1/2	1/4	1	2	0.156	0.062	0.050	5-13 (142-370)	LL	1.95	Sc	297-H
35-829	35-829-BU	11	15	1/2	1/4	1	2	0.156	0.062	0.050	5-13 (142-370)	LL	1.97	Sd	297-H
35-890	35-890-BU	12	20	1/2	1/4			0.380	0.190	0.156	3.5-26 (100-740)	Lever	2.50	Sc	297-J
35-892	35-892-BU	13	20	1/2	1/4	1	2	0.020	0.055	0.002	12.3 (350)	SP		Sd/Sc	297-K&L
35-894	35-894-BU	14	20	1/2	1/4	1	2	0.020	0.005	0.002	12.3 (350)	PP		Sd/Sc	297-L
35-896	35-896-BU	15	20	1/2	1/4	1	2	0.020	0.063	0.002	12.3 (350)	PI w/OT		Sd/Sc	297-M
35-980	35-980-BU	14	20	1/2	1/4			0.030	0.005	0.005	26 (740)	PP		Sd/Sc	297-L
35-982	35-982-BU	15	20	1/2	1/4			0.030	0.220	0.005	26 (740)	PI		Sd/Sc	297-M
35-984	35-984-BU	12	20	1/2	1/4			0.380	0.190	0.047	2.5-9 (60-255)	Lever	2.50	Sd/Sc	297-J
35-987	35-987-BU	16	20	1/2	1/4	1/2	1	0.468	0.062	0.085	3.5 (100)	Ro	1.91	Sc	297-N
35-3903	35-3903-BU	13	20	1/2	1/4	3/4	1 1/2	0.020	0.055	0.002	12.3 (350)	SP		Sc	297-K
35-3904	35-3904-BU	17	20	1/2	1/4	1/2	1	0.158	0.062	0.050	5.3 (150)	LL	1.95	Sc	297-H
35-3906	35-3906-BU	16	20	1/2	1/4	1	2	0.156	0.062	0.050	5-13 (142-370)	LRO	1.78	Sc	297-O

Notes: All of the above have momentary action

*DPDT

**125/250VAC

All have SPDT, but 35-990 & 35-992

DT=Differential Travel

HP=Horse Power

HRo=Hinged Roller

LRO=Leaf Rollers

LL=Leaf Lever

OF=Operating Force

OT=Over Travel

Pb=Pushbuttons

PI=Plunger

PT=Pre-Travel

QC=Quick Connect

RP=Roller Plunger

Sc=Screw

Sd=Solder

ShRo=Short Roller






SP=Stub Plunger

PP=Pin Plunger

Ro=Roller

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

Switches



GENERAL PURPOSE SNAP ACTION (Cont.)



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5

Retail Part No.	Bulk Part No.	Fig. No.	Amps **VAC	Amps 125 VDC	Amps 250 VDC	HP 125 VAC	HP 250 VAC	PT Max. (In)	OT Min. (In)	DT Max. (In)	OF Max. Oz. (grams)	Actuator	Actuator Length (In)	Terminal Type	Spec Drawing Page No.
35-3908	35-3908-BU	1	20	1/2	1/4	3/4	1-1/2	0.025	0.22	0.002	20 (567)	High OT Pl		Sc	299-A
35-3914	35-3914-BU	2	20	1/2	1/4	3/4	1-1/2	0.020	0.062	0.002	13 (368)	Small OT Pl		Sc	299-A
35-3916	35-3916-BU	3	20	1/2	1/4	3/4	1-1/2	0.380	0.190	0.078	2.5-18 (71-510)	Lever	2.34	Sc	299-B
35-3920	35-3920-BU	4	20	1/2	1/4	3/4	1 1/2	0.080	0.090	0.008	10-13 (284-370)	RARO	0.65	Sd/Sc	299-C
35-3921	35-3921-BU	4	20	1/2	1/4	N/R	N/R	0.080	0.090	0.008	10-13 (284-370)	RARO	0.65	Sd/Sc	299-C
35-3922	35-3922-BU	5	20	1/2	1/4	1/2	1		0.094	0.020	18 (510)	HRo	0.91	Sc	299-D

Notes: All of the above have momentary action
 **125/250/480VAC
 All have SPDT

DT=Differential Travel
 HP=Horse Power
 HRo=Hinged Roller
 LRo=Leaf Rollers
 LL=Leaf Lever

OF=Operating Force
 OT=Over Travel
 Pb=Pushbuttons
 Pl.=Plunger

PT=Pre-Travel
 QC=Quick Connect
 RP=Roller Plunger
 Sc=Screw
 RARO=Reverse Action Roller

Sd=Solder
 SP=Stub Plunger
 PP=Pin Plunger
 Ro=Roller

KEYLOCK SWITCHES



Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10



Fig. 11

Retail Part No.	Bulk Part No.	Fig. No.	Poles/Throws	Amps 125 VAC	Action	Index	Lock Type	Key Removal	Actuator	Terminal Type	Mounting Hole (In)	Hardware	Spec Drawing Page No.
35-196	35-196-BU	6	SPST	2.5*	On/Off	90°	5 disk tumbler	2 Pos.	Metal Key††	Sc	0.875	***	299-E
35-3190	35-3190-BU	7	SPDT	4	On/On	90°	4 tumbler w/detent	2 Pos.	Metal Key†	Sd Lug	0.760 x 0.640	N, 2Keys	299-G
35-3192	35-3192-BU	7	DPDT	4	On/On	90°	4 tumbler w/detent	2 Pos.	Metal Key†	Sd Lug	0.760	N, 2Keys	299-G
35-3193	35-3193-BU	8	SPDT	4	On/On	90°	6 tumbler w/tube lock	2 Pos.	Metal Barrel Key†	6" WL	0.760 x 0.640	N, 2Keys	299-H
35-3194	35-3194-BU	8	SPDT	4	On/On	90°	6 tumbler w/tube lock	1 Pos.	Metal Barrel Key†	6" WL	0.760 x 0.640	N, 2Keys	299-H
35-3195	35-3195-BU	9	SPDT	4	On(On)	45°	4 tumbler	1 Pos.	Metal Key†	6" WL	0.760 x 0.640	N, 2Keys	299-F
35-3197	35-3197-BU	10	SP3T	4	**	45°	4 tumbler	1 Pos.	Metal Key†	Sd Lug	0.760 x 0.640	N, 2Keys	299-G
35-3482		11	SPDT	****	Off/On(On)	90°	5 tumbler	1 Pos.	Metal Key†	Sc	0.844	N, 2Keys	299-I

Notes: *Rated @ 2.5Amps 120VAC (480V.A.)

**SP-3 pos. On1 - Off - On2

***Nut, 2 Screws, Ring, and 2 Keys

35-196 is rated @ 2.5A @120VAC (480V.A.),

2.1amps @46VDC (96V.A.), all of the rest are rated

@ 2A @250VAC/4A @ 28VDC, except 35-3482

****35-3482 is rated @ 15A 6-12VDC-2 Position SPDT

Keys(2) included in Hardware

N=Nut

Pos.=Positions

Sc=Screw

Sd=Solder

WL=Wire Leads

†=All keyed alike per figure

††=For 35-196 switches all keyed alike order:

Key#530=35-530-BU

Key#531=35-531-BU

Key#540=35-540-BU

Key#541=35-541-BU

Key#550=35-550-BU

Key#553=35-553-BU

#1110801 Keys for 35-3193 & 35-3194

#115140126 Keys for 35-3190, 35-3192, 35-3195 & 35-3197

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

35-3914

Side View Dimensions:
 Total Width: 92 (23.4)
 Mounting Hole Diameter: 155 dia (3.94)
 Base Hole Diameter: 250 dia (6.35)
 Mounting Hole Spacing: 110 ± .050 (28.19 ± 0.51) over pos

Top View Dimensions:
 Total Width: 92 (23.4)
 Mounting Hole Spacing: 110 (28.19)

35-3908




Side View Dimensions:
 Total Width: 92 (23.4)
 Mounting Hole Diameter: 155 dia (3.94)
 Base Hole Diameter: 250 dia (6.35)
 Mounting Hole Spacing: 110 ± .050 (28.19 ± 0.51) over pos

Top View Dimensions:
 Total Width: 92 (23.4)
 Mounting Hole Spacing: 110 (28.19)

35-3907

Side View Dimensions:
 Total Width: 92 (23.4)
 Mounting Hole Diameter: 155 dia (3.94)
 Base Hole Diameter: 250 dia (6.35)
 Mounting Hole Spacing: 110 ± .050 (28.19 ± 0.51) over pos

Top View Dimensions:
 Total Width: 92 (23.4)
 Mounting Hole Spacing: 110 (28.19)



Technical drawings of the Rod Head Cam Lock assembly. The top drawing shows a side view of the lock with dimensions: 1.68 (42.8) for the total length, .75 (19) for the distance from the end to the first thread, .906 (23) for the diameter of the cylinder ring, .03 (.76) for the thickness of the cylinder ring, and 3/4-24 THD for the thread. The bottom drawing shows a side view of the rod head cam lock with dimensions: .875 (22.2) for the diameter of the rod head, .162 (4.11) for the thickness of the rod head, and A and B for the distances from the end to the center of the rod head and the center of the rod, respectively.

