


1SV231

CATV TUNING

- High Capacitance Ratio : $C_{2V} / C_{25V} = 15$ (Typ.)
- Excellent C-V Characteristics, and Small Tracking Error.
- Useful for Small Size Tuner.

MAXIMUM RATINGS ($T_a = 25^\circ\text{C}$)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Reverse Voltage	V_R	30	V
Peak Reverse Voltage	V_{RM}	35 ($R_L = 10k\Omega$)	V
Junction Temperature	T_j	125	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	$-55 \sim 125$	$^\circ\text{C}$



Weight : 0.004g

ELECTRICAL CHARACTERISTICS ($T_a = 25^\circ\text{C}$)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Reverse Voltage	V_R	$I_R = 1\mu\text{A}$	30	—	—	V
Reverse Current	I_R	$V_R = 28\text{V}$	—	—	10	nA
Capacitance	C_{2V}	$V_R = 2\text{V}, f = 1\text{MHz}$	41.0	45.0	49.5	pF
Capacitance	C_{25V}	$V_R = 25\text{V}, f = 1\text{MHz}$	2.7	3.0	3.4	pF
Capacitance Ratio	C_{2V} / C_{25V}	—	14	15	—	—
Series Resistance	r_s	$V_R = 5\text{V}, f = 470\text{MHz}$	—	1.05	1.25	Ω

(Note 1) : Available in matched group for capacitance to 2.5%.

MARKING






$$\frac{C(\text{Max.}) - C(\text{Min.})}{C(\text{Min.})} \leq 0.025$$

($V_R = 2 \sim 25\text{V}$)



000707EAA2

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.



NOTE : $\delta C (\%) = \frac{C(T_a) - C(25)}{C(25)} \times 100$


SPICE PARAMETER

SPICE MODEL : BERKLEY SPICE.2G.6 DIODE MODEL
 DATA FORMAT : MODEL FORMAT
 SPICE SYMBOL : I_S (A), R_S (Ω), N (-), $CJ0$ (F), V_J (V), M (-), B_V (V), I_{BV} (A)
 FREQUENCY RANGE : $f = 0.1 \sim 3$ GHz
 REVERSE VOLTAGE RANGE : $V_R = 2 \sim 25$ V
 AMBIENT TEMPERATURE : $T_a = 27^\circ\text{C}$

PARAMETER

$I_S = 1.195\text{E} - 14$
 $N = 1.072$
 $B_V = 30$
 $I_{BV} = 1.00\text{E} - 04$
 $R_S = 1.05$
 $CJ0 = 9.127\text{E} - 11$
 $V_J = 5.096$
 $M = 2.031$

 $L_s = 1.00\text{E} - 09$



- (Note 1) : These parameters from I_S to M mean die characteristic.
 Actually device has lead inductance so L_s is necessary for simulation.
 And please use default value except above parameters.
- (Note 2) : R_S shows the value at the condition of $V_R = 5$ V and $f = 470$ MHz.
 If another value is needed, please refer to $R_S - V_R$ curve in this data sheets.