

TOSHIBA PHOTOCOUPLER GaAs IRED & PHOTO-TRANSISTOR

4N29(Short), 4N29A(Short), 4N30(Short), 4N31(Short) 4N32(Short), 4N32A(Short), 4N33(Short)

AC LINE / DIGITAL LOGIC ISOLATOR.

DIGITAL LOGIC/DIGITAL LOGIC ISOLATOR.

TELEPHONE LINE RECEIVER.


TWISTED PAIR LINE RECEIVER.

RELAY CONTACT MONITOR.

The TOSHIBA 4N29 (Short) through 4N33 (Short) consists arsenide infrared emitting diode coupled with a silicon photo darlington in a dual in-line package.


- Switching Time : $100\mu s$ (Max.)
- DC Current Transfer Ratio : 500%
- Isolation Resistance : $10^{11}\Omega$ (Typ.)
- Isolation Voltage : $2500V_{rms}$ (Min.)
- UL Recognized : UL1577, File No. E67349

Unit in mm



Weight : 0.4g

PIN CONFIGURATIONS (Top view)



- 1 : ANODE
- 2 : CATHODE
- 3 : N.C.
- 4 : EMITTER
- 5 : COLLECTOR
- 6 : BASE

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
LED	Forward Current (Continuous)	I_F	80	mA
	Forward Current Derating	$\Delta I_F / ^\circ\text{C}$	1.07(*)	mA / °C
	Peak Forward Current (Note 1)	I_{PF}	3	A
	Power Dissipation	P_D	150	mW
	Power Dissipation Derating	$\Delta P_D / ^\circ\text{C}$	2.0(*)	mW / °C
	Reverse Voltage	V_R	3	V
DETECTOR	Collector-Emitter Voltage	BV_{CEO}	30	V
	Collector-Base Voltage	BV_{CBO}	30	V
	Emitter-Collector Voltage	BV_{ECO}	5	V
	Collector Current (Continuous)	I_C	100	mA
	Power Dissipation	P_C	150	mW
	Power Dissipation Derating	$\Delta P_C / ^\circ\text{C}$	2.0(*)	mW / °C
COUPLED	Storage Temperature Range	T_{stg}	-55~150	°C
	Operating Temperature Range	T_{opr}	-55~100	°C
	Lead Soldering Temperature	T_{sol}	260	°C
	Total Package Power Dissipation	P_T	250	mW
	Total Package Power Dissipation Derating	$\Delta P_T / ^\circ\text{C}$	3.3(*)	mW / °C







(Note 1) Pulse width 300 μ s, 2% duty cycle.







(*) Above 25°C ambient.

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC			SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
LED	Forward Voltage		V _F	I _F = 10mA	—	1.15	1.5	V
	Reverse Current		I _R	V _R = 3V	—	—	100	μA
	Capacitance		C _D	V = 0, f = 1MHz	—	30	—	pF
DETECTOR	DC Forward Current Gain		h _{FE}	V _{CE} = 5, I _C = 0.5mA	—	10k	—	—
	Collector-Emitter Breakdown Voltage		V (BR) CEO	I _C = 1mA	30	—	—	V
	Collector-Base Breakdown Voltage		V (BR) CBO	I _C = 100μA	30	—	—	V
	Emitter-Collector Breakdown Voltage		V (BR) ECO	I _E = 100μA	5	—	—	V
	Collector Dark Current		I _{CEO}	V _{CE} = 10V	—	1.0	100	nA
COUPLED	Collector Output Current	4N32, 4N32A 4N33	I _C	I _F = 10mA, V _{CE} = 10V	50	—	—	mA
		4N29, 4N29A 4N30			10	—	—	
		4N31			5	—	—	
	Collector-Emitter Saturation Voltage	4N29, 4N29A 4N30, 4N32 4N32A, 4N33	V _{CE} (sat)	I _F = 8mA, I _C = 2mA	—	—	1.0	V
		4N31			—	—	1.2	
	Turn-on Time		t _{ON}	I _F = 200mA, V _{CC} = 10V I _C = 50mA	—	—	5	μs
	Turn-off Time	4N29, 4N29A 4N30, 4N31	t _{OFF}		—	—	40	μs
		4N32, 4N32A 4N33					100	
	Capacitance Input to Output		C _S	V = 0, f = 1MHz	—	0.8	—	pF
	Isolation Resistance		R _S	V = 500V	—	10 ¹¹	—	Ω
	Isolation Voltage		BV _S	AC, 1 minute R. H. ≤ 60%	2500	—	—	V _{rms}
			BV _S (*)	AC, peak	2500	—	—	V _{pk}
					1500	—	—	
1775					—	—	V _{rms}	

(*) JEDEC registered minimum BV_S , however, Toshiba specifies a minimum BV_S of $2500V_{rms}$ 1 minute.





RESTRICTIONS ON PRODUCT USE

000707EBC

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.