

# Common Mode Filter with ESD Protection

## EMI8141, EMI8142, EMI8143

### Functional Description

The EMI814x is a family of Common Mode Filters (CMF) with integrated ESD protection, a first in the industry. Differential signaling I/Os can now have both common mode filtering and ESD protection in one package. The EMI814x protects against ESD pulses up to  $\pm 15$  kV contact per the IEC61000-4-2 standard.

The EMI814x is well-suited for protecting systems using high-speed differential ports such as USB 3.0, MIPI D-PHY; corresponding ports in removable storage, and other applications where ESD protection are required in a small footprint package.

The EMI814x is available in a RoHS-compliant, XDFN6 for one Differential Pair, XDFN-10 for two Differential Pair and XDFN-16 package for three Differential Pair.

### Features

- Total Insertion Loss  $DM_{LOSS} < 2.5$  dB at 2.5 GHz
- Large Differential Mode Cutoff Frequency  $f_{3dB} > 5$  GHz
- High Common Mode Stop Band Attenuation:  
 $> 10$  dB at 500 MHz, 15 dB at 700 MHz
- Low Channel Resistance  $6.0 \Omega$
- Provides ESD Protection to IEC61000-4-2 Level 4,  $\pm 15$  kV Contact
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

### Applications

- USB 3.0
- MHL 2.0
- $\mu$ SD Card
- eSATA
- HDMI/DVI Display in Mobile Phones
- MIPI D-PHY (CSI-2, DSI, etc) in Mobile Phones and Digital Still Cameras




Figure 1. EMI8141 Electrical Schematic



XDFN6  
CASE 711AV





XDFN10  
CASE 711AU





XDFN16  
CASE 711AW

### MARKING DIAGRAMS



XX = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package

### ELECTRICAL SCHEMATICS



### ORDERING INFORMATION

| Device       | Package | Shipping <sup>†</sup> |
|--------------|---------|-----------------------|
| EMI8141MUTAG | XDFN6   | 3000 / Tape & Reel    |
| EMI8142MUTAG | XDFN10  | 3000 / Tape & Reel    |
| EMI8143MUTAG | XDFN16  | 3000 / Tape & Reel    |

<sup>†</sup> For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, [BRD8011/D](http://www.onsemi.com/BRD8011/D).

# EMI8141, EMI8142, EMI8143

## PIN FUNCTION DESCRIPTION

| Pin Name | Device Pin |         |           | Type | Description                            |
|----------|------------|---------|-----------|------|----------------------------------------|
|          | EMI8141    | EMI8142 | EMI8143   |      |                                        |
| In_1+    | 1          | 1       | 1         | I/O  | CMF Channel 1+ to Connector (External) |
| In_1-    | 2          | 2       | 2         | I/O  | CMF Channel 1- to Connector (External) |
| Out_1+   | 6          | 10      | 16        | I/O  | CMF Channel 1+ to ASIC (Internal)      |
| Out_1-   | 5          | 9       | 15        | I/O  | CMF Channel 1- to ASIC (Internal)      |
| In_2+    | NA         | 4       | 4         | I/O  | CMF Channel 2+ to Connector (External) |
| In_2-    | NA         | 5       | 5         | I/O  | CMF Channel 2- to Connector (External) |
| Out_2+   | NA         | 7       | 13        | I/O  | CMF Channel 2+ to ASIC (Internal)      |
| Out_2-   | NA         | 6       | 12        | I/O  | CMF Channel 2- to ASIC (Internal)      |
| In_3+    | NA         | NA      | 7         | I/O  | CMF Channel 3+ to Connector (External) |
| In_3-    | NA         | NA      | 8         | I/O  | CMF Channel 3- to Connector (External) |
| Out_3+   | NA         | NA      | 10        | I/O  | CMF Channel 3+ to ASIC (Internal)      |
| Out_3-   | NA         | NA      | 9         | I/O  | CMF Channel 3- to ASIC (Internal)      |
| VN       | 3,4        | 3, 8    | 3,6,14,11 | GND  | Ground                                 |

## ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

| Parameter                                                                          | Symbol     | Value       | Unit             |
|------------------------------------------------------------------------------------|------------|-------------|------------------|
| Operating Temperature Range                                                        | $T_{OP}$   | -40 to +85  | $^\circ\text{C}$ |
| Storage Temperature Range                                                          | $T_{STG}$  | -65 to +150 | $^\circ\text{C}$ |
| Maximum Lead Temperature for Soldering Purposes<br>(1/8" from Case for 10 seconds) | $T_L$      | 260         | $^\circ\text{C}$ |
| DC Current per Line                                                                | $I_{LINE}$ | 100         | mA               |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

# EMI8141, EMI8142, EMI8143

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25 °C unless otherwise noted)


| Symbol             | Parameter                                                                                                                                                                                                 | Test Conditions                                                                                                                      | Min       | Typ                          | Max | Unit |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|-----------|------------------------------|-----|------|
| V <sub>RWM</sub>   | Reverse Working Voltage                                                                                                                                                                                   | (Note 3)                                                                                                                             |           | 3.3                          |     | V    |
| V <sub>BR</sub>    | Breakdown Voltage                                                                                                                                                                                         | I <sub>T</sub> = 1 mA; (Note 4)                                                                                                      | 4.0       |                              | 9.0 | V    |
| I <sub>LEAK</sub>  | Channel Leakage Current                                                                                                                                                                                   | T <sub>A</sub> = 25 °C, V <sub>IN</sub> = 3.3 V, GND = 0 V                                                                           |           |                              | 1.0 | μA   |
| R <sub>CH</sub>    | Channel Resistance<br>(Pins 1–6, 2–5) – EMI8141<br>(Pins 1–10, 2–9, 4–7 and 5–6) – EMI8142<br>(Pins 1–16, 2–15, 4–13, 5–12, 7–10 and 8–9) – EMI8143                                                       |                                                                                                                                      |           | 6.0                          |     | Ω    |
| DM <sub>LOSS</sub> | Differential Mode Insertion Loss                                                                                                                                                                          | @ 2.5 GHz                                                                                                                            |           | 2.5                          |     | dB   |
| f <sub>3dB</sub>   | Differential Mode Cut-off Frequency                                                                                                                                                                       | 50 Ω Source and Load Termination                                                                                                     |           | 5.0                          |     | GHz  |
| F <sub>atten</sub> | Common Mode Stop Band Attenuation                                                                                                                                                                         | @ 700 MHz                                                                                                                            |           | 15                           |     | dB   |
| V <sub>ESD</sub>   | In-system ESD Withstand Voltage<br>a) Contact discharge per IEC 61000-4-2 standard, Level 4 ( <b>External Pins</b> )<br>b) Contact discharge per IEC 61000-4-2 standard, Level 1 ( <b>Internal Pins</b> ) | (Notes 1 and 2)                                                                                                                      | ±15<br>±2 |                              |     | kV   |
| V <sub>CL</sub>    | TLP Clamping Voltage                                                                                                                                                                                      | Forward I <sub>PP</sub> = 8 A<br>Forward I <sub>PP</sub> = 16 A<br>Forward I <sub>PP</sub> = –8 A<br>Forward I <sub>PP</sub> = –16 A |           | 7.26<br>11.8<br>–3.5<br>–6.7 |     | V    |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.


1. Standard IEC61000-4-2 with C<sub>Discharge</sub> = 150 pF, R<sub>Discharge</sub> = 330, GND grounded.
2. These measurements performed with no external capacitor.
3. TVS devices are normally selected according to the working peak reverse voltage (V<sub>RWM</sub>), which should be equal to or greater than the DC or continuous peak operating voltage level.
4. V<sub>BR</sub> is measured at pulse test current I<sub>T</sub>.

# EMI8141, EMI8142, EMI8143

## TYPICAL CHARACTERISTICS



**Figure 2. Typical Differential Mode Attenuation vs. Frequency**




**Figure 3. Typical Common Mode Attenuation vs. Frequency**


| Interface | Data Rate (Gb/s) | Fundamental Frequency (GHz) | ESD814x Insertion Loss (dB) |
|-----------|------------------|-----------------------------|-----------------------------|
| USB 3.0   | 5                | 2.5 (m1)                    | m1 = 2.13                   |

## TRANSMISSION LINE PULSE (TLP) MEASUREMENTS


Transmission Line Pulse (TLP) provides current versus voltage (I-V) curves in which each data point is obtained from a 100 ns long rectangular pulse from a charged transmission line. A simplified schematic of a typical TLP system is shown in Figure 4. TLP I-V curves of ESD protection devices accurately demonstrate the product's ESD capability because the 10 s of amps current levels and under 100 ns time scale match those of an ESD event. This is illustrated in Figure 5 where an 8 kV IEC61000-4-2 current waveform is compared with TLP current pulses at 8 A and 16 A. A TLP curve shows the voltage at which the device turns on as well as how well the device clamps voltage over a range of current levels. Typical TLP I-V curves for the EMI814x are shown in Figure 4.



**Figure 4. Simplified Schematic of a Typical TLP System**



**Figure 5. Comparison Between 8 kV IEC61000-4-2 and 8 A and 16 A TLP Waveforms**



**Figure 6. Positive and Negative TLP Waveforms**

## EMI8141, EMI8142, EMI8143




Figure 7. Eye Diagram Test Setup for 5Gbps Data Rate




Figure 8. Eye Diagram 5Gbps with and without EMI814x

|                                   | Eye Height (mVppd) | Rise Time (ps) | Fall Time (ps) | Jrms (ps) | Jpp (ps) |
|-----------------------------------|--------------------|----------------|----------------|-----------|----------|
| Reference (No Device)-Left Figure | 724                | 30.4           | 29.6           | 1.997     | 9.6      |
| EMI814x Right Figure              | 405                | 60             | 60.8           | 3.484     | 16       |

## EMI8141, EMI8142, EMI8143

### REVISION HISTORY

| Revision | Description of Changes                            | Date       |
|----------|---------------------------------------------------|------------|
| 1        | Rebranded the Data Sheet to <b>onsemi</b> format. | 06/30/2025 |



This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.




SCALE 4:1

**XDFN10 2.2x1.35, 0.4P**  
CASE 711AU  
ISSUE B

DATE 17 JUN 2014


**DETAIL A**  
ALTERNATE  
CONSTRUCTIONS


EXPOSED Cu MOLD CMPD


**DETAIL B**  
ALTERNATE  
CONSTRUCTION

## NOTES:


1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSIONS b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM THE TERMINAL TIP.

| MILLIMETERS |          |      |
|-------------|----------|------|
| DIM         | MIN      | MAX  |
| A           | 0.40     | 0.50 |
| A1          | 0.00     | 0.05 |
| A3          | 0.15 REF |      |
| b           | 0.15     | 0.25 |
| D           | 2.20 BSC |      |
| E           | 1.35 BSC |      |
| e           | 0.40 BSC |      |
| L           | 0.40     | 0.60 |
| L1          | ---      | 0.15 |

**GENERIC  
MARKING DIAGRAM\***


- XX = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present.

**RECOMMENDED  
MOUNTING FOOTPRINT**


DIMENSIONS: MILLIMETERS

|                         |                              |                                                                                                                                                                                  |
|-------------------------|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON83517F</b>           | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>XDFN10 2.2X1.35, 0.4P</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.







SCALE 4:1

**XDFN6 1.40x1.35, 0.4P**  
CASE 711AV  
ISSUE A


DATE 04 JUN 2014



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
  2. CONTROLLING DIMENSION: MILLIMETERS.
  3. DIMENSIONS b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM TERMINAL TIP.

| MILLIMETERS |          |      |
|-------------|----------|------|
| DIM         | MIN      | MAX  |
| A           | 0.40     | 0.50 |
| A1          | 0.00     | 0.05 |
| A3          | 0.15 REF |      |
| b           | 0.15     | 0.25 |
| D           | 1.40 BSC |      |
| E           | 1.35 BSC |      |
| e           | 0.40 BSC |      |
| L           | 0.40     | 0.60 |
| L1          | ---      | 0.15 |

### GENERIC MARKING DIAGRAM\*




- XX = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package

(Note: Microdot may be in either location)


\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present.

### RECOMMENDED MOUNTING FOOTPRINT






|                         |                              |                                                                                                                                                                                  |
|-------------------------|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON83554F</b>           | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>XDFN6 1.40X1.35, 0.4P</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.



**XDFN16 3.5x1.35, 0.4P**  
CASE 711AW  
ISSUE A

DATE 17 JUN 2014



**NOTES:**

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 mm FROM THE TERMINAL TIP.

| MILLIMETERS |          |      |
|-------------|----------|------|
| DIM         | MIN      | MAX  |
| A           | 0.40     | 0.50 |
| A1          | 0.00     | 0.05 |
| A3          | 0.15 REF |      |
| b           | 0.15     | 0.25 |
| D           | 3.50 BSC |      |
| E           | 1.35 BSC |      |
| e           | 0.40 BSC |      |
| L           | 0.40     | 0.60 |
| L1          | ---      | 0.15 |


**GENERIC MARKING DIAGRAM\***



XXX = Specific Device Code  
M = Month Code  
▪ = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking.  
Pb-Free indicator, "G" or microdot "▪", may or may not be present.

**RECOMMENDED SOLDERING FOOTPRINT\***



\*For additional information on our Pb-Free strategy and soldering details, please download the [onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D](#).

|                         |                              |                                                                                                                                                                                     |
|-------------------------|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON83555F</b>           | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>XDFN16 3.5X1.35, 0.4P</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                                  |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)