



ARK Home ▶

Add to Compare
Twitter
Facebook
LinkedIn

## Intel® Atom™ Processor E3815 (512K Cache, 1.46 GHz)

**SPECIFICATIONS**

- [Essentials](#)
- [Memory Specifications](#)
- [Graphics Specifications](#)
- [Expansion Options](#)
- [I/O Specifications](#)
- [Package Specifications](#)
- [Advanced Technologies](#)
- [Intel® Data Protection Technology](#)
- [Intel® Platform Protection Technology](#)

**ORDERING / SSPECS / STEPPINGS**

**SPECIFICATIONS**

Essentials	
Status	Launched
Launch Date	Q4'13
Processor Number	E3815
# of Cores	1
# of Threads	1
Clock Speed	1.46 GHz
Cache	512 KB
Instruction Set	64-bit
Embedded Options Available	Yes
Lithography	22 nm
Max TDP	5 W
Recommended Customer Price	

  

Memory Specifications	
Max Memory Size (dependent on memory type)	8 GB
Memory Types	DDR3L-1067
# of Memory Channels	1
ECC Memory Supported <small>‡</small>	Yes

  

Graphics Specifications	
Processor Graphics <small>‡</small>	Intel® HD Graphics
Graphics Base Frequency	400 MHz
Graphics Burst Frequency	400 MHz
# of Displays Supported <small>‡</small>	2

  

Expansion Options	
PCI Express Revision	2.0
PCI Express Configurations <small>‡</small>	x4, x2, x1
Max # of PCI Express Lanes	4

  

I/O Specifications	
USB Revision	2.0, 3.0
Total # of SATA Ports	2
Integrated LAN	No
Integrated IDE	No
UART	Yes

  

Package Specifications	
T <sub>JUNCTION</sub>	-40°C to 110°C
Package Size	25mm x27mm
Sockets Supported	FCBGA1170

**RELATED PRODUCTS**

- [Intel® Atom™ Processor](#)
- [Intel® Atom™ Processor E3800 Series](#)
- [Products formerly Bay Trail](#)



[Visit the Embedded Design Center >](#)

**QUICK LINKS**

- [No Datasheet Available](#)
- [Export Full Specifications](#)
- [Search Distributors](#)
- [Software Downloads](#)
- [Support Overview](#)
- [Search all of intel.com](#)

**PCN/MDDs Information**

**SR1RA**  
932048: [PCN](#) | [MDDs](#)



[Visit Intel AppUp<sup>SM</sup> >](#)

[http://ark.intel.com/products/78476/Intel-Atom-Processor-E3815-512K-Cache-1\\_46-GHz](http://ark.intel.com/products/78476/Intel-Atom-Processor-E3815-512K-Cache-1_46-GHz)

1 / 2

Low Halogen Options Available	See MDDS
-------------------------------	----------

### Advanced Technologies

Intel® vPro Technology‡	<input checked="" type="checkbox"/> No
Intel® Hyper-Threading Technology‡	<input checked="" type="checkbox"/> No
Intel® Virtualization Technology (VT-x)‡	<input checked="" type="checkbox"/> Yes
Intel® Virtualization Technology for Directed I/O (VT-d)‡	<input checked="" type="checkbox"/> No
Intel® 64‡	<input checked="" type="checkbox"/> Yes
Intel® HD Audio Technology	<input checked="" type="checkbox"/> Yes

### Intel® Data Protection Technology

AES New Instructions	<input checked="" type="checkbox"/> Yes
----------------------	---

### Intel® Platform Protection Technology

Trusted Execution Technology‡	<input checked="" type="checkbox"/> No
Execute Disable Bit‡	<input checked="" type="checkbox"/> Yes

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

"Intel classifications" consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company may be the exporter of record, and as such, your company is responsible for determining the correct classification of any item at the time of export.

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

‡ This feature may not be available on all computing systems. Please check with the system vendor to determine if your system delivers this feature, or reference the system specifications (motherboard, processor, chipset, power supply, HDD, graphics controller, memory, BIOS, drivers, virtual machine monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

See <http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html?wapkw=hyper+threading> for more information including details on which processors support Intel® HT Technology.

Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See [www.intel.com/technology/turboboost/](http://www.intel.com/technology/turboboost/) for more information.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply. Listing of these RCP does not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

For benchmarking data see <http://www.intel.com/performance>.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See <http://www.intel.com/content/www/us/en/processors/processor-numbers.html> for details.

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.

[Send us your feedback!](#)

