



POWER SUPPLY UNIV 24VDC OUTPUT

Part Number: AP9505I



Output	
Number of Ports	1
Physical	
Net Weight	0.34 KG
Maximum Height	70.00 mm
Maximum Width	95.00 mm
Maximum Depth	70.00 mm
Shipping Weight	0.50 KG
Shipping Height	76.00 mm
Shipping Width	235.00 mm
Shipping Depth	140.00 mm
Connector A	IEC320-C7(Power)

Connector B	BS-1363(Power)
-------------	----------------

Environmental

Operating Environment	0 - 45 °C
-----------------------	-----------

Operating Relative Humidity	0 - 95%
-----------------------------	---------

Operating Elevation	0-3000 meters
---------------------	---------------

Storage Temperature	-15 - 45 °C
---------------------	-------------

Storage Relative Humidity	0 - 95%
---------------------------	---------

Storage Elevation	0-15000 meters
-------------------	----------------

Conformance

Regulatory Approvals	AS/NZS 3548 (C-Tick) Class A, cUL Listed, CE, EMC Directive 2004/108/EC, FCC Part 15 Class A, ICES-003, Low Voltage Directive 2006/95/EC, PSE, UL Listed, VCCI Class A, VDE
----------------------	---

Standard Warranty	2 years repair or replace
-------------------	---------------------------

Sustainable Offer Status

RoHS	Compliant
------	-----------

*