



## Optocoupler, Phototransistor Output, High Reliability, 5300 V<sub>RMS</sub>



17448-5

1



### DESCRIPTION

The SFH615A-3X018T features a variety of transfer ratios, low coupling capacitance and high isolation voltage. This coupler has a GaAs infrared diode emitter, which is optically coupled to a silicon planar phototransistor detector, and is incorporated in a plastic SMD package.

The coupling devices are designed for signal transmission between two electrically separated circuits.

### FEATURES

- Excellent CTR linearity depending on forward current
- Isolation test voltage, 5300 V<sub>RMS</sub>
- Fast switching times
- Low CTR degradation
- Low coupling capacitance
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

### APPLICATIONS

- Switchmode power supply
- Telecom
- Battery powered equipment

### AGENCY APPROVALS

- UL1577, file no. E52744 system code H or J, double protection
- DIN EN 60747-5-5 (VDE 0884-5) available with option 1
- cUL tested to CSA 22.2 bulletin 5A
- BSI IEC 60950, IEC 60065
- FIMKO EN6005, EN60950-1

ORDERING INFORMATION																				
S    F    H    6    1    5    A    -    3							X    0    1    8    T													
PART NUMBER							CTR BIN													
CTR (%)																				
10 mA																				
100 to 200																				
SFH615A-3X018T																				
SMD-4 9.27 mm																				
AGENCY CERTIFIED/PACKAGE																				
VDE, UL, cUL, BSI, FIMKO																				
SMD-4, option 8																				

**ABSOLUTE MAXIMUM RATINGS** ( $T_{amb} = 25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
<b>INPUT</b>				
Reverse voltage		$V_R$	6	V
DC forward current		$I_F$	60	mA
Surge forward current	$t_p \leq 10 \mu\text{s}$	$I_{FSM}$	2.5	A
<b>OUTPUT</b>				
Collector emitter voltage		$V_{CEO}$	70	V
Emitter collector voltage		$V_{ECO}$	7	V
Collector current	$t_p \leq 1 \text{ ms}$	$I_C$	50	mA
		$I_C$	100	mA
<b>COUPLER</b>				
Isolation test voltage between emitter and detector	$t = 1 \text{ s}$	$V_{ISO}$	5300	$V_{RMS}$
Creepage distance			$\geq 7$	mm
Clearance distance			$\geq 7$	mm
Insulation thickness between emitter and detector			$\geq 0.4$	mm
Comparative tracking index per DIN IEC112/VDE0303 part 1		CTI	$\geq 175$	
Isolation resistance	$V_{IO} = 500 \text{ V}, T_{amb} = 25^\circ\text{C}$	$R_{IO}$	$\geq 10^{12}$	$\Omega$
	$V_{IO} = 500 \text{ V}, T_{amb} = 100^\circ\text{C}$	$R_{IO}$	$\geq 10^{11}$	$\Omega$
Storage temperature range		$T_{stg}$	- 55 to + 150	$^\circ\text{C}$
Ambient temperature range		$T_{amb}$	- 55 to +100	$^\circ\text{C}$
Soldering temperature <sup>(1)</sup>	max. 10 s	$T_{sld}$	260	$^\circ\text{C}$

**Notes**

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.

(1) Refer to reflow profile for soldering conditions for surface mounted devices (SMD).





Fig. 1 - Permissible Power Dissipation vs. Ambient Temperature

**THERMAL CHARACTERISTICS**

PARAMETER	SYMBOL	VALUE	UNIT
LED power dissipation	$P_{diss}$	100	mW
Output power dissipation	$P_{diss}$	150	mW
Maximum LED junction temperature	$T_{jmax.}$	125	°C
Maximum output die junction temperature	$T_{jmax.}$	125	°C
Thermal resistance, junction emitter to board	$\theta_{EB}$	173	°C/W
Thermal resistance, junction emitter to case	$\theta_{EC}$	149	°C/W
Thermal resistance, junction detector to board	$\theta_{DB}$	111	°C/W
Thermal resistance, junction detector to case	$\theta_{DC}$	127	°C/W
Thermal resistance, junction emitter to junction detector	$\theta_{ED}$	95	°C/W
Thermal resistance, board to ambient <sup>(1)</sup>	$\theta_{BA}$	195	°C/W
Thermal resistance, case to ambient <sup>(1)</sup>	$\theta_{CA}$	3573	°C/W


**Notes**

- The thermal model is represented in the thermal network below. Each resistance value given in this model can be used to calculate the temperatures at each node for a given operating condition. The thermal resistance from board to ambient will be dependent on the type of PCB, layout and thickness of copper traces. For a detailed explanation of the thermal model, please reference Vishay's thermal characteristics of optocouplers application note.

<sup>(1)</sup> For 2 layer FR4 board (4" x 3" x 0.062")

**ELECTRICAL CHARACTERISTICS** ( $T_{amb} = 25$  °C, unless otherwise specified)

PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
<b>INPUT</b>						
Forward voltage	$I_F = 60$ mA	$V_F$		1.25	1.65	V
Reverse current	$V_R = 6$ V	$I_R$		0.01	10	µA
Capacitance	$V_R = 0$ V, $f = 1$ MHz	$C_O$		13		pF
<b>OUTPUT</b>						
Collector emitter capacitance	$V_{CE} = 5$ V, $f = 1$ MHz	$C_{CE}$		5.2		pF
Collector emitter leakage current	$V_{CE} = 10$ V	$I_{CEO}$		5	100	nA
<b>COUPLER</b>						
Collector emitter saturation voltage	$I_F = 10$ mA, $I_C = 2.5$ mA	$V_{CEsat}$		0.25	0.4	V
Coupling capacitance		$C_C$		0.4		pF

**Note**

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.

**CURRENT TRANSFER RATIO**

PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
$I_C/I_F$	$I_F = 10$ mA, $V_{CE} = 5$ V	CTR	100		200	%
	$I_F = 1$ mA, $V_{CE} = 5$ V	CTR	34	70		%

**SWITCHING CHARACTERISTICS**


PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
<b>NON-SATURATED</b>						
Rise time	$I_F = 10 \text{ mA}, V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}, R_L = 75 \Omega$	$t_r$		2		$\mu\text{s}$
Fall time	$I_F = 10 \text{ mA}, V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}, R_L = 75 \Omega$	$t_f$		2		$\mu\text{s}$
Turn-on time	$I_F = 10 \text{ mA}, V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}, R_L = 75 \Omega$	$t_{on}$		3		$\mu\text{s}$
Turn-off time	$I_F = 10 \text{ mA}, V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}, R_L = 75 \Omega$	$t_{off}$		2.3		$\mu\text{s}$
Cut-off frequency	$I_F = 10 \text{ mA}, V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}, R_L = 75 \Omega$	$f_{ctr}$		250		$\text{kHz}$
<b>SATURATED</b>						
Rise time	$V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}, R_L = 1 \text{ k}\Omega, I_F = 10 \text{ mA}$	$t_r$		3		$\mu\text{s}$
Fall time	$V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}, R_L = 1 \text{ k}\Omega, I_F = 10 \text{ mA}$	$t_f$		14		$\mu\text{s}$
Turn-on time	$V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}, R_L = 1 \text{ k}\Omega, I_F = 10 \text{ mA}$	$t_{on}$		4.2		$\mu\text{s}$
Turn-off time	$V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}, R_L = 1 \text{ k}\Omega, I_F = 10 \text{ mA}$	$t_{off}$		23		$\mu\text{s}$

**SAFETY AND INSULATION RATINGS**

PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
Climatic classification (according to IEC 68 part 1)				55/100/21		
Comparative tracking index		CTI	175		399	
$V_{IOTM}$		$V_{IOTM}$	10 000			$V_{\text{peak}}$
$V_{IORM}$		$V_{IORM}$	890			$V_{\text{peak}}$
$P_{SO}$		$P_{SO}$			400	$\text{mW}$
$I_{SI}$		$I_{SI}$			275	$\text{mA}$
$T_{SI}$		$T_{SI}$			175	$^\circ\text{C}$
Creepage distance			7			$\text{mm}$
Clearance distance			7			$\text{mm}$
Insulation thickness, reinforced rated	per IEC 60950 2.10.5.1		0.4			$\text{mm}$

**Note**

- As per IEC 60747-5-5, § 7.4.3.8.2, this optocoupler is suitable for "safe electrical insulation" only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits.

**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25^{\circ}\text{C}$ , unless otherwise specified)


isfh615a\_01





Fig. 5 - Output Characteristics (Typ.) Collector Current vs. Collector Emitter Voltage



isfh615a\_02

Fig. 3 - Switching Operation (with Saturation)




Fig. 6 - Diode Forward Voltage (Typ.) vs. Forward Current




Fig. 4 - Current Transfer Ratio (Typ.) vs. Temperature




Fig. 7 - Transistor Capacitance (Typ.) vs. Collector Emitter Voltage






Fig. 8 - Permissible Pulse Handling Capability Forward Current vs. Pulse Width

### PACKAGE DIMENSIONS millimeters



### PACKAGE MARKING (example of SFH615A-3X018T)



#### Notes

- VDE logo is only marked on option 1 parts.
- Tape and reel suffix (T) is not part of the package marking.

## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.