

			<table><tr><th colspan="4">REVISIONS</th></tr><tr><th>REV</th><th>DESCRIPTION</th><th>DATE</th><th>APPROVED</th></tr><tr><td>01</td><td>RELEASED</td><td>KYLE 10-6-97</td><td>PCW 10/7/97</td></tr><tr><td>B</td><td>REVISED PER ECN 0020-0262-01</td><td>GV 1/6/03</td><td>JGH</td></tr></table>				REVISIONS				REV	DESCRIPTION	DATE	APPROVED	01	RELEASED	KYLE 10-6-97	PCW 10/7/97	B	REVISED PER ECN 0020-0262-01	GV 1/6/03	JGH																																																																																																																									
			REVISIONS																																																																																																																																												
			REV	DESCRIPTION	DATE	APPROVED																																																																																																																																									
01	RELEASED	KYLE 10-6-97	PCW 10/7/97																																																																																																																																												
B	REVISED PER ECN 0020-0262-01	GV 1/6/03	JGH																																																																																																																																												
RECOMMENDED MOUNTING HOLE																																																																																																																																															
<table><tr><th colspan="2">ELECTRICAL</th></tr><tr><td>Nominal Impedance (Ohms)</td><td>50</td></tr><tr><td>Frequency Range (GHz) DC to</td><td>22</td></tr><tr><td>Volt Rating (VRMS MAX) @ Sea Level</td><td>335</td></tr><tr><td>VSWR</td><td>TBD</td></tr><tr><td>Insertion Loss (dB MAX)</td><td>TBD</td></tr><tr><td>RF Leakage (dB MIN) (Interface Only, Fully Mated)</td><td>-(90-f(GHz))</td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN)</td><td>250</td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level</td><td>1000</td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td></td></tr><tr><td>Center Contact</td><td>4.0</td></tr><tr><td>Outer Contact</td><td>2.0</td></tr><tr><td>RF High Potential @ Sea Level (VRMS MIN @ 5 MHz)</td><td>670</td></tr><tr><td>I.R.(Megohms MIN)</td><td>5000</td></tr></table>		ELECTRICAL		Nominal Impedance (Ohms)	50	Frequency Range (GHz) DC to	22	Volt Rating (VRMS MAX) @ Sea Level	335	VSWR	TBD	Insertion Loss (dB MAX)	TBD	RF Leakage (dB MIN) (Interface Only, Fully Mated)	-(90-f(GHz))	Corona, 70,000 Ft (VRMS MIN)	250	Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level	1000	Contact Resistance (Milliohms MAX)		Center Contact	4.0	Outer Contact	2.0	RF High Potential @ Sea Level (VRMS MIN @ 5 MHz)	670	I.R.(Megohms MIN)	5000	<table><tr><th colspan="2">MECHANICAL</th></tr><tr><td colspan="2">Interface Dimensions (DSP End Only)</td></tr><tr><td colspan="2">MIL-STD-348, Fig 321-1</td></tr><tr><td>Force to Engage</td><td></td></tr><tr><td>3.5mm (In-Lbs MAX)</td><td>2</td></tr><tr><td>DSP (Lbs MAX)</td><td>3</td></tr><tr><td>Force to Disengage</td><td></td></tr><tr><td>3.5mm (In-Lbs MAX)</td><td>2</td></tr><tr><td>DSP (Lbs MAX)</td><td>1.5</td></tr><tr><td>Center Contact Captivation</td><td></td></tr><tr><td>Axial (Lbs)</td><td>6</td></tr><tr><td>Mating Characteristics (3.5mm Only)</td><td></td></tr><tr><td>Insertion (Lbs MAX)</td><td>3</td></tr><tr><td>Withdrawal (Oz MIN)</td><td>1</td></tr></table>		MECHANICAL		Interface Dimensions (DSP End Only)		MIL-STD-348, Fig 321-1		Force to Engage		3.5mm (In-Lbs MAX)	2	DSP (Lbs MAX)	3	Force to Disengage		3.5mm (In-Lbs MAX)	2	DSP (Lbs MAX)	1.5	Center Contact Captivation		Axial (Lbs)	6	Mating Characteristics (3.5mm Only)		Insertion (Lbs MAX)	3	Withdrawal (Oz MIN)	1	<table><tr><th colspan="2">ENVIRONMENTAL</th></tr><tr><td colspan="2">TEMPERATURE RATING -65° TO +125°C</td></tr><tr><td colspan="2">Vibration MIL-STD-202, Method 204, Condition D</td></tr><tr><td colspan="2">Shock MIL-STD-202, Method 213, Condition I</td></tr><tr><td colspan="2">Thermal Shock MIL-STD-202, Method 107, Condition B</td></tr><tr><td colspan="2">Moisture Resistance MIL-STD-202, Method 106</td></tr><tr><td colspan="2">Corrosion - MIL-STD-202, Method 101, Condition B</td></tr></table> .XXX = in XX.X = mm (REF)		ENVIRONMENTAL		TEMPERATURE RATING -65° TO +125°C		Vibration MIL-STD-202, Method 204, Condition D		Shock MIL-STD-202, Method 213, Condition I		Thermal Shock MIL-STD-202, Method 107, Condition B		Moisture Resistance MIL-STD-202, Method 106		Corrosion - MIL-STD-202, Method 101, Condition B		<table><tr><td>HOUSING MOUNTING NUT LOCKWASHER</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>PASSIVATE PER QQ-P-35</td></tr><tr><td>DIELECTRIC</td><td>PTFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>O-RING</td><td>FLOUROSILICONE PER MIL-R-25988, CLASS I, TYPE I.</td><td>N/A</td></tr></table> <table><tr><th>COMPONENT</th><th>MATERIAL</th><th>FINISH</th></tr><tr><td colspan="3">UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES</td></tr><tr><td>FRAC.</td><td>DEC.</td><td>ANGLES</td></tr><tr><td>± 1/64</td><td>± .005</td><td>± 1°</td></tr><tr><td colspan="3">These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.</td></tr><tr><td colspan="3">DRAWN BY: J. Amato DATE: 7/22/97</td></tr><tr><td colspan="3">CHECKED BY:</td></tr><tr><td colspan="3">APP'D BY:</td></tr><tr><td colspan="3">USE ASS'Y PROCEDURE</td></tr><tr><td colspan="3">NO. AP. N/A</td></tr></table> <table><tr><td colspan="4">AMP Incorporated</td></tr><tr><td colspan="4">140 Fourth Avenue</td></tr><tr><td colspan="4">Waltham, MA 02451-7599</td></tr></table> <table><tr><td colspan="4">TITLE DSP BULKHEAD FEEDTHRU PLUG TO 3.5MM JACK ADAPTER</td></tr><tr><td>SIZE B</td><td>CODE IDENT NO. 26805</td><td>4585-2352-02</td><td>REV 01</td></tr><tr><td colspan="2">SCALE 4:1</td><td colspan="2">SHEET 1 OF 1</td></tr></table>		HOUSING MOUNTING NUT LOCKWASHER	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35	DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	O-RING	FLOUROSILICONE PER MIL-R-25988, CLASS I, TYPE I.	N/A	COMPONENT	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			FRAC.	DEC.	ANGLES	± 1/64	± .005	± 1°	These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.			DRAWN BY: J. Amato DATE: 7/22/97			CHECKED BY:			APP'D BY:			USE ASS'Y PROCEDURE			NO. AP. N/A			AMP Incorporated				140 Fourth Avenue				Waltham, MA 02451-7599				TITLE DSP BULKHEAD FEEDTHRU PLUG TO 3.5MM JACK ADAPTER				SIZE B	CODE IDENT NO. 26805	4585-2352-02	REV 01	SCALE 4:1		SHEET 1 OF 1	
ELECTRICAL																																																																																																																																															
Nominal Impedance (Ohms)	50																																																																																																																																														
Frequency Range (GHz) DC to	22																																																																																																																																														
Volt Rating (VRMS MAX) @ Sea Level	335																																																																																																																																														
VSWR	TBD																																																																																																																																														
Insertion Loss (dB MAX)	TBD																																																																																																																																														
RF Leakage (dB MIN) (Interface Only, Fully Mated)	-(90-f(GHz))																																																																																																																																														
Corona, 70,000 Ft (VRMS MIN)	250																																																																																																																																														
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level	1000																																																																																																																																														
Contact Resistance (Milliohms MAX)																																																																																																																																															
Center Contact	4.0																																																																																																																																														
Outer Contact	2.0																																																																																																																																														
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz)	670																																																																																																																																														
I.R.(Megohms MIN)	5000																																																																																																																																														
MECHANICAL																																																																																																																																															
Interface Dimensions (DSP End Only)																																																																																																																																															
MIL-STD-348, Fig 321-1																																																																																																																																															
Force to Engage																																																																																																																																															
3.5mm (In-Lbs MAX)	2																																																																																																																																														
DSP (Lbs MAX)	3																																																																																																																																														
Force to Disengage																																																																																																																																															
3.5mm (In-Lbs MAX)	2																																																																																																																																														
DSP (Lbs MAX)	1.5																																																																																																																																														
Center Contact Captivation																																																																																																																																															
Axial (Lbs)	6																																																																																																																																														
Mating Characteristics (3.5mm Only)																																																																																																																																															
Insertion (Lbs MAX)	3																																																																																																																																														
Withdrawal (Oz MIN)	1																																																																																																																																														
ENVIRONMENTAL																																																																																																																																															
TEMPERATURE RATING -65° TO +125°C																																																																																																																																															
Vibration MIL-STD-202, Method 204, Condition D																																																																																																																																															
Shock MIL-STD-202, Method 213, Condition I																																																																																																																																															
Thermal Shock MIL-STD-202, Method 107, Condition B																																																																																																																																															
Moisture Resistance MIL-STD-202, Method 106																																																																																																																																															
Corrosion - MIL-STD-202, Method 101, Condition B																																																																																																																																															
HOUSING MOUNTING NUT LOCKWASHER	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35																																																																																																																																													
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A																																																																																																																																													
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																																																																																																													
O-RING	FLOUROSILICONE PER MIL-R-25988, CLASS I, TYPE I.	N/A																																																																																																																																													
COMPONENT	MATERIAL	FINISH																																																																																																																																													
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES																																																																																																																																															
FRAC.	DEC.	ANGLES																																																																																																																																													
± 1/64	± .005	± 1°																																																																																																																																													
These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.																																																																																																																																															
DRAWN BY: J. Amato DATE: 7/22/97																																																																																																																																															
CHECKED BY:																																																																																																																																															
APP'D BY:																																																																																																																																															
USE ASS'Y PROCEDURE																																																																																																																																															
NO. AP. N/A																																																																																																																																															
AMP Incorporated																																																																																																																																															
140 Fourth Avenue																																																																																																																																															
Waltham, MA 02451-7599																																																																																																																																															
TITLE DSP BULKHEAD FEEDTHRU PLUG TO 3.5MM JACK ADAPTER																																																																																																																																															
SIZE B	CODE IDENT NO. 26805	4585-2352-02	REV 01																																																																																																																																												
SCALE 4:1		SHEET 1 OF 1																																																																																																																																													