

C3216X7R2A224K115AA (TDK item description : C3216X7R2A224KT****)

Applications



Commercial Grade



Please refer to Part No. CGA5H2X7R2A224K115AA for automotive use.


Feature

Mid

Mid Voltage (100 to 630V)

Series

C3216 [EIA CC1206]



Size

Length(L)	3.20mm +/-0.20mm
Width(W)	1.60mm +/-0.20mm
Thickness(T)	1.15mm +/-0.15mm
Terminal Width(B)	0.20mm Min.
Terminal Spacing(G)	1.00mm Min.
Recommended Land Pattern(PA)	2.10 to 2.50mm (Flow Soldering) 2.00 to 2.40mm (Reflow Soldering)
Recommended Land Pattern(PB)	1.10 to 1.30mm (Flow Soldering) 1.00 to 1.20mm (Reflow Soldering)
Recommended Land Pattern(PC)	1.00 to 1.30mm (Flow Soldering) 1.10 to 1.60mm (Reflow Soldering)
Recommended Slit Pattern(SD)	

Electrical Characteristics

Capacitance	220nF +/-10%
Rated Voltage	100Vdc
Temperature Characteristic	X7R(+/-15%)
Dissipation Factor	3% Max.
Insulation Resistance	2272MΩ Min.

Other

Soldering Method	Reflow, Flow
AEC Q200	No
Packing	Blister (Plastic)Taping [180mm Reel]
Package Quantity	2000Pcs Min.

C3216X7R2A224K115AA

Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)

