

TABLE 1					
EDGE MOUNT THICKNESS	"A"	"B"	"C"	BODY	CONTACT
-EM2	.130[3.30]	.0670[1.702]	.058[1.47]	BTE-XXX-01-D-EM2	T-1S42-01-X
*-EM3	.160[4.06]	.0980[2.489]	.088[2.24]	BTE-XXX-01-D-EM3	T-1S42-02-X

* = SEE NOTE 9

BTE-XXX-XX-X-D-EMX-XX

No OF POSITIONS
-020, -040, -060,
-080, -100, -120
(PER ROW)

OPTION
-GP: GUIDE POST (60 POS MAX)
(USE BTE-XXX-01-D-EM2-GP)
[SEE SHEET 2, FIG. 2-
AVAILABLE ONLY ON -EM2]

EDGE MOUNT THICKNESS
-EM2: .064[1.63] ±.004 PCB
(USE BTE-XXX-01-D-EM2 & T-1S42-01-X)
-EM3: (USE BTE-XXX-01-D-EM3 &
T-1S42-02-X) **SEE NOTE 9**

LEAD STYLE
-01 .160 [4.06]

ROW SPECIFICATION
-D: DOUBLE (USE BTE-XXX-01-D-EMX)

PLATING SPECIFICATION
-F: FLASH SELECTIVE GOLD WITH MATTE TIN TAILS
(USE T-1S42-XX-F) (SEE NOTE 7)
-L: LIGHT SELECTIVE GOLD WITH MATTE TIN TAILS
(USE T-1S42-XX-L)
-H: HEAVY GOLD (USE T-1S42-XX-H)







TABLE 2	
No OF POSITIONS	ASSEMBLY BOW
-020 THRU -060	.004 [.10]
-080 THRU -120	.005 [.13]

- NOTES:
1. Ⓢ REPRESENTS A CRITICAL DIMENSION.
 2. BURR ALLOWANCE: .0015 [.038] MAX.
 3. MINIMUM TERMINAL RETENTION: 6 OZ.
 4. PARTS TO BE MOLD-TO-POSITION.
 5. NOTE DELETED.
 6. BOARD THICKNESS TO BE MEASURED FROM SOLDER PAD TO SOLDER PAD.
 7. -L PLATING MAY BE SUBSTITUTED FOR -F PLATING.
 8. MAX VARIANCE: .002 [.05]
 9. -EM3 IS NOT A STANDARD OFFERING; AVAILABLE AS AN ASP ONLY. PLEASE CONTACT SAMTEC INTERCONNECT PROCESSING GROUP WITH ORDER INQUIRIES.
 10. NOTE DELETED.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. TOLERANCES ARE:

DECIMALS	ANGLES
.XX: ±.01 [.3]	2°
.XXX: ±.005 [.13]	
.XXXX: ±.0020 [.051]	

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.

samtec

520 PARK EAST BLVD. NEW ALBANY, IN 47150
PHONE: 812-944-6733 FAX: 812-948-5047
e-Mail: info@SAMTEC.com code: 55322

MATERIAL: DO NOT SCALE DRAWING SHEET SCALE: 1:625:1

INSULATOR: BLACK LCP
TERMINAL: PHOS BRONZE

DESCRIPTION: .8mm TERMINAL ASSEMBLY, EDGEMOUNT

DWG. NO. BTE-XXX-XX-X-D-EMX-XX

BY: KEVIN B 2/18/00 SHEET 1 OF 2








FIG 2
 -GP OPTION (60 POS MAX)
 BTE-060-01-X-D-EM2-GP SHOWN
 [DIFFERENT AS SHOWN, OTHERWISE SAME AS FIG 1]




SECTION "B"- "B"




SECTION "C"- "C"

PACKAGING VIEW
 [PARTS TO HAVE POSITION #1 LOADED IN
 SAME DIRECTION AS ARROW ON TUBE]



-EM2

TUBE: PT-1-24-01-95
 PLUG: TP-03



-EM2-GP

TUBE: PT-1-24-02-09
 PLUG: TP-07

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION
 CONFIDENTIAL AND PROPRIETARY TO
 SAMTEC, INC. AND SHALL NOT BE REPRODUCED
 OR TRANSFERRED TO OTHER DOCUMENTS OR
 DISCLOSED TO OTHERS OR USED FOR ANY
 PURPOSE OTHER THAN THAT WHICH IT WAS
 OBTAINED WITHOUT THE EXPRESSED WRITTEN
 CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING

SHEET SCALE: 1.625:1

samtec

520 PARK EAST BLVD, NEW ALBANY, IN 47150
 PHONE: 812-944-6733 FAX: 812-948-5047
 e-Mail: info@SAMTEC.com code: 55322

DESCRIPTION:
 .8mm TERMINAL ASSEMBLY, EDGEMOUNT

DWG. NO. **BTE-XXX-XX-X-D-EMX-XX**

BY: KEVIN B 2/18/00 SHEET 2 OF 2