

4-2 Fast Recovery Diodes

●Thru-Hole

V _{RM} (V)	I _F (A) (A) Values in parentheses are for the products with heatsinks	Package Axial (Body Diameter/Lead Diameter)	Part Number	I _{FSM} (A)	T _j (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (μA)	T _j (°C)	trr ⁽¹⁾ (μs)	I _F /I _{RP} (mA)	trr ⁽²⁾ (μs)	I _F /I _{RP} (mA)	R _{th} (j-l) R _{th} (j-c) (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max							
200	0.5	Axial(φ2.7/φ0.6)	EU01Z	15	-40 to +150		1.0	0.5	10	150	100(Ta)	0.4	10/10	0.18	10/20	20	0.2
	0.5	Axial(φ2.7/φ0.78)	EU 1Z	15	-40 to +150		1.0	0.5	10	150	100(Ta)	0.4	10/10	0.18	10/20	17	0.3
	0.5	Axial(φ2.4/φ0.6)	AU01Z	15	-40 to +150		1.7	0.5	10	150	100(Ta)	0.4	10/10	0.18	10/20	22	0.13
	0.6	Axial(φ4.0/φ0.78)	RH 1Z	35	-40 to +150		1.3	0.6	5.0	70	150(Ta)	4.0	10/10	1.3	10/20	15	0.4
	0.7	Axial(φ2.7/φ0.78)	ES 1Z	30	-40 to +150		2.5	0.8	10	200	100(Ta)	1.5	10/10	0.6	10/20	17	0.3
	0.8	Axial(φ2.4/φ0.6)	AU02Z	25	-40 to +150		1.3	0.8	10	250	100	0.4	10/10	0.18	10/20	22	0.13
	1.0	Axial(φ2.7/φ0.6)	EU02Z	15	-40 to +150		1.4	1.0	10	300	100	0.4	10/10	0.18	10/20	20	0.2
	1.0	Axial(φ2.7/φ0.78)	EU 2Z	15	-40 to +150		1.4	1.0	10	3000	150	0.4	10/10	0.18	10/20	17	0.3
	1.0	Axial(φ4.0/φ0.78)	RU 2Z	20	-40 to +150		1.5	1.0	10	300	100(Ta)	0.4	10/10	0.18	10/20	15	0.4
	3.5	Axial(φ6.5/φ1.4)	RU 4Z	70	-40 to +150		1.3	3.5	10	300	100	0.4	10/10	0.18	10/20	8.0	1.2
	5.0	TO-220F(Center-tap)	FMU-12S, R	30	-40 to +150		1.5	2.5	50	500	100(Ta)	0.4	100/100	0.18	100/200	4.0	2.1
	10	TO-220F(Center-tap)	FMU-22S, R	40	-40 to +150		1.5	5.0	50	3000	150	0.4	100/100	0.18	100/200	4.0	2.1
400	0.25	Axial(φ2.7/φ0.6)	EU01	15	-40 to +150		2.5	0.25	10	150	100(Ta)	0.4	10/10	0.18	10/20	20	0.2
	0.25	Axial(φ2.7/φ0.78)	EU 1	15	-40 to +150		2.5	0.25	10	150	100(Ta)	0.4	10/10	0.18	10/20	17	0.3
	0.25	Axial(φ4.0/φ0.78)	RU 1	15	-40 to +150		2.5	0.25	10	200	100(Ta)	0.4	10/10	0.18	10/20	15	0.4
	0.5	Axial(φ2.4/φ0.6)	AU01	15	-40 to +150		1.7	0.5	10	150	100(Ta)	0.4	10/10	0.18	10/20	22	0.13
	0.6	Axial(φ2.4/φ0.6)	AS01	20	-40 to +150		1.5	0.6	10	50	100	1.5	10/10	0.6	10/20	22	0.13
	0.6	Axial(φ2.7/φ0.78)	EH 1	30	-40 to +150		1.35	0.6	10	200	100(Ta)	4.0	10/10	1.3	10/20	17	0.3
	0.7	Axial(φ2.7/φ0.78)	ES 1	30	-40 to +150		2.5	0.8	10	200	100(Ta)	1.5	10/10	0.6	10/20	20	0.2
	0.8	Axial(φ2.4/φ0.6)	AU02	25	-40 to +150		1.3	0.8	10	250	100	0.4	10/10	0.18	10/20	22	0.13
	1.0	Axial(φ2.7/φ0.6)	EU02	15	-40 to +150		1.4	1.0	10	300	100	0.4	10/10	0.18	10/20	20	0.2
	1.0	Axial(φ2.7/φ0.78)	EU 2	15	-40 to +150		1.4	1.0	10	300	100	0.4	10/10	0.18	10/20	17	0.3
	1.1	Axial(φ4.0/φ0.78)	RU 2M	20	-40 to +150		1.2	1.1	10	300	100	0.4	10/10	0.18	10/20	15	0.4
	1.5	Axial(φ4.0/φ0.98)	RU 3	20	-40 to +150		1.5	1.5	10	400	100	0.4	10/10	0.18	10/20	12	0.6
	1.5	Axial(φ4.0/φ0.98)	RU 3M	50	-40 to +150		1.1	1.5	10	350	100	0.4	10/10	0.18	10/20	12	0.6
	1.5(3.0)	Axial(φ6.5/φ1.4)	RU 4	50	-40 to +150		1.5	3.0	10	300	100(Ta)	0.4	10/10	0.18	10/20	8.0	1.2
	2.0(3.5)	Axial(φ6.5/φ1.4)	RU 4M	70	-40 to +150		1.3	3.5	10	300	100	0.4	100/100	0.18	100/200	8.0	1.2
	5.0	TO-220F(Center-tap)	FMU-14S, R	30	-40 to +150		1.5	2.5	50	500	100(Ta)	0.4	100/100	0.18	100/200	4.0	2.1
	10	TO-220F(Center-tap)	FMU-24S, R	40	-40 to +150		1.5	5.0	50	3000	150	0.4	100/100	0.18	100/200	4.0	2.1
	600	0.25	Axial(φ4.0/φ0.78)	RU 1A	15	-40 to +150		2.5	0.25	10	150	100	0.4	10/10	0.18	10/20	15
0.5		Axial(φ2.4/φ0.6)	AU01A	15	-40 to +150		1.7	0.5	10	150	100(Ta)	0.4	10/10	0.18	10/20	22	0.13
0.6		Axial(φ4.0/φ0.78)	RF 1A	15	-40 to +150		2.0	0.6	10	200	100(Ta)	0.4	10/10	0.18	10/20	15	0.4
0.6		Axial(φ2.4/φ0.6)	AS01A	20	-40 to +150		1.5	0.6	10	50	100	1.5	10/10	0.6	10/20	22	0.13
0.6		Axial(φ4.0/φ0.78)	RH 1A	35	-40 to +150		1.3	0.6	5.0	70	150(Ta)	4.0	10/10	1.3	10/20	15	0.4
0.7		Axial(φ2.7/φ0.6)	ES01A	20	-40 to +150		3.0	0.8	10	200	100(Ta)	1.5	10/10	0.6	10/20	20	0.2
0.7		Axial(φ4.0/φ0.78)	RS 1A	30	-40 to +150		2.5	0.8	10	2000	150	1.5	10/10	0.6	10/20	15	0.4
0.8		Axial(φ2.4/φ0.6)	AU02A	25	-40 to +150		1.3	0.8	10	250	100(Ta)	0.4	10/10	0.18	10/20	22	0.13
1.0		Axial(φ2.7/φ0.6)	EU02A	15	-40 to +150		1.4	1.0	10	300	100	0.4	10/10	0.18	10/20	20	0.2
1.0		Axial(φ2.7/φ0.78)	EU 2A	15	-40 to +150		1.4	1.0	10	300	100(Ta)	0.4	10/10	0.18	10/20	17	0.3
1.0		Axial(φ4.0/φ0.78)	RU 2	20	-40 to +150		1.5	1.0	10	300	100(Ta)	0.4	10/10	0.18	10/20	15	0.4
1.1		Axial(φ4.0/φ0.78)	RU 2AM	20	-40 to +150		1.2	1.1	10	300	100	0.4	10/10	0.18	10/20	15	0.4
1.5		Axial(φ4.0/φ0.98)	RU 3A	20	-40 to +150		1.5	1.5	10	400	100	0.4	10/10	0.18	10/20	12	0.6
1.5		Axial(φ4.0/φ0.78)	RU 20A	50	-40 to +150		1.1	1.5	10	350	100	0.4	10/10	0.18	10/20	15	0.4
1.5		Axial(φ4.0/φ0.98)	RU 3AM	50	-40 to +150		1.1	1.5	10	350	100	0.4	10/10	0.18	10/20	12	0.6
1.5(3.0)		Axial(φ6.5/φ1.4)	RU 4A	50	-40 to +150		1.5	3.0	10	300	100(Ta)	0.4	10/10	0.18	10/20	8	1.2
3.0		Axial(φ4.0/φ0.98)	RY2A	50	-40 to +150		1.15	3.0	10	1000	150	0.2	100/100	0.1	100/200	12	0.6
3.0		TO-220F2Pin	FMY-1036S	50	-40 to +150		1.15	3	10	1000	150	0.2	100/100	0.1	100/200	4.0	2.1
5.0		TO-220F2Pin	FMU-G16S	30	-40 to +150		1.25	5.0	50	500	100(Ta)	0.4	100/100	0.18	100/200	4.0	2.1
5.0		TO-220F(Center-tap)	FMU-16S, R	30	-40 to +150		1.5	2.5	50	500	100(Ta)	0.4	100/100	0.18	100/200	4.0	2.1
10		TO-220F(Center-tap)	FMU-26S, R	40	-40 to +150		1.5	5.0	50	3000	150	0.4	100/100	0.18	100/200	4.0	2.1
10		TO-220F2Pin	FMU-G26S	40	-40 to +150		1.35	10	50	500	150	0.4	100/100	0.18	100/200	4.0	2.1
10		TO-220F2Pin	FMY-1106S	180	-40 to +150		1.15	10	30	3000	150	0.2	100/100	0.1	100/200	4.0	2.1
20		TO-220F(Center-tap)	FMY-2206S*	180	-40 to +150		1.15	10	30	3000	150	0.2	100/100	0.1	100/200	4.0	2.1

*Under development