

MCX Bulkhead Straight Jack



Specifications:

Connector Type	: MCX Coaxial
Body Style	: Straight Bulkhead Jack
Coaxial Type	: RG178, RG196
Mounting Type	: Cable

Electrical Characteristics:

Frequency Range	: DC-6GHz
Nominal Impedance	: 50Ω
Maximum Working Voltage	: 170V
Proof Voltage	: 500V
Maximum VSWR	: 1.22 at 1GHz : 1.35 at 3GHz
Contact Resistance	: 1mΩ
Insulation Resistance	: 1,000MΩ
Withstand Voltage	: 1,000V

Materials:

Bodies	: Brass per JIS-C3604
Centre Contact	: Beryllium copper per ASTM B196 UNS C17300
Insulation	: PTFE per ASTM D1457 and ASTM D1710
Crimp Ferrule	: Brass per JIS-C2700

Mechanical Characteristics:

Interface in accordance with CECC 22220


For use with RG402 or similar style cable

Cable Attachment	: Outer	: Crimp
	: Inner	: Solder
Minimum Cable Retention	: 6lbs	
Crimp Size Required	: Contact	: Solder
	: Ferrule	: 2.8 (0.11) hexagon crimp tool

Environmental Characteristic:

Operating Temperature Range	: -55°C to +155°C
-----------------------------	-------------------

MCX Bulkhead Straight Jack



Dimensions : Millimetres (Inches)

Mounting Hole

Stripping Dimension

Number	Description	Material	Finish
1	Nut	Brass	Gold
2	Washer		
3	Body		Gold 3µ" Min.
4	Insulation	PTFE	None
5	Chassis	Brass	Gold 3µ" Min.
6	Centre Contact	Beryllium Copper	Gold 30µ" Min.
7	Crimp Ferrule	Brass	Gold

Part Number Table

Description	Part Number
Jack MCX, Bulkhead, Straight, Crimp	27-10M TGG

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com

