

Discrete Relays

910597

When good enough just isn't good enough

Weidmüller **RSRM 4, Combi-foot, TS 35/32**[Email to a Friend](#)[View Line Drawing](#)

Representative Photo

Technical Information

Rail Type	Combi Foot
Input Voltage	120 VAC
Module Type	Open Pluggable
Number of Channels	4
Contact Current/Resistive Load (continuous in Amps)	10 A
Relay Contact Type	SPDT Changeover Form C
LED Color	Red
Plug-In Relay Type	IDEC RH1B or Eagle Signal 1601C
Housing Type	RSRM 4

Additional Data

Input Current	7.5 mA
Coil Resistance	7680 ohms
Drop OFF (Voltage/Current)	4.6 mA
Operative Time ON	20 ms
Operative Time OFF	20 ms
Status Indicator (LED)	Red
Voltage Output	240 VAC / 30 VDC
Continuous Current Rating for Inductive Loads	7.0 A at 30 VDC or 240 VAC
Continuous Current for Resistive Loads	10 A at 30 VDC or 240 VAC
Contact Arrangement (Style)	SPDT
Contact Material	Silver cadmium (AgCdO)
Mechanical Operations	5x10 ⁷
Electrical Operations	5x10 ⁵
Storage Temperature Range	-40°C...+60°C
Operating Temperature Range	-25°C...+40°C
Wire Size	#22...14 AWG 0.5...2.5 mm ²
Clamp Screw Tightening Torque Nm (lb.in.)	0.4 (3.50)

Mechanical Dimensions (WxLxH) mm (in.)	75/70.3/73.7 (2.95"/2.77"/2.90")
Insulation Stripping Length mm (in.)	7 (.28")
Certifications	UL

Suggested Accessories

DIN-rail

End bracket

Ferrules

Markers (SchT)

Marking pens

Marking tags (DEK)

Mounting brackets

Replacement relay

Tools

Product Liability The above information describes our products. It does not constitute guaranteed properties and is not intended to affirm the suitability of a product for a particular application. Regrettably, omissions and exceptions cannot be completely ruled out. Technical data are always specified by their average values. Exact data and the tolerances which apply to our processes can be requested from:

Weidmüller - North America
United States 001 (800) 849-9343
Canada 001 (800) 268-4080

or

Weidmüller - Germany
Telephone operator 0049 (-5252) 960-0