



# **SPECIFICATIONS**

	GRADE	
SILIKROME®	COMMERCIAL	MILITARY
Material	Silicone Rubber ASTM D 1418	Silicone Rubber conforming to ZZ-R-765 Class II GR 50
Temperature Range	-112°F to +400°F (-80°C to +204°C)	-160°F to +450°F (-106°C to +260°C)
	-112°F to +575°F (-80°C to +302°C)	
Shelf Life	25 Years (minimum)	
Resistant to	Salt spray, sunlight, ozone, cleaning solutions, and most acids	
Physical Characteristics	Flexible, non-breakable, re-usable. Acts as shock mount. Protects against shattering. Easy to mount.	



**SECTION AA**

B	REDRAWN and MAT'L CHANGED		S. GOK	05.28.09
A	CAD COMPUTER GENERATED			01.10.03
REV.	DESCRIPTION		DATE	
MAXIMUM AND MINIMUM MEASUREMENTS ARE STATED DIRECTLY ON EACH DIMENSION. MAT'L: SEE ABOVE	TITLE:	SILIKROMES® COLORED	ENG. S. GOK	05.28.09
		FILTERS FOR INCANDESCENT	DWN. N.K. STEIGER	02.18.66
		G-3 1/2 LAMPS	CHKD. J. CELLA	05.28.09
COLOR: SPECIFY	APM-HEXSEAL CORPORATION		SCALE 4 : 1	DWG. NO. 1813/26

THIS DRAWING COVERS PROPRIETARY ITEM AND IS THE PROPERTY OF THE APM-HEXSEAL CORPORATION.  
THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE WRITTEN APPROVAL OF AN OFFICER OF THE APM-HEXSEAL CORPORATION.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## APM HEXSEAL:

[1813/26](#) [1813/26 A2 C](#) [1813/26 B1 C](#) [1813/26 G1 C](#) [1813/26 LW1 C](#) [1813/26 R2 C](#) [1813/26 Y1 C](#)