



SURFACE MOUNT SCHOTTKY DIODE

This device is an extremely fast Schottky diode housed in the ultra-small SOD-523 package. Ideal for applications where board space is at a

FEATURES

- Extremely low V_f
- Low capacitance for reduced insertion losses
- Reverse voltage rating of 30V
- Also available in lead-free plating (100% matte tin finish)

APPLICATIONS

- Mobile phones and accessories
- Hand-held computers
- High speed switching applications



Marking Code: 520

MAXIMUM RATINGS $T_J = 25^\circ\text{C}$ Unless otherwise noted

Rating	Symbol	Value	Units
Peak Reverse Voltage	V_{RM}	30	V
Continuous Reverse Voltage	V_R	30	V
Continuous Forward Current	I_F	200	mA
Non-repetitive Peak Forward Current, 60Hz Half Sine-Wave	I_{FSM}	1	A
Total Power Dissipation (Note 1)	P_{tot}	200	mW
Operating Junction Temperature Range	T_J	-55 to +125	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-55 to +150	$^\circ\text{C}$

Note 1. FR-5 Board 1.0 x 0.75 x 0.062 in.

THERMAL CHARACTERISTICS

Characteristic	Symbol	Value	Units
Thermal Resistance, Junction to Ambient	R_{thja}	500	$^\circ\text{C/W}$






ELECTRICAL CHARACTERISTICS

$T_J = 25^\circ\text{C}$ Unless otherwise noted

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Forward Voltage (Note 2)	V_F	$I_F = 200\text{mA}$	-	-	0.6	V
Reverse Leakage Current	I_R	$V_R = 10\text{V}$	-	-	1.0	μA
Junction Capacitance	C_D	0Vdc Bias, $f = 1\text{ MHz}$	-	21	30	pF


Note 2. Short duration pulse test to avoid self-heating effect

TYPICAL CHARACTERISTIC CURVES





PACKAGE LAYOUT AND SUGGESTED PAD DIMENSIONS



ORDERING INFORMATION

RB520S30 T/R7 - 7" reel, 3K units per reel

RB520S30 T/R13 - 13" reel, 10K units per reel

Copyright PanJit International, Inc 2005

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.