

## MM74HC132

### Quad 2-Input NAND Schmitt Trigger

#### General Description

The MM74HC132 utilizes advanced silicon-gate CMOS technology to achieve the low power dissipation and high noise immunity of standard CMOS, as well as the capability to drive 10 LS-TTL loads.

The 74HC logic family is functionally and pinout compatible with the standard 74LS logic family. All inputs are protected from damage due to static discharge by internal diode clamps to  $V_{CC}$  and ground.

#### Features


- Typical propagation delay: 12 ns
- Wide power supply range: 2V–6V
- Low quiescent current: 20  $\mu$ A maximum (74HC Series)
- Low input current: 1  $\mu$ A maximum
- Fanout of 10 LS-TTL loads
- Typical hysteresis voltage: 0.9V at  $V_{CC}=4.5V$

#### Ordering Code:


| Order Number | Package Number | Package Description                                                               |
|--------------|----------------|-----------------------------------------------------------------------------------|
| MM74HC132M   | M14A           | 14-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-120, 0.150" Narrow Body |
| MM74HC132SJ  | M14D           | 14-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide                     |
| MM74HC132MTC | MTC14          | 14-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide       |
| MM74HC132N   | N14A           | 14-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide            |

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code. (Tape and Reel not available in N14A.)

#### Connection Diagram



#### Logic Diagram



**Absolute Maximum Ratings**(Note 1)

(Note 2)

|                                                  |                       |
|--------------------------------------------------|-----------------------|
| Supply Voltage ( $V_{CC}$ )                      | -0.5 to +7.0V         |
| DC Input Voltage ( $V_{IN}$ )                    | -1.5 to $V_{CC}+1.5V$ |
| DC Output Voltage ( $V_{OUT}$ )                  | -0.5 to $V_{CC}+0.5V$ |
| Clamp Diode Current ( $I_{IK}, I_{OK}$ )         | $\pm 20$ mA           |
| DC Output Current, per pin ( $I_{OUT}$ )         | $\pm 25$ mA           |
| DC $V_{CC}$ or GND Current, per pin ( $I_{CC}$ ) | $\pm 50$ mA           |
| Storage Temperature Range ( $T_{STG}$ )          | -65°C to +150°C       |
| Power Dissipation ( $P_D$ )                      |                       |
| (Note 3)                                         | 600 mW                |
| S.O. Package only                                | 500 mW                |

Lead Temperature ( $T_L$ )

(Soldering 10 seconds)

260°C

**Recommended Operating Conditions**

|                                                  | Min | Max      | Units |
|--------------------------------------------------|-----|----------|-------|
| Supply Voltage ( $V_{CC}$ )                      | 2   | 6        | V     |
| DC Input or Output Voltage ( $V_{IN}, V_{OUT}$ ) | 0   | $V_{CC}$ | V     |
| Operating Temperature Range ( $T_A$ )            | -40 | +125     | °C    |

**Note 1:** Absolute Maximum Ratings are those values beyond which damage to the device may occur.**Note 2:** Unless otherwise specified all voltages are referenced to ground.**Note 3:** Power Dissipation temperature derating — plastic "N" package: —**DC Electrical Characteristics** (Note 4)

| Symbol          | Parameter                         | Conditions                                                                                                                                                                                                  | V <sub>CC</sub> | T <sub>A</sub> = 25°C |                   | T <sub>A</sub> = -40 to 85°C |      | T <sub>A</sub> = -40 to 125°C |   | Units |
|-----------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------------|-------------------|------------------------------|------|-------------------------------|---|-------|
|                 |                                   |                                                                                                                                                                                                             |                 | Typ                   | Guaranteed Limits |                              |      |                               |   |       |
| V <sub>T+</sub> | Positive Going Threshold Voltage  |                                                                                                                                                                                                             | Min             | 2.0V                  |                   | 1.0                          | 1.0  | 1.0                           | V |       |
|                 |                                   |                                                                                                                                                                                                             |                 | 4.5V                  |                   | 2.0                          | 2.0  | 2.0                           | V |       |
|                 |                                   |                                                                                                                                                                                                             |                 | 6.0V                  |                   | 3.0                          | 3.0  | 3.0                           | V |       |
|                 |                                   |                                                                                                                                                                                                             | Max             | 2.0V                  |                   | 1.5                          | 1.5  | 1.5                           | V |       |
|                 |                                   |                                                                                                                                                                                                             |                 | 4.5V                  |                   | 3.15                         | 3.15 | 3.15                          | V |       |
|                 |                                   |                                                                                                                                                                                                             |                 | 6.0V                  |                   | 4.2                          | 4.2  | 4.2                           | V |       |
| V <sub>T-</sub> | Negative Going Threshold Voltage  | Min                                                                                                                                                                                                         | 2.0V            |                       | 0.3               | 0.3                          | 0.3  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 4.5V            |                       | 0.9               | 0.9                          | 0.9  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 6.0V            |                       | 1.2               | 1.2                          | 1.2  | V                             |   |       |
|                 |                                   | Max                                                                                                                                                                                                         | 2.0V            |                       | 1.0               | 1.0                          | 1.0  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 4.5V            |                       | 2.2               | 2.2                          | 2.2  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 6.0V            |                       | 3.0               | 3.0                          | 3.0  | V                             |   |       |
| V <sub>H</sub>  | Hysteresis Voltage                | Min                                                                                                                                                                                                         | 2.0V            |                       | 0.2               | 0.2                          | 0.2  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 4.5V            |                       | 0.4               | 0.4                          | 0.4  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 6.0V            |                       | 0.5               | 0.5                          | 0.5  | V                             |   |       |
|                 |                                   | Max                                                                                                                                                                                                         | 2.0V            |                       | 1.0               | 1.0                          | 1.0  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 4.5V            |                       | 1.4               | 1.4                          | 1.4  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 6.0V            |                       | 1.5               | 1.5                          | 1.5  | V                             |   |       |
| V <sub>OH</sub> | Minimum HIGH Level Output Voltage | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br> I <sub>OUT</sub>   ≤ 20 μA<br>V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br> I <sub>OUT</sub>   ≤ 4.0 mA<br> I <sub>OUT</sub>   ≤ 5.2 mA | 2.0V            | 2.0                   | 1.9               | 1.9                          | 1.9  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 4.5V            | 4.5                   | 4.4               | 4.4                          | 4.4  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 6.0V            | 6.0                   | 5.9               | 5.9                          | 5.9  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 4.5V            | 4.2                   | 3.98              | 3.84                         | 3.7  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 6.0V            | 5.7                   | 5.48              | 5.34                         | 5.2  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 6.0V            | 5.7                   | 5.48              | 5.34                         | 5.2  | V                             |   |       |
| V <sub>OL</sub> | Maximum LOW Level Output Voltage  | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br> I <sub>OUT</sub>   ≤ 20 μA<br>V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br> I <sub>OUT</sub>   ≤ 4.0 mA<br> I <sub>OUT</sub>   ≤ 5.2 mA | 2.0V            | 0                     | 0.1               | 0.1                          | 0.1  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 4.5V            | 0                     | 0.1               | 0.1                          | 0.1  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 6.0V            | 0                     | 0.1               | 0.1                          | 0.1  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 4.5V            | 0.2                   | 0.26              | 0.33                         | 0.4  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 6.0V            | 0.2                   | 0.26              | 0.33                         | 0.4  | V                             |   |       |
|                 |                                   |                                                                                                                                                                                                             | 6.0V            | 0.2                   | 0.26              | 0.33                         | 0.4  | V                             |   |       |
| I <sub>IN</sub> | Maximum Input Current             | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                                                                                                                                    | 6.0V            |                       | ±0.1              | ±1.0                         | ±1.0 | μA                            |   |       |
| I <sub>CC</sub> | Maximum Quiescent Supply Current  | V <sub>IN</sub> = V <sub>CC</sub> or GND<br>I <sub>OUT</sub> = 0 μA                                                                                                                                         | 6.0V            |                       | 2.0               | 20                           | 40   | μA                            |   |       |

**Note 4:** For a power supply of 5V  $\pm 10\%$  the worst case output voltages ( $V_{OH}$  and  $V_{OL}$ ) occur for HC at 4.5V. Thus the 4.5V values should be used when designing with this supply. Worst case  $V_{IH}$  and  $V_{IL}$  occur at  $V_{CC} = 5.5V$  and 4.5V respectively. (The  $V_{IH}$  value at 5.5V is 3.85V.) The worst case leakage current ( $I_{IN}$ ,  $I_{CC}$ , and  $I_{OZ}$ ) occur for CMOS at the higher voltage and so the 6.0V values should be used.

# AC Electrical Characteristics

$V_{CC} = 5V$ ,  $T_A = 25^{\circ}C$ ,  $C_L = 15\text{ pF}$ ,  $t_r = t_f = 6\text{ ns}$

| Symbol                | Parameter                 | Conditions | Typ | Guaranteed Limit | Units |
|-----------------------|---------------------------|------------|-----|------------------|-------|
| $t_{PHL}$ , $t_{PLH}$ | Maximum Propagation Delay |            | 12  | 20               | ns    |


# AC Electrical Characteristics

$V_{CC} = 2.0V$  to  $6.0V$ ,  $C_L = 50\text{ pF}$ ,  $t_r = t_f = 6\text{ ns}$  (unless otherwise specified)


| Symbol                | Parameter                              | Conditions | $V_{CC}$ | $T_A = 25^{\circ}C$ |                   | $T_A = -40\text{ to }85^{\circ}C$ | $T_A = -55\text{ to }125^{\circ}C$ | Units |
|-----------------------|----------------------------------------|------------|----------|---------------------|-------------------|-----------------------------------|------------------------------------|-------|
|                       |                                        |            |          | Typ                 | Guaranteed Limits |                                   |                                    |       |
| $t_{PHL}$ , $t_{PLH}$ | Maximum Propagation Delay              |            | 2.0V     | 63                  | 125               | 158                               | 186                                | ns    |
|                       |                                        |            | 4.5V     | 13                  | 25                | 32                                | 37                                 | ns    |
|                       |                                        |            | 6.0V     | 11                  | 21                | 27                                | 32                                 | ns    |
| $t_{TLH}$ , $t_{THL}$ | Maximum Output Rise and Fall Time      |            | 2.0V     | 30                  | 75                | 95                                | 110                                | ns    |
|                       |                                        |            | 4.5V     | 8                   | 15                | 19                                | 22                                 | ns    |
|                       |                                        |            | 6.0V     | 7                   | 13                | 16                                | 19                                 | ns    |
| $C_{PD}$              | Power Dissipation Capacitance (Note 5) | (per gate) |          | 130                 |                   |                                   |                                    | pF    |
| $C_{IN}$              | Maximum Input Capacitance              |            |          |                     | 5                 | 10                                | 10                                 | pF    |

**Note 5:**  $C_{PD}$  determines the no load dynamic power consumption,  $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$ , and the no load dynamic current consumption,  $I_S = C_{PD} V_{CC} f + I_{CC}$ .

# Physical Dimensions inches (millimeters) unless otherwise noted



14-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-120, 0.150" Narrow Body  
Package Number M14A



14-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide  
Package Number M14D

14 8

5.0 ± 0.1  
-A-

0.43 TYP

6.4

3.2





4.4 ± 0.1  
-B-

1 7

0.2 C B A

ALL LEAD TIPS

PIN #1 IDENT.




A. CONFORMS TO JEDEC REGISTRATION MO-153 VARIATION AB,  
REF NOTE 6, DATED 7/93

B. DIMENSIONS ARE IN MILLIMETERS

C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH,  
AND TIE BAR EXTRUSIONS

**14-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide  
Package Number MTC14**

## Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



N14A (REV F)

### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.