

MNLM2940-5.0-X REV 1A1

 Original Creation Date: 07/22/96
 Last Update Date: 10/08/99
 Last Major Revision Date: 09/01/99

1A LOW DROPOUT REGULATOR
General Description

The LM2940 positive voltage regulator features the ability to source 1A of output current with a dropout voltage of typically 0.5V and a maximum of 1V over the entire temperature range. Furthermore, a quiescent current reduction circuit has been included which reduces the ground current when the differential between the input voltage and the output voltage exceeds approximately 3V. The quiescent current with 1A of output current and an input-output differential of 5V is therefore only 30 mA. Higher quiescent currents only exist when the regulator is in the dropout mode ($V_{in} - V_{out} \leq 3V$).

Designed also for vehicular applications, the LM2940 and all regulated circuitry are protected from reverse battery installations or 2-battery jumps. During line transients, such as load dump when the input voltage can momentarily exceed the specified maximum operating voltage, the regulator will automatically shut down to protect both the internal circuits and the load. The LM2940 cannot be harmed by temporary mirror-image insertion. Familiar regulator features such as short circuit and thermal overload protection are also provided.

Industry Part Number

LM2940

NS Part Numbers

 LM2940J-5.0/883
 LM2940K-5.0/883
 LM2940WG-5.0/883

Prime Die

LM2940

Controlling Document

SEE FEATURES SECTION

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883, Method 5005

Subgrp	Description	Temp (°C)
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

Features

- Dropout voltage typically 0.5V @ $I_o = 1A$
- Output current in excess of 1A
- Output voltage trimmed before assembly
- Reverse battery protection
- Internal short circuit current limit
- Mirror image insertion protection
- CONTROLLING DOCUMENT

LM2940J-5.0/883	5962-8958701EA
LM2940K-5.0/883	5962-8958701YA
LM2940WG5.0/883	5962-8958701XA

(Absolute Maximum Ratings)

(Note 1)

Input Voltage (Survival Voltage $\leq 100\text{ms}$)	60V
Internal Power Dissipation (Note 2, 3)	Internally Limited
Maximum Junction Temperature	150 C
Storage Temperature Range	-65 C to +150 C
Lead Temperature (Soldering, 10 seconds)	300 C
Thermal Resistance	
ThetaJA	
T03 Pkg (Still Air)	40 C/W
T03 Pkg (500LF/Min Air Flow)	TBD
CERDIP (Still Air)	73 C/W
CERDIP (500LF/Min Air Flow)	37 C/W
CERAMIC SOIC (Still Air)	122 C/W
CERAMIC SOIC (500LF/Min Air Flow)	77 C/W
ThetaJC	
T03	5 C/W
CERDIP	3 C/W
(Note 3)	
CERAMIC SOIC	5 C/W
(Note 3)	
Package Weight	
T03 Pkg	TBD
CERDIP	1970mg
CERAMIC SOIC	360mg
ESD Susceptibility (Note 4)	4000V

Note 1: Absolute Maximum Ratings are limits beyond which damage to the device may occur. Operating Ratings are conditions for which the device is functional, but do not guarantee specific performance limits. For guaranteed specifications and test conditions see the Electrical Characteristics. The guaranteed specification apply only for the test conditions listed. Some performance characteristics may degrade when the device is not operated under the listed test conditions.

Note 2: The maximum power dissipation must be derated at elevated temperatures and is dictated by T_{jmax} (maximum junction temperature), Θ_{JA} (package junction to ambient thermal resistance), and T_A (ambient temperature). The maximum allowable power dissipation at any temperature is $P_{dmax} = (T_{jmax} - T_A)/\Theta_{JA}$ or the number given in the Absolute Maximum Ratings, whichever is lower.

Note 3: The package material for these devices allows much improved heat transfer over our standard ceramic packages. In order to take full advantage of this improved heat transfer, heat sinking must be provided between the package base (directly beneath the die), and either metal traces on, or thermal vias through, the printed circuit board. Without this additional heat sinking, device power dissipation must be calculated using junction-to-ambient, rather than junction-to-case, thermal resistance. It must not be assumed that the device leads will provide substantial heat transfer out of the package, since the thermal resistance of the leadframe material is very poor, relative to the material of the package base. The stated junction-to-case thermal resistance is for the package material only, and does not account for the additional thermal resistance between the package base and the printed circuit board. The user must determine the value of the additional thermal resistance and must combine this with the stated value for the package, to calculate the total allowed power dissipation for the device.

Note 4: Human body model, 100pF discharged through 1.5K Ohms

Recommended Operating Conditions

(Note 1)

Input Voltage

26V

Operating Temperature Range

$-55\text{ }^{\circ}\text{C} \leq T_A \leq +125\text{ }^{\circ}\text{C}$

Note 1: Absolute Maximum Ratings are limits beyond which damage to the device may occur. Operating Ratings are conditions for which the device is functional, but do not guarantee specific performance limits. For guaranteed specifications and test conditions see the Electrical Characteristics. The guaranteed specifications apply only for the test conditions listed. Some performance characteristics may degrade when the device is not operated under the listed test conditions.

Electrical Characteristics

DC PARAMETERS:

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: $V_{in} = 10V$, $I_o = 1A$, $C_{out} = 22\mu F$

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
Vout	Output Voltage	$V_{in} = 10V$, $I_o = 5mA$			4.85	5.15	V	1
					4.75	5.25	V	2, 3
		$V_{in} = 6V$, $I_o = 5mA$			4.85	5.15	V	1
					4.75	5.25	V	2, 3
		$V_{in} = 7V$, $I_o = 5mA$			4.85	5.15	V	1
					4.75	5.25	V	2, 3
		$V_{in} = 26V$, $I_o = 5mA$			4.85	5.15	V	1
					4.75	5.25	V	2, 3
		$V_{in} = 10V$, $I_o = 1A$			4.85	5.15	V	1
					4.75	5.25	V	2, 3
		$V_{in} = 6V$, $I_o = 1A$			4.85	5.15	V	1
					4.75	5.25	V	2, 3
		$V_{in} = 6V$, $I_o = 50mA$			4.85	5.15	V	1
					4.75	5.25	V	2, 3
		$V_{in} = 10V$, $I_o = 50mA$			4.85	5.15	V	1
					4.75	5.25	V	2, 3
	Reverse Polarity Input Voltage DC	$R_o = 100\ \Omega$	1		-15		V	1, 2, 3
Iq	Quiescent Current	$V_{in} = 10V$, $I_o = 5mA$			0	15	mA	1
					0	20	mA	2, 3
		$V_{in} = 7V$, $I_o = 5mA$			0	15	mA	1
					0	20	mA	2, 3
		$V_{in} = 26V$, $I_o = 5mA$			0	15	mA	1
					0	20	mA	2, 3
Vrline	Line Regulation	$7V \leq V_{in} \leq 26V$, $I_o = 5mA$			-40	40	mV	1
					-50	50	mV	2, 3
Vrload	Load Regulation	$V_{in} = 10V$, $50mA \leq I_o \leq 1A$			-50	50	mV	1
					-100	100	mV	2, 3

Electrical Characteristics

DC PARAMETERS: (Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: $V_{in} = 10V$, $I_o = 1A$, $C_{out} = 22\mu F$

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
V _{do}	Dropout Voltage	$I_o = 1A$			0	0.7	V	1
					0	1	V	2, 3
		$I_o = 100mA$			0	200	mV	1
					0	300	mV	2, 3
I _{sc}	Short Circuit Current	$V_{in} = 10V$			1.5		A	1
					1.3		A	2, 3

AC PARAMETERS:

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: $V_{in} = 10V$, $I_o = 1A$, $C_{out} = 22\mu F$

	Max Line Transient	$V_o \leq 6V$, $R_o = 100 \text{ Ohms}$, $T = 20ms$	1		40		V	7, 8A, 8B
	Reverse Polarity Input Voltage Transient	$T = 20ms$, $R_o = 100 \text{ Ohms}$	1		-45		V	7, 8A, 8B
RR	Ripple Rejection	$V_{in} = 10V$, $1V_{rms}$, $f = 1KHz$, $I_o = 5mA$	1		60		dB	4
			1		50		dB	5, 6
No	Output Noise Voltage	$V_{in} = 10V$, $I_o = 5mA$, $10Hz = 100KHz$	1		0	700	μV_{rms}	4, 5, 6
Z _o	Output Impedance	$V_{in} = 10V$, $I_o = 100mA$ DC and $20mA$ AC, $f_o = 120Hz$	1			1	Ohm	4, 5, 6


Note 1: Functional test only.

Graphics and Diagrams

GRAPHICS#	DESCRIPTION
05826HRA2	METAL CAN (KA), TO-3, 2LD, LOW PROFILE (B/I CKT)
06332HRA2	CERDIP (J), 16 LEAD (B/I CKT)
06351HRA1	CERPACK (W), 16 LEAD (B/I CKT)
J16ARL	CERDIP (J), 16 LEAD (P/P DWG)
K02CRE	METAL CAN (KA), TO-3, 2LD, LOW PROFILE (P/P DWG)
P000137A	METAL CAN (KA), TO-3, 2LD, LOW PROFILE (PINOUT)
P000159A	CERDIP (J), 16 LEAD (PINOUT)
P000386A	CERAMIC SOIC (WG), 16 LEAD (PINOUT)
WG16ARC	CERAMIC SOIC (WG), 16 LEAD (P/P DWG)

See attached graphics following this page.

R E V I S I O N S			
LTR	DESCRIPTION	E.C.N.	DATE
L	REVISE PER CURRENT STD; REDRAW	09996	09/15/93
			TL/




- NOTES: UNLESS OTHERWISE SPECIFIED
1. LEAD FINISH TO BE 200 MICRONS / 5.08 MICROMETERS MINIMUM SOLDER MEASURED AT THE CREST OF THE MAJOR FLATS.
 2. JEDEC REGISTRATION M0-036, VARIATION AD, DATED 04/1981.

MIL/AERO MIL-M-38510
CONFIGURATION CONTROL CONFIGURATION CONTROL

CONTROLLING DIMENSION: INCH			
APPROVALS	DATE	NATIONAL SEMICONDUCTOR CORPORATION	
DRAWN: LEQUANG	09/15/93	2900 Semiconductor Drive, Santa Clara, CA 95052-8090	
DFTG. CHK.			
ENGR. CHK.			
APPROVAL			
PROJECTION		SCALE	DRAWING NUMBER
		N/A	B
INCH [MM]		DO NOT SCALE	DRAWING
		SHEET	OF
		1	1


CERDIP (J),
16 LEAD



LM2940K-XX/883
2 - LEAD TO3
CONNECTION DIAGRAM
BOTTOM VIEW
P000137A



National Semiconductor™
MIL/AEROSPACE OPERATIONS
2900 SEMICONDUCTOR DRIVE
SANTA CLARA, CA 95050



LM2940J-XX

16 - LEAD DIP

CONNECTION DIAGRAM


TOP VIEW

P000159A



National Semiconductor™

MIL/AEROSPACE OPERATIONS
2900 SEMICONDUCTOR DRIVE
SANTA CLARA, CA 95050



LM2940WG
 16 - LEAD CERAMIC SOIC
 CONNECTION DIAGRAM
 TOP VIEW
 P000386A



National Semiconductor™

MIL/AEROSPACE OPERATIONS
 2900 SEMICONDUCTOR DRIVE
 SANTA CLARA, CA 95050

Revision History

Rev	ECN #	Rel Date	Originator	Changes
0A0	M0001534	12/15/98	Barbara Lopez	Initial Release of: MNLM2940-5.0-X Rev. 0A0. Added note for power dissipation and reference to thermal resistance for Aluminum Nitride package.
0B0	M0003110	02/03/99	Rose Malone	Update MDS: MNLM2940-5.0-X, Rev. 0A0 to MNLM2940-5.0-X, Rev. 0B0
0C1	M0003228	10/08/99	Rose Malone	Update MDS: MNLM2940-5.0-X, Rev. 0B0 to MNLM2940-5.0-X, Rev. 0C1.
1A1	M0003560	10/08/99	Rose Malone	Update MDS: MNLM2940-5.0-X, Rev. 0C1 to MNLM2940-5.0-X, Rev. 1A1. Updated Absolute Section Thermal Resistance temp. ThetaJa and ThetaJc to T03 package. Changed Vdo, Io = 100mA, Max. condition for subgroup 1 from 150mV to 200mV and subgroup 2 from 200mV to 300mV.