





TWO HOLE HYLUG™ CODE CONDUCTOR LONG BARREL (Continued)



Catalog Number	Fig #	Conductor		Stud Hole Size	Stud Hole Spacing	Tongue Width	Figure Dimensions			Dieless (# of crimps)	▲ Installation Tooling						Wire Strip Length													
		AWG	*** MM ²				Figure Dimensions				Mechanical MD6, OUR840, MD7-34R	Hydraulic		Color Code	Die Index															
							(B)	(T)	(L)			BCT500HS, Y500CTHS	Y35, Y39, Y750, Y46", PAT750																	
YA322TC38	1	400 kcmil	-	3/8"	1"	1.38"	2.12"	.19"	4.66"	Y644M (1)	W32VT (4)	W32VT (4) W32RT (4)	U32RT (4) U30RT (4)	Blue	19	2-3/16"														
YA322TC38-45	2																450 kcmil	-	1/2"	1-3/4"	1.48"	2.12"	.21"	5.93"	W33VT (4) W33RT (4)	U33RT	Gray	326	2-3/16"	
YA322TC38-90	3																													500 kcmil
YA332N	1	550 kcmil	-	1/2"	1-3/4"	1.65"	2.63"	.25"	6.06"		-	-	U35RT (4)	Yellow	21	2-11/16"														
YA332N-45	2																600 kcmil	300	1/2"	1-3/4"	1.69"	2.69"	.27"	6.49"	-	-	U36RT (4) U32ART (4)	Green	22	
YA332N-90	3																													650 kcmil
YA342N	1	700 kcmil	-	1/2"	1-3/4"	1.84"	2.81"	.27"	6.17"		-	-	U38RT (4)	Pink	400	2-7/8"														
YA342N-45	2																750 kcmil	-	1/2"	1-3/4"	1.89"	2.88"	.27"	6.29"	-	-	U39RT (4) P39RT (4) **	Black	24	
YA342N-90	3																													800 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"		-	-	-	Gold	26	3"														
YA342TC38-45	2																850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"															
YA342TC38-45	2															850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"															
YA342TC38-45	2															850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"															
YA342TC38-45	2															850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"															
YA342TC38-45	2															850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"															
YA342TC38-45	2															850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"															
YA342TC38-45	2															850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"															
YA342TC38-45	2															850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"	
YA342TC38-90	3																													850 kcmil
YA342TC38	1	850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"	6.29"	-	-	-	Gold	26	3"															
YA342TC38-45	2															850 kcmil	-	1/2"	1-3/4"	2.01"	2.94"	.31"								

C-55

▲ See tooling section of this catalog for complete tool and die listings.

* Use PUADP-1 adaptor with "U" -dies in Y46 HYPRESS™.

** P-RT die sets for use in Y46 HYPRESS™ only, PUADP-1 adaptor not required.

*** The MM² conductor sizes listed are the recommendations for Class 2 conductor.

" Available undrilled. Add suffix "U" to catalog number (example: YA25U).

◆ For applications greater than 2000 Volts consult cable manufacturer for voltage stress relief instructions.