

2108 SERIES TOTALIZING COUNTER

- 8 Digit 7mm High LCD Display
- Replaceable Lithium Battery 8 Year Life
- Compact Size

24 x 48mm (.95" x 1.89") Front Panel 37.5mm (1.48") Depth



GENERAL FEATURES:

The 2108 Series is a totalizing counter housed in a DIN-sized (24 x 48mm) enclosure. The 2108 has an eight digit 7mm high LCD display. The count input (slow speed) and reset input can be by contact closure and by NPN open collector transistor. The high speed input (7 kHz max) requires a 4 to 30 VDC voltage pulse and is compatible with 2 and 3 wire DC proximity switches and encoders. The unit is powered by a 3 volt lithium battery with an eight year life. When changing the battery, the current count value is retained long enough to allow battery replacement without losing the count value. The unit can be set remotely or from the front panel. The front panel reset can be enabled or disabled with jumpering of terminals on back of unit.

SPECIFICATIONS:

Power Lithium battery, 8 year life
Count Inputs . . . Contact Closure (slow speed)
NPN open collector (slow speed)

Voltage input (high speed)

Voltage input (high speed)

 Low Speed
 40 Hz

 Minimum Pulse
 12 ms

 Current Consumption
 52 μA max.

 Leakage Current
 0.2 μA max.

 Residual Voltage
 0.4 V max.

 High Speed
 7 kHz max.

 1 State
 4 to 30 VDC

 0 State
 0 to 1 VDC

 Absorbed current
 6 mA at 24 VDC

 Reset Remote
 Contact Closure

NPN open collector

12 ms min.

Reset Pushbutton Activate with jumper across

terminals 2 & 4

Memory Yes, 1 lithium battery - 8 year life

Protection Front Panel IP64
Terminal IP20

Corow torminals

Connections Screw terminals 2 x 1.5mm² capacity

 Operating temperature
 +32 to 131°F (0 to +55°C)

 Storage temperature
 -13° to 158°F (-25°C to 70°C)

Weight 2.1 oz. (60g)

CONFORMITY:

Electromagnetic environment

Radiated field IEC 1000-4-3, level 3, 10 V/M, 26 MHz to 1 GHz

Fast transients IEC 1000-4-4, level 3, 1 KV Damped oscillatory wave Electrostatic discharge IEC 1000-4-2, level 3, 8 KV

ORDERING INFORMATION:

87 610 340


Products and specifications subject to change without notice.


Consult factory for application assistance.


WIRING:

87 610 340


- 1- Reset Input
- 2- Front Panel Reset Enable
- 3- Low Speed Input
- 4- OV
- 5- High Speed Input












DIMENSIONS: (mm)



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Crouzet: 87610340