

Log on

Log on as distributor

Search product

SearchProducts

Navigation

Main page

Products

Sales outlets

Support

Publications

Jobs

About us

News

NEW MK193 LED CUBE

CubeAnimator software available for download here!!

Posted on 04-06-12

Read more...

New Ring scanners

Velleman invests again in its logistics system.

Posted on 14-05-12

Read more...

Glass Touch Panels

Glass Touch Panels with or without OLED. Coming soon.

Posted on 04-04-12

Read more...

New cable range

Discover our new audio, video & computer cables range!

Posted on 12-03-12

Read more...

PROLYTE Product news

Due to its recent increased raw material costs, Prolyte...

Posted on 19-07-11

Read more...

velleman

Vatican City State - English (UK)

Change

CD018

Support

InfoSheet

Support

DC PLUG 5.5x2.5MM MALE TO SCREW TERMINAL (5pcs)

Features

- male to fixed screw

Specifications

- max. voltage: 25V
- max. current: 4A
- max. operating temperature: 30°C

All registered trademarks and trade names are properties of their respective owners and are used only for the clarification of the compatibility of our products with the products of the different manufacturers.

Due to constant product improvements the actual product appearance might differ from the shown images. Product images are for illustrative purposes only.

REACH communication information according to article 33 WEEE

velleman.eu

hqpower.eu

perel.eu

vellemanprojects.com

888 - modules - instruments

velbus.eu

forum.velleman.eu

Advertisements

K8090 / VM8090

IPad/iPod/iPhone app

SAC1

SAC2

14

K8055(N) / VM1110(N)

Android Application

Set All Digital

Clear All Digital

A1

A2

K8055(N) / VM1110(N)

iPhone application

velleman projects

Subscribe to our NEWSLETTER

© 2012

All rights reserved

Sitemap

Disclaimer

FEED-Feeds

http://www.velleman.eu/products/view/?id=387134

8/30/2012