

Xtend-2/FL (MM)

10Base-2/10Base-FL Converter (Multi-Mode)

PART NUMBER	DESCRIPTION
ETP-20118	10Base-2/FL Multi-Mode Converter

Specifications

Interface:

BNC Connector for 10Base-2 Thin Ethernet connection
ST Connector for 10Base-FL Multi-Mode Fiber Optic Connection

Cable Type:

RG-58 Cable for 10Base-2 Thin Ethernet
62.5/125µm Multi-Mode Fiber Optic Cable for 10Base-FL

Distance:

185 meter max. for RG-58 cable
2,000 meter max. for fiber optic cable

Protocol:

Baseband

Standards:

IEEE 802.3 10Base-2 and 10Base-FL Ethernet

Connection Switch:

2-Position; 10Base-2 switch on BNC side
for Termination On/Off

LEDs:

LMON, COL, XMT, POWER, RCV, JAB, LINK

Temperature:

0° to 55°C (Standard Operating)

Humidity:

10 to 90% (Non-condensing)

Dimensions:

4.2"(L) x 2.2"(H) x 0.8"(D)

Power Adapter:

9V DC Input, 1A

EMI:

FCC Class A



908 Canada Court
City of Industry, CA 91748 U.S.A.
Phone: 626.964.7873 or 800.346.6668 **Fax:** 626.964.7880
www.unicomlink.com e-mail: info@unicomlink.com