UNCONTROLLED DOCUMENT

| PART NUMBER |
|------------------|
| SLX-LX5093UPGC/D |

REV.

| _ | | | | | |
|---|------|--------|------------------------------|------|-------|
| | REV. | E,C,N. | NUMBER AND REVISION COMMENTS | D/ | ATE |
| | Α | E,C,N. | #11152. | 7.1 | 4,04 |
| Г | В | E.C.N. | #11188. | 12.0 | 33.04 |

| - / | ø5.90 | [ø0.232] |
|-----|---------|----------|
| | - Ø5.00 | [ø0.197] |
| | | |



| | ELECTRO-OPTICAL CHARACTERISTICS TA=25°C | | | I _f =20mA | | |
|---|---|-------|-------------|----------------------|----------|-----------------------|
| | PARAMETER | MIN | TYP | MAX | UNITS | TEST COND |
| A | PEAK WAVELENGTH | | 525 (GREEN) | | nm | |
| | FORWARD VOLTAGE | | 3.5 | 4.0 | V_f | |
| | REVERSE VOLTAGE | 5.0 | | | ٧r | 1 _r =100µA |
| | AXIAL INTENSITY | | 8000 | | med | $I_f = 20 \text{mA}$ |
| | VIEWING ANGLE | | 20 | | 2x theta | |
| | EMITTED COLOR: | GREEN | | | | |
| | EPOXY LENS FINISH: | WATER | CLEAR | | | |

| 8.70 [0.343] | 1.00 [0.039] |
|-----------------------|----------------------|
| 24.00 [0.945] MIN. | 1.50 [0.059] TYP. |
| 1 | <u> </u> |

LIMITS OF SAFE OPERATION AT 25°C PER DIE

| PARAMETER | MAX | UNITS |
|--------------------------|--------------|------------|
| PEAK FORWARD CURRENT* | 100 | mA |
| STEADY CURRENT | 30 | mA |
| POWER DISSIPATION | 120 | mW |
| DERATE FROM 25°C | - 1.2 | mW/°C |
| OPERATING, STORAGE TEMP. | - 40 TO + 85 | .c |
| SOLDERING TEMP. | + 260 | .c |
| 2.0mm FROM BODY | | 3 SEG. MAX |

* t<10µS

CAUTION: STATIC SENSITIVE DEVICE FOLLOW PROPER E.S.D. HANDLING PROCEDURES WHEN WORKING WITH THIS PART.

UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +0.00 (±0.030). MIN

PART NUMBER

B SLX-LX5093UPGC/D

T-5mm (T-1 3/4) 525nm ULTRA PURE GREEN LED, WATER CLEAR LENS.

Confidential information

The information contained in this document is the property of lumex inc. except as specifically authorized in writing by Lumex inc., the holder of this document shall keep all information contained herein confidential and shall protect same in whole or in part from disolosure and dissemination to all third parties.

RELABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT

SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.
PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067—6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 12.03.02
PAGE: 1 OF 1
JD SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SLX-LX5093UPGC/D