

(3,96 mm) .156"

FWJ, HFWJ, JW SERIES

FWJ-08-01-T-S

FWJ-05-02-T-S-RA

POWER HEADERS & BOARD STACKERS

Mates with:
FHP

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?FWJ

FWJ

Insulator Material:
Black Glass Filled
Polyester

Terminal Material:
Phosphor Bronze

Plating:
Sn over 50µ" (1,27 µm) Ni

Operating Temp Range:
-55°C to +105°C

RoHS Compliant:
Yes

Lead-Free Solderable:
Wave only

HFWJ

For complete specifications and recommended PCB layouts see www.samtec.com?HFWJ

Same as FWJ except:
Insulator Material:
Natural Liquid Crystal
Polymer

Processing:

Lead-Free Solderable:
Yes

SMT Lead Coplanarity:
(0,20 mm) .008" max (02-16)
(0,25 mm) .010" max (17-24)



TYPE STRIP	NO. OF PINS	LEAD STYLE	PLATING OPTION	S	OTHER OPTION																																																														
FWJ = Standard Header	<table border="1"> <thead> <tr> <th colspan="3">CURRENT RATING (PER CONTACT)</th> </tr> <tr> <th>AMBIENT TEMP</th> <th>2 PINS</th> <th>4 PINS</th> </tr> </thead> <tbody> <tr> <td>20°C</td> <td>19.5A</td> <td>15.5A</td> </tr> <tr> <td>40°C</td> <td>17A</td> <td>14A</td> </tr> <tr> <td>60°C</td> <td>14A</td> <td>11.5A</td> </tr> <tr> <td>75°C</td> <td>11.2A</td> <td>9.2A</td> </tr> </tbody> </table>	CURRENT RATING (PER CONTACT)			AMBIENT TEMP	2 PINS	4 PINS	20°C	19.5A	15.5A	40°C	17A	14A	60°C	14A	11.5A	75°C	11.2A	9.2A	<table border="1"> <thead> <tr> <th>LEAD STYLE</th> <th>A</th> <th>B</th> <th>LEAD STYLE</th> <th>C</th> <th>LEAD STYLE</th> <th>D</th> <th>E</th> <th>F</th> </tr> </thead> <tbody> <tr> <td>-01</td> <td>(11,43) .450</td> <td>(4,45) .175</td> <td>-01</td> <td>(10,46) .412</td> <td>-02</td> <td>(4,45) .175</td> <td>(8,13) .320</td> <td>(2,54) .100</td> </tr> <tr> <td>-02</td> <td>(12,70) .500</td> <td>(3,96) .156</td> <td>-02</td> <td>(11,73) .462</td> <td>-02</td> <td>(3,96) .156</td> <td>(13,56) .534</td> <td>(4,95) .195</td> </tr> <tr> <td>-04</td> <td>(20,55) .809</td> <td>(12,07) .475</td> <td>-04</td> <td>(19,10) .752</td> <td>-04</td> <td>(19,10) .752</td> <td>(19,10) .752</td> <td>(19,10) .752</td> </tr> <tr> <td>-05</td> <td>(3,81) .150</td> <td>(12,07) .475</td> <td>-05</td> <td>(3,81) .150</td> <td>-05</td> <td>(3,81) .150</td> <td>(12,07) .475</td> <td>(12,07) .475</td> </tr> </tbody> </table>	LEAD STYLE	A	B	LEAD STYLE	C	LEAD STYLE	D	E	F	-01	(11,43) .450	(4,45) .175	-01	(10,46) .412	-02	(4,45) .175	(8,13) .320	(2,54) .100	-02	(12,70) .500	(3,96) .156	-02	(11,73) .462	-02	(3,96) .156	(13,56) .534	(4,95) .195	-04	(20,55) .809	(12,07) .475	-04	(19,10) .752	-04	(19,10) .752	(19,10) .752	(19,10) .752	-05	(3,81) .150	(12,07) .475	-05	(3,81) .150	-05	(3,81) .150	(12,07) .475	(12,07) .475	Specify LEAD STYLE from chart below.	Leave blank for Through-hole
CURRENT RATING (PER CONTACT)																																																																			
AMBIENT TEMP		2 PINS	4 PINS																																																																
20°C		19.5A	15.5A																																																																
40°C	17A	14A																																																																	
60°C	14A	11.5A																																																																	
75°C	11.2A	9.2A																																																																	
LEAD STYLE	A	B	LEAD STYLE	C	LEAD STYLE	D	E	F																																																											
-01	(11,43) .450	(4,45) .175	-01	(10,46) .412	-02	(4,45) .175	(8,13) .320	(2,54) .100																																																											
-02	(12,70) .500	(3,96) .156	-02	(11,73) .462	-02	(3,96) .156	(13,56) .534	(4,95) .195																																																											
-04	(20,55) .809	(12,07) .475	-04	(19,10) .752	-04	(19,10) .752	(19,10) .752	(19,10) .752																																																											
-05	(3,81) .150	(12,07) .475	-05	(3,81) .150	-05	(3,81) .150	(12,07) .475	(12,07) .475																																																											
HFWJ = High Temp Header	-T = Matte Tin	-RA = Right Angle (Style -02 & -04 only)	-VS = Surface Mount Requires HFWJ (2 pins/row minimum) Style -05 not available.	-P = Pick & Place Pad (3 Pos. min.) (6,98 mm) .275" min. post height (-VS only)																																																															

Note: Some lengths, styles and options are non-standard, non-returnable.

01 thru 24

*FWJ Only

Mates with:
FHP

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?JW

Insulator Material:
Natural Liquid Crystal
Polymer

Terminal Material:
Phosphor Bronze

Plating:
Sn over 50µ" (1,27 µm) Ni

RoHS Compliant:
Yes

Processing:

Lead-Free Solderable:
Yes

SMT Lead Coplanarity:
(0,20 mm) .008" max (02-16)
(0,25 mm) .010" max (17-24)



JW	NO. OF PINS	04	PLATING OPTION	S	STACK HEIGHT	POST HEIGHT	OTHER OPTION
			-T = Matte Tin		-“XXX” = Stacker Height (in inches) (0,13 mm) .005" increments Example: -250 = (6,35 mm) .250"		Leave blank for Through-hole
						-“XXX” = Post Height (in inches)	-VS = Surface Mount (2 pins/row minimum)
							-P = Pick & Place Pad (3 Pos. min.) (6,98 mm) .275" min. post height (-VS only)

02 thru 24

Note: This Series is non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC NORTHERN CALIFORNIA • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 6890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292
 SAMTEC ISRAEL • Tel: 972-3-7526600 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-6083 3766
 SAMTEC TAIWAN • Tel: 886-2-2735-6109 SAMTEC HONG KONG • Tel: 852-26904858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9580 0683