

## BOARD-TO-BOARD CONNECTOR CONTACTS



✓ Active

TE CONNECTIVITY (TE)

### 2MM HM CABLE REC CONT FORM

Z-PACK | Z-PACK 2mm HM

1376260-2

TE Internal Number: 1376260-2

EU RoHS Compliant

EU ELV Compliant

Contact Type Receptacle, Socket

Contact Mating Area Plating Material Gold

Wire Range .05 – .12 mm<sup>2</sup> [ 30 – 26 AWG ]

PCB Mount Retention Without

Body Style Straight

 **PRODUCT DRAWING**  
Japanese

 **3D PDF**

## DOCUMENTATION

Product Drawings

### RECEPTACLE CONTACT AMP MCC CONN

PDF [\(TIFF AVAILABLE\)](#)

Japanese

CAD Files

### 3D PDF

PDF

### 3D

### Customer View Model

2D\_DXF.ZIP

English

## Customer View Model

3D\_IGS.ZIP

English

## Customer View Model

3D\_STP.ZIP

English

---

Product Specifications

Application Specification

## Crimping Of AMP METRIC CRIMP CABLE (MCC)

PDF

Japanese

## Crimping Of AMP METRIC CRIMP CABLE (MCC)

TIF

Japanese

Product Specification

## AMP-Metric Crimp Cable Connector

TIF

English

## AMP-Metric Crimp Cable Connector

PDF

English

## Application Specification For 2.0mm,2.5mm Pitch WTB CONNECTOR

TIF

Japanese

## Application Specification For 2.0mm,2.5mm Pitch WTB CONNECTOR

PDF

Japanese

---

## FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

---

Product Type Features

**Connector & Contact Terminates To** Wire & Cable

**Product Type** Contact

**With Insulation Support** Yes

**Make First / Break Last** No

**Type** MCC

---

Body Features

**Body Style** Straight

---

Contact Features

**Contact Type** Receptacle, Socket

**Contact Mating Area Plating Material** Gold

**Contact Current Rating (Max) (A)** 1

**Contact Mating Area Plating Thickness** .762  $\mu\text{m}$  [ 30  $\mu\text{in}$  ]

**Contact Style** High Current

**Contact Base Material** Phosphor Bronze

---

#### Termination Features

**Termination End Plating Thickness** .76  $\mu\text{m}$  [ 30  $\mu\text{in}$  ]

**Termination End Plating Material** Gold

**Interface Type** 2mm HM

---

#### Mechanical Attachment

**PCB Mount Retention** Without

---

#### Dimensions

**Wire Range** .05 – .12  $\text{mm}^2$  [ 30 – 26 AWG ]

---

#### Usage Conditions

**Operating Temperature Range (°C)** -20 – 85

---

#### Operation/Application

**For Use With** Cable Connectors

---

#### Packaging Features

**Packaging Method** Reel

**Packaging Quantity** 15000

---

#### Other

**Comment** For Applicator

---

### PRODUCT COMPLIANCE



#### Statement of Compliance

#### **Statement of Compliance**

PDF

---