



ARRANGEMENT OF CONTACTS								SPECIFICATIONS	
PARTS	B2001-3P	B2001-4P	B2001-5P	B2001-6P	B2001-7P	B2001-8P	B2001-9P	Contact resistance	
ANGLE	180°	216°	180°	240°	240°	270°	270°	20M Ω max	
POSITION OF VIEWS								Dielectric strength	
								1,000V AC/R.M.G.	
								Insulation resistance	
								100M Ω min. at 500V DC	
								TEMP.	
								100V AC 24	



4	DRAWING FILE	1	800-H (LPC)	CONV-10	WIRL	5-6/7
3	CONTACT TERMINAL	6	200-H (LPC)	CONV-10	WIRL	5-6/7
2	PLASTIC CORE	1	ASS.	[7770]	BLACK	SLK
1	MAIN BODY	1	800-H (LPC)	CONV-10	WIRL	5-6/7
P/A	PART NAME	QTY	MATERIAL	PLATING	REMARKS	

DRAWN	KID	APP'D	UNIT	PP	TOLERANCE
CHK'D			SCALE	1:1	W. ± 0.20 H. ± 0.20 R. ± 0.25 A. ± 0.25



CIC Components

TITLE	B2001-6P METAL DIN CIRCULAR SOCKET			DRW
PART NO.	B2001-6P	INS. NO.	METAL DIN	1:1