

# SCHRACK MINIATURE POWER PCB RYII & RYII REFLOW SOLDERABLE

## GENERAL PURPOSE RELAYS PCB RELAYS

### INTRODUCTION

TE Connectivity (TE)'s Miniature Power PCB Relays RYII & RYII reflow is general purpose relay designed for various types of loads (e.g., resistive, inductive) with low component height. The relay is designed as 1 pole 8A with different contact variants: 1 form C (CO) or 1 form A (NO) or 1 form B (NC) contact.


Other advantages include: high initial dielectric strength, reinforced insulation (protection class II) and the possibility of the relay to use for the reflow-solderable process.

### FEATURES

- 1 pole 8A, 1 form C (CO) or 1 form A (NO) or 1 form B (NC) contact
- Low component height 12.3mm
- 5kV/8mm coil-contact
- Reinforced insulation (protection class II)
- Pinnings: 3.2mm and 5mm
- Reflow-solderable version
- Especially suitable for resistive and inductive loads on form A (NO) and form B (NC) contacts
- Plastic materials according to IEC 60335-1 (domestic appliances)

### APPLICATIONS

- Heating control
- Interface technology
- Domestic appliances
- Timers
- Temperature control



### APPROVALS

- VDE Cert. No. 40009639
- UL E214025

Technical data of approved types on request



# SCHRACK Miniature Power PCB RYII & RYII Reflow Solderable

General Purpose Relays


## CONTACT DATA

|                                              |                                                       |
|----------------------------------------------|-------------------------------------------------------|
| Contact arrangement                          | 1 form C (CO) or<br>1 form A (NO) or<br>1 form B (NC) |
| Rated voltage                                | 250VAC                                                |
| Max. switching voltage                       | 400VAC                                                |
| Rated current                                | 8A                                                    |
| Breaking capacity max.                       | 2000VA                                                |
| Contact material                             | AgNi0.15, AgSnO <sub>2</sub>                          |
| Frequency of operation,<br>with/without load | 6/1200min-1                                           |
| Operate/release time max.                    | 9/5ms                                                 |
| Bounce time max., form A/form B              | 6/10ms                                                |


## CONTACT RATINGS

| Type                             | Contact        | Load                                  | Cycles              |
|----------------------------------|----------------|---------------------------------------|---------------------|
| <b>IEC61810</b>                  |                |                                       |                     |
| RY531                            | A (NO)         | 8A, 250VAC, 70°C                      | 100x10 <sup>3</sup> |
| RY211                            | A (NO)         | 8A, 250VAC, 75°C                      | 100x10 <sup>3</sup> |
| RY211                            | A (NO)         | 8A, 250VAC, 85°C                      | 50x10 <sup>3</sup>  |
| RY211                            | B (NC)         | 8A, 250VAC, 70°C                      | 50x10 <sup>3</sup>  |
| <b>UL61810-1 (UL508)</b>         |                |                                       |                     |
| RY211                            | A/B<br>(NO/NC) | 10A, 250VAC, general<br>purpose, 70°C | 30x10 <sup>3</sup>  |
| RY211                            | A (NO)         | 1/2hp, 240VAC, 85°C                   | 30x10 <sup>3</sup>  |
| RY211                            | B (NC)         | B300, 70°C                            | 6x10 <sup>3</sup>   |
| RY211                            | A (NO)         | 8A, 250VAC, 85°C                      | 100x10 <sup>3</sup> |
| RY211                            | A (NO)         | 8A, 24VDC, 85°C                       | 30x10 <sup>3</sup>  |
| RY211                            | A (NO)         | B300, 85°C                            | 30x10 <sup>3</sup>  |
| RY211                            | A (NO)         | C300, 105°C                           | 30x10 <sup>3</sup>  |
| RY211                            | A (NO)         | 1/3 hp, 250VAC, 85°C                  | 30x10 <sup>3</sup>  |
| RY211                            | A (NO)         | 1/4 hp, 120VAC, 70°C                  | 30x10 <sup>3</sup>  |
| <b>EN60730-1</b>                 |                |                                       |                     |
| RY211                            | A/B<br>(NO/NC) | 6(4)A, 250VAC, 85°C                   | 100x10 <sup>3</sup> |
| RY211                            | A (NO)         | 8(4)A, 250VAC, 75°C                   | 50x10 <sup>3</sup>  |
| RY211                            | A (NO)         | 8(4)A, 250VAC, 85°C                   | 30x10 <sup>3</sup>  |
| RY211                            | A (NO)         | 2(2)A, 250VAC,<br>-40 / +105°C        | 100x10 <sup>3</sup> |
| RY211                            | C (CO)         | 2(2)A, 250VAC,<br>-40 / +105°C        | 30x10 <sup>3</sup>  |
| Mechanical endurance,<br>DC coil |                | 30x10 <sup>6</sup> operations         |                     |

## MAX. DC LOAD BREAKING CAPACITY



## ELECTRICAL ENDURANCE



# SCHRACK Miniature Power PCB RYII & RYII Reflow Solderable

## General Purpose Relays

### COIL DATA

|                            |            |
|----------------------------|------------|
| Coil voltage range         | 5 to 60VDC |
| Operative range, IEC 61810 | 2          |


### COIL VERSIONS, DC COIL

| Coil code | Rated voltage VDC | Operate voltage VDC | Release voltage VDC | Coil resistance $\Omega \pm 10\%$ | Rated coil power mW |
|-----------|-------------------|---------------------|---------------------|-----------------------------------|---------------------|
| 005       | 5                 | 3.5                 | 0.5                 | 112                               | 223                 |
| 006       | 6                 | 4.2                 | 0.6                 | 162                               | 222                 |
| 009       | 9                 | 6.3                 | 0.9                 | 320                               | 253                 |
| 012       | 12                | 8.4                 | 1.2                 | 627                               | 230                 |
| 024       | 24                | 16.8                | 2.4                 | 2350                              | 245                 |
| 048       | 48                | 33.6                | 4.8                 | 9391                              | 245                 |
| 060       | 60                | 42.0                | 6.0                 | 14000                             | 257                 |

All figures are given for coil without pre energization, at ambient temperature +23°C.

Other coil voltages on request.

### COIL OPERATING RANGE DC



### INSULATION DATA

|                                    |                      |
|------------------------------------|----------------------|
| Initial dielectric strength        |                      |
| Between open contacts              | 1000V <sub>rms</sub> |
| Between contact and coil           | 5000V <sub>rms</sub> |
| Clearance/creepage                 |                      |
| Between contact and coil           | ≥8/8mm               |
| Material group of insulation parts | IIIa                 |
| Tracking index of relay base       | PTI250               |
| Reflow-solderable version          | PTI175               |

### OTHER DATA

|                                      |                                                                                                                                                                                                                    |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material compliance                  | EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at <a href="http://www.te.com/customer-support/rohssupportcenter">www.te.com/customer-support/rohssupportcenter</a> |
| Ambient temperature                  | -40 to +70°C<br>+85°C at 6A                                                                                                                                                                                        |
| Category of environmental protection |                                                                                                                                                                                                                    |
| IEC 61810                            | RTII - flux proof<br>RTIII - wash tight <sup>1)</sup>                                                                                                                                                              |
| Vibration resistance (functional)    |                                                                                                                                                                                                                    |
| Form A (NO) / form B (NC)            | 20/5g                                                                                                                                                                                                              |

### OTHER DATA CONTINUED

|                                  |                                          |
|----------------------------------|------------------------------------------|
| Shock resistance (functional)    |                                          |
| Form A (NO) / form B (NC)        | 20/5g                                    |
| Shock resistance (destructive)   | 100g                                     |
| Terminal type                    | PCB-THT, PCB-THR                         |
| Weight                           | 8 g                                      |
| Resistance to soldering heat THT |                                          |
| IEC 60068-2-20                   | RTII: 270°C/10s<br>RTIII: 260°C/5s       |
| Resistance to soldering heat THR |                                          |
| IEC 60068-2-58                   | 250°C, no infrared heating allowed       |
| Packaging/unit                   |                                          |
| standard version                 | tube/20 pcs., box/500 pcs.               |
| reflow version                   | reel/280 pcs.<br>box/1120 pcs. (4 reels) |


1) not available as reflow-solderable version

# SCHRACK Miniature Power PCB RYII & RYII Reflow Solderable

General Purpose Relays


## DIMENSIONS

Pinning 3.2 mm



2) Values in brackets are valid for reflow-solderable version


Pinning 5 mm





## PCB LAYOUT / TERMINAL ASSIGNMENT

Bottom view on solder pins

1 form C (CO) contact, 3.2 mm




1 form A (NO), 1 form B (NC) contact 5 mm




# SCHRACK Miniature Power PCB RYII & RYII Reflow Solderable

General Purpose Relays


## SOLDERING PROFILE FOR REFLOW-SOLDERABLE VERSION



## TAPE DIMENSIONS




## REEL DIMENSIONS



# SCHRACK Miniature Power PCB RYII & RYII Reflow Solderable

General Purpose Relays

## PRODUCT CODE STRUCTURE



## PRODUCT INFORMATION

| Product code | Version                      | Contacts                  | Contact material         | Coil  | TE Part Number              |
|--------------|------------------------------|---------------------------|--------------------------|-------|-----------------------------|
| RY211005     | Pinning 3.2 mm<br>flux proof | 1 form C,<br>1 CO contact | AgNi 0.15                | 5VDC  | <a href="#">4-1393224-2</a> |
| RY211006     |                              |                           |                          | 6VDC  | <a href="#">4-1393224-3</a> |
| RY211012     |                              |                           |                          | 12VDC | <a href="#">4-1393224-6</a> |
| RY211024     |                              |                           |                          | 24VDC | <a href="#">4-1393224-9</a> |
| RY211048     |                              |                           |                          | 48VDC | <a href="#">5-1393224-1</a> |
| RY212005     |                              |                           | AgNi 0.15<br>gold plated | 5VDC  | <a href="#">5-1393224-2</a> |
| RY212006     |                              |                           |                          | 6VDC  | <a href="#">5-1393224-3</a> |
| RY212012     |                              |                           |                          | 12VDC | <a href="#">5-1393224-5</a> |
| RY212024     |                              |                           |                          | 24VDC | <a href="#">5-1393224-8</a> |
| RY212048     |                              |                           |                          | 48VDC | <a href="#">5-1393224-9</a> |
| RY213005     |                              |                           | AgSnO <sub>2</sub>       | 5VDC  | <a href="#">6-1393224-0</a> |
| RY213006     |                              |                           |                          | 6VDC  | <a href="#">9-1393224-0</a> |
| RY213012     |                              |                           |                          | 12VDC | <a href="#">6-1393224-1</a> |
| RY213024     |                              |                           |                          | 24VDC | <a href="#">6-1393224-2</a> |
| RY213048     |                              |                           |                          | 48VDC | <a href="#">6-1393224-3</a> |

## SCHRACK Miniature Power PCB RYII & RYII Reflow Solderable

### General Purpose Relays

| Product code | Version                      | Contacts                    | Contact material          | Coil                        | TE Part Number              |
|--------------|------------------------------|-----------------------------|---------------------------|-----------------------------|-----------------------------|
| RY531005     | Pinning 5 mm<br>flux proof   | 1 form A,<br>1 NO contact   | AgNi 0.15                 | 5VDC                        | <a href="#">7-1393224-6</a> |
| RY531006     |                              |                             |                           | 6VDC                        | <a href="#">7-1393224-7</a> |
| RY531012     |                              |                             |                           | 12VDC                       | <a href="#">7-1393224-9</a> |
| RY531024     |                              |                             |                           | 24VDC                       | <a href="#">8-1393224-2</a> |
| RY531048     |                              |                             |                           | 48VDC                       | <a href="#">8-1393224-3</a> |
| RY532012     |                              |                             | AgNi 0.15<br>gold plated  | 12VDC                       | <a href="#">8-1393224-4</a> |
| RY532024     |                              |                             |                           | 24VDC                       | <a href="#">8-1393224-5</a> |
| RY533006     |                              |                             | AgSnO <sub>2</sub>        | 6VDC                        | <a href="#">8-1393224-6</a> |
| RY533012     |                              |                             |                           | 12VDC                       | <a href="#">8-1393224-8</a> |
| RY533024     |                              |                             |                           | 24VDC                       | <a href="#">8-1393224-9</a> |
| RY533048     |                              |                             |                           | 48VDC                       | <a href="#">9-1393224-0</a> |
| RY611005     | Pinning 3.2 mm<br>wash tight | 1 form C,<br>1 CO contact   | AgNi 0.15                 | 5VDC                        | <a href="#">1-1393225-7</a> |
| RY611006     |                              |                             |                           | 6VDC                        | <a href="#">1-1393225-8</a> |
| RY611012     |                              |                             |                           | 12VDC                       | <a href="#">1-1393225-9</a> |
| RY611024     |                              |                             |                           | 24VDC                       | <a href="#">2-1393225-1</a> |
| RY611048     |                              |                             |                           | 48VDC                       | <a href="#">2-1393225-2</a> |
| RY612005     |                              |                             | AgNi 0.15<br>gold plated  | 5VDC                        | <a href="#">2-1393225-3</a> |
| RY612006     |                              |                             |                           | 6VDC                        | <a href="#">2-1393225-4</a> |
| RY612012     |                              |                             |                           | 12VDC                       | <a href="#">2-1393225-6</a> |
| RY612024     |                              |                             |                           | 24VDC                       | <a href="#">2-1393225-9</a> |
| RY612048     |                              |                             |                           | 48VDC                       | <a href="#">3-1393225-0</a> |
| RY613005     |                              |                             | AgSnO <sub>2</sub>        | 5VDC                        | <a href="#">5-1419136-2</a> |
| RY613012     |                              |                             |                           | 12VDC                       | <a href="#">3-1393225-1</a> |
| RY613024     |                              |                             |                           | 24VDC                       | <a href="#">3-1393225-3</a> |
| RY613048     |                              |                             |                           | 48VDC                       | <a href="#">3-1393225-4</a> |
| RY631024     |                              |                             | 1 form A,<br>1 NO contact | AgNi 0.15                   | 24VDC                       |
| RYA31005     | 5VDC                         | <a href="#">1393224-7</a>   |                           |                             |                             |
| RYA31006     | 6VDC                         | <a href="#">1393224-8</a>   |                           |                             |                             |
| RYA31012     | 12VDC                        | <a href="#">1393224-9</a>   |                           |                             |                             |
| RYA31024     | 24VDC                        | <a href="#">1-1393224-2</a> |                           |                             |                             |
| RYA31048     | 48VDC                        | <a href="#">1-1393224-3</a> |                           |                             |                             |
| RYA32005     | AgNi 0.15<br>gold plated     | 5VDC                        |                           | <a href="#">1-1393224-4</a> |                             |
| RYA32006     |                              | 6VDC                        |                           | <a href="#">8-1393224-8</a> |                             |
| RYA32012     |                              | 12VDC                       |                           | <a href="#">1-1393224-6</a> |                             |
| RYA32024     |                              | 24VDC                       |                           | <a href="#">1-1393224-8</a> |                             |
| RYA33005     | AgSnO <sub>2</sub>           | 5VDC                        |                           | <a href="#">1-1393224-9</a> |                             |
| RYA33024     |                              | 24VDC                       |                           | <a href="#">2-1393224-1</a> |                             |

| Product code | Version                                          | Contacts               | Contact material | Coil  | Part Number                 |
|--------------|--------------------------------------------------|------------------------|------------------|-------|-----------------------------|
| RY211005R    | pinning 3.2mm<br>flux proof reflow<br>solderable | 1 form C, 1 CO contact | AgNi 0.15        | 5VDC  | <a href="#">1-1956170-2</a> |
| RY211012R    |                                                  |                        |                  | 12VDC | <a href="#">1-1956170-6</a> |
| RY211024R    |                                                  |                        |                  | 24VDC | <a href="#">1956164-1</a>   |
| RY531005R    | pinning 5.0mm<br>flux proof reflow<br>solderable | 1 form A, 1 NO contact |                  | 5VDC  | <a href="#">1-1956171-1</a> |
| RY531012R    |                                                  |                        |                  | 12VDC | <a href="#">1-1956171-4</a> |
| RY531024R    |                                                  |                        |                  | 24VDC | <a href="#">1-1956171-7</a> |

**te.com**

©2025 TE Connectivity Plc. family of companies. All Rights Reserved.

TE Connectivity, SCHRACK, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any changes to the information contained herein without prior notice. TE Connectivity assumes only those obligations set forth in the terms and conditions for this product and shall in no event be liable for any incidental, indirect, or consequential damages arising out of the sale, resale, use, or misapplication of the product. TE expressly disclaims any implied warranties with respect to the information contained herein, including, but not limited to, implied warranties of merchantability or fitness for a particular purpose. Dimensions, specifications and/or information contained herein are for reference purposes only and are subject to change without notice. Consult TE for the latest dimensions, specifications and/or information. Users of TE Connectivity products must make their own assessment as to whether the respective product is suitable for the respective desired application.

04/25 ED